1-1-2005

Computational analysis on proton exchange membrane fuel cell technology

Hao Wu
Ryerson University

Follow this and additional works at: <http://digitalcommons.ryerson.ca/dissertations>

Part of the [Mechanical Engineering Commons](#)

Recommended Citation

Wu, Hao, "Computational analysis on proton exchange membrane fuel cell technology" (2005). *Theses and dissertations*. Paper 271.

This Thesis is brought to you for free and open access by Digital Commons @ Ryerson. It has been accepted for inclusion in Theses and dissertations by an authorized administrator of Digital Commons @ Ryerson. For more information, please contact bcameron@ryerson.ca.

COMPUTATIONAL ANALYSIS ON PROTON EXCHANGE MEMBRANE FUEL CELL TECHNOLOGY

by

Hao Wu

B.Eng., Northwestern Polytechnical University, Xi'an, China, 1998

A Thesis

presented to Ryerson University

in partially fulfillment of the

requirements for the degree of

Master of Applied Science

in

Mechanical Engineering

Toronto, Ontario, Canada, 2005

©Hao Wu, 2005

PROPERTY OF
RYERSON UNIVERSITY LIBRARY

UMI Number: EC53674

INFORMATION TO USERS

The quality of this reproduction is dependent upon the quality of the copy submitted. Broken or indistinct print, colored or poor quality illustrations and photographs, print bleed-through, substandard margins, and improper alignment can adversely affect reproduction.

In the unlikely event that the author did not send a complete manuscript and there are missing pages, these will be noted. Also, if unauthorized copyright material had to be removed, a note will indicate the deletion.

UMI Microform EC53674

Copyright 2009 by ProQuest LLC

All rights reserved. This microform edition is protected against unauthorized copying under Title 17, United States Code.

ProQuest LLC
789 East Eisenhower Parkway
P.O. Box 1346
Ann Arbor, MI 48106-1346

I hereby declare that I am the sole author of this thesis.

I authorize Ryerson University to lend this thesis to other institutions or individuals for the purpose of scholarly research.

I further authorize Ryerson University to reproduce this thesis by photocopying or by other means, in total or in part, at the request of other institutions or individuals for the purpose of scholarly research.

Ryerson University requires the signatures of all persons using or photocopying this thesis.

Please sign below, and give address and date.

Computational Analysis on Proton Exchange Membrane Fuel Cell Technology

A thesis for the degree of
Master of Applied Science, 2005

by

Hao Wu

Department of Mechanical and Industrial Engineering
Ryerson University

Abstract

In proton-exchange membrane fuel cells, it is particularly important to maintain appropriate water content and temperature in the electrolyte membrane. Taking into account the diffusion of water, the pressure variation, and the electro-osmotic drag in the membrane and using an empirical relationship between electro-osmotic drag and water content, a transport equation for membrane water molar concentration was obtained, and a new equation for the electric potential that strictly accounts for variable water contents was derived. The new potential equation is more accurate than the conventionally employed Laplace's equation.

A number of numerical simulations are performed for comparing the new model with other results obtained computationally or experimentally. The relationship between the humidity in fuel cell and the electric potential loss within the membrane is also investigated at different nominal current densities. The impact and importance of three-dimensionality, relative humidity, temperature, and pressure non-uniformity are assessed and discussed.

Acknowledgements

The computational model presented in this thesis is based mainly on Dr. Jun Cao's previous work. I am very grateful to Dr. Jun Cao for giving me the opportunity to work on such an exciting project and for his constant encouragement and valuable guidance throughout this study.

This work is funded by the National Science and Engineering Research Council of Canada.

Table of Contents

Abstract.....	iv
Acknowledgements	v
Table of Contents	vi
List of Tables.....	x
List of Figures	xi
Nomenclature.....	xvi
Chapter 1. Introduction.....	1
1.1. Background.....	1
1.2. Operation Principle of a PEM Fuel Cell	3
1.3. Fuel Cell Components	4
1.3.1. Polymer Electrolyte Membrane.....	4
1.3.2. Catalyst Layer.....	5
1.3.3. Gas Diffusion Electrodes.....	6
1.3.4. Bipolar Plate	7
1.4. Fuel Cell Electrochemistry and Performance.....	8
1.4.1. Gibb's Free Energy Change and Cell Potential: the Nernst Equation.....	8
1.4.2. Fuel Cell Performance.....	9
1.5. Literature Review	12

1.6. Thesis Objective	16
Chapter 2. Two-Dimensional Model of PEM Fuel Cell.....	17
2.1. Introduction	17
2.2. Modeling Domain and Geometry.....	17
2.3. Assumptions	18
2.4. Modeling equations	20
2.4.1. Computational Sub-domain I (Bulk fluid flow)	20
2.4.2. Computational Sub-domain II (Stefan-Maxwell transport).....	21
2.4.3. Computational Sub-domain III (Heat transfer of gases)	24
2.4.4. Computational Sub-domain IV (Heat transfer in solid MEA)	25
2.4.5. Computational Sub-domain V (Water transport)	26
2.4.6. Computational Sub-domain VI (Proton transport)	28
2.5. Boundary Conditions.....	31
2.6. Computational Procedure	36
2.7. Modeling Parameters.....	40
Chapter 3. Base Case Results and Parametric Study.....	46
3.1. Validation Comparisons	46
3.2. Base Case Results.....	49
3.2.1. Velocity Profiles.....	50
3.2.2. Reactants Distribution	51

3.2.3.	Current Density Distribution	53
3.2.4.	Temperature Distribution.....	55
3.2.5.	Water Content in Membrane	58
3.2.6.	Membrane Potential Loss.....	59
3.3.	Parametric Study.....	63
3.3.1.	Effect of Partial Humidification	63
3.3.2.	Effect of Pressure Loading	66
3.3.3.	Effect of Temperature	69
Chapter 4.	Three-Dimensional Model of PEM Fuel Cell	73
4.1.	Modeling Domain and Geometry.....	73
4.2.	Assumptions	74
4.3.	Modeling Equations	74
4.4.	Boundary Conditions.....	75
4.5.	Modeling Parameters.....	75
4.6.	Results and Analysis.....	76
4.6.1.	Reactants Distribution	76
4.6.2.	Temperature Distribution.....	82
4.6.3.	Current Density Distribution	87
4.6.4.	Water Content and Potential loss inside Membrane.....	88
4.6.5.	Polarization Curve	92

Chapter 5. Conclusions and Outlook.....	94
5.1. Conclusions	94
5.2. Contributions	94
5.3. Recommendations	95
References.....	96

List of Tables

Table 2-1 Physical dimension of the PEM fuel cell (refer to Figure 2.1).....	40
Table 2-2 Operational parameters at base case conditions	41
Table 2-3 Source terms for momentum, species, and energy equations in various regions.....	42
Table 2-4 Electrode properties.....	43
Table 2-5 Binary diffusivities at 1 atm and reference temperatures.....	44
Table 2-6 Transport properties and physical parameters of the membrane.....	45
Table 3-1 Variation of exchange current density with temperatures at 3atm.....	71
Table 4-1 Complementary parameters for 3D model.....	76

List of Figures

Figure 1.1 Operating scheme of a PEM fuel cell (Courtesy of U.S. Department of Energy)	3
Figure 1.2 Typical polarization curve and predominant loss mechanisms of a PEMFC	10
Figure 2.1 Schematic illustration of computational sub-domains	17
Figure 2.2 Schematic illustration of boundary numbering	31
Figure 2.3 Mesh of the computational domain	37
Figure 2.4 Flow chart of the solution procedure	39
Figure 3.1 Comparison of polarization curves between numerical model and experiments [56]	46
Figure 3.2 Different potential loss mechanisms	48
Figure 3.3 Comparison of power density between numerical and experiment results [56]	49
Figure 3.4 Velocity profile in the fuel cell (upper) and cross section velocity profile at $x=0.0125\text{m}$ (lower) (Refer to Figure 2.1 for coordinate system)	50
Figure 3.5 Hydrogen mass fraction in anode-side channel and GDE for three loading conditions: $0.4\text{A}/\text{cm}^2$ (top), $0.8\text{A}/\text{cm}^2$ (middle), and $1.2\text{A}/\text{cm}^2$ (bottom) (Refer to Figure 2.1 for coordinate system)	52
Figure 3.6 Oxygen mass fraction in cathode-side channel and GDE for three loading	

conditions: $0.4\text{A}/\text{cm}^2$ (top), $0.8\text{A}/\text{cm}^2$ (middle), and $1.2\text{A}/\text{cm}^2$ (bottom) (Refer to Figure 2.1 for coordinate system).....	53
Figure 3.7 Comparison of current density distributions on the two catalyst layers for three different nominal current densities	54
Figure 3.8 Temperature distribution in the cell for three loading conditions: $0.4\text{A}/\text{cm}^2$ (top), $0.8\text{A}/\text{cm}^2$ (middle), and $1.2\text{A}/\text{cm}^2$ (bottom) (Refer to Figure 2.1 for coordinate system).....	56
Figure 3.9 Temperature distribution on the cathode-side catalyst layer	57
Figure 3.10 Water content in membrane for three loading conditions: $0.4\text{A}/\text{cm}^2$ (top), $0.8\text{A}/\text{cm}^2$ (middle), and $1.2\text{A}/\text{cm}^2$ (bottom) (Refer to Figure 2.1 for coordinate system).....	59
Figure 3.11 Membrane potential loss as a percent of the total loss vs. cell current density.....	60
Figure 3.12 Comparison of the maximum and average membrane potential loss on the cathode-side boundary between the new model and the model using Laplace's equation.....	61
Figure 3.13 Potential distribution inside membrane for three loading conditions: $0.4\text{A}/\text{cm}^2$ (top), $0.8\text{A}/\text{cm}^2$ (middle), and $1.2\text{A}/\text{cm}^2$ (bottom) (Refer to Figure 2.1 for coordinate system)	62
Figure 3.14 Polarization curves corresponding to different relative humidity.....	64

Figure 3.15 Membrane potential loss vs. current density corresponding to three different humidities.....	65
Figure 3.16 Cell voltage and membrane potential loss vs. relative humidity at current density of $0.4\text{A}/\text{cm}^2$	66
Figure 3.17 Water content at the mid-section of the cell length using different model and pressure conditions corresponding to current density at $0.8\text{A}/\text{cm}^2$	67
Figure 3.18 Polarization curves corresponding to different pressure conditions	68
Figure 3.19 Air stream compositions corresponding to different working temperature ($^{\circ}\text{C}$).....	70
Figure 3.20 Water viscosity in membrane using isothermal (upper) and anisothermal (lower) models (Refer to Figure 2.1 for coordinate system)	72
Figure 4.1 Computational domain of half unit cell	73
Figure 4.2 Hydrogen mass fraction in anode gas channel and electrode for three loading conditions: $0.4\text{A}/\text{cm}^2$ (top), $0.8\text{A}/\text{cm}^2$ (middle), and $1.2\text{A}/\text{cm}^2$ (bottom) (Refer to Figure 4.1 for coordinate system).....	79
Figure 4.3 Oxygen mass fraction in cathode gas channel and electrode for three loading conditions: $0.4\text{A}/\text{cm}^2$ (top), $0.8\text{A}/\text{cm}^2$ (middle), and $1.2\text{A}/\text{cm}^2$ (bottom) (Refer to Figure 4.1 for coordinate system).....	80
Figure 4.4 Iso-line of oxygen mass fraction on channel inlet section at current density: $0.4\text{A}/\text{cm}^2$ (top left), $0.8\text{A}/\text{cm}^2$ (top right) and $1.2\text{A}/\text{cm}^2$ (bottom) (Refer to Figure	

4.1 for coordinate system)	81
Figure 4.5. Oxygen mass fraction on cathode-side catalyst layer at current density 1.2A/cm ²	81
Figure 4.6 Temperature distribution inside the cell for three loading conditions: 0.4A/cm ² (top), 0.8A/cm ² (middle), and 1.2A/cm ² (bottom) (Refer to Figure 4.1 for coordinate system)	84
Figure 4.7 Temperature distribution on cathode-side catalyst layer for three loading conditions: 0.4A/cm ² (top), 0.8A/cm ² (middle), and 1.2A/cm ² (bottom)	85
Figure 4.8 Temperature distribution of infinite dimension stack modeling at current density 1.2A/cm ² , slice plot (upper), tetrahedron plot (lower) (Refer to Figure 4.1 for coordinate system)	86
Figure 4.9 Temperature distribution on cathode-side catalyst layer of infinite dimension stack modeling at current density 1.2A/cm ²	86
Figure 4.10 Dimensionless current density distribution i/i_{ave} on cathode-side catalyst layer for three loading conditions: 0.4A/cm ² (top), 0.8A/cm ² (middle), 1.2A/cm ² (bottom)	88
Figure 4.11 Water content in membrane for three loading conditions: 0.4A/cm ² (top), 0.8A/cm ² (middle), and 1.2A/cm ² (bottom) (Refer to Figure 4.1 for coordinate system)	90
Figure 4.12 Potential distribution inside membrane for three loading conditions:	

0.4A/cm ² (top), 0.8A/cm ² (middle), and 1.2A/cm ² (bottom) (Refer to Figure 4.1 for coordinate system)	91
Figure 4.13 Comparison of maximum potential losses using different mathematical models.....	92
Figure 4.14 Comparison of polarization curves using different models	93

Nomenclature

A_{MEA}	Full active MEA area	m^2
a	Chemical activity	-
b	Tafel slope	V/dec
C	Electric charge	Coulomb
c	Concentration	mol/m^3
c_p	Specific heat capacity at constant pressure	$J/(kg^\circ C)$
D	Diffusion coefficient	m^2/s
d	Diffusional driving force	N
E	Cell potential	V
E_m	Equivalent membrane weight	kg/mol
e	Membrane constant	mol/m^3
F	Faraday's constant	96487 Coulomb/mol
F	Volume force field	N
f	Swelling coefficient of membrane	-
G	Gibb's free energy	J
H	Enthalpy	J
i	Current density	A/m^2
i_0	Exchange current density	A/m^2
J	Mass flux through diffusion	$kg/(m^2 \cdot s)$
K	Chemical equilibrium constant	-
k	Membrane conductivity	$A/(V \cdot m)$
k_ϕ	Electric permeability	m^2
k_h	Hydraulic permeability	m^2

k_p	Permeability of electrode/membrane	m^2
M	Molecular weight	kg/mol
N	Molar flux	$\text{mol/ (m}^2\text{s)}$
n	Molar number of electrons transferred	-
$\mathbf{n}$	Normal unit vector	-
$\tilde{n}$	Mass flux of species	$\text{kg/ (m}^2\text{s)}$
n_d	Electro-osmotic drag coefficient	-
P	Pressure	Pa
Q	Heat source	J/m^2
R	Universal gas constant	$8.3145 \text{ J/(mol}\cdot\text{K)}$
S	Mass source/sink	$\text{kg/(m}^3\text{s)}$
S	Entropy	J
s	Specific entropy	$\text{J/(mol}\cdot\text{K)}$
T	Temperature	K
$\mathbf{U}$	Velocity vector	m/s
u	x - component of $\mathbf{U}$	m/s
v	y - component of $\mathbf{U}$	m/s
ν	Stoichiometric coefficients	-
x	Molar fraction	mol/m^3
x	x axis	m
y	y axis	m
Z	Charge number	-
z	z axis	m

Greek Symbols

α	Relative humidity	-
α	Transfer coefficient	-
β	Heat transfer coefficient	W/(m ³ K)
γ	Concentration coefficient	-
ε	Porosity	-
ε_w^m	Volume fraction of water	-
η	Overpotential	V
η	Dynamic viscosity	kg/(m ² s)
λ	Thermal conductivity	W/(m·K)
λ	Membrane water content	-
μ	Viscosity	kg/(m·s)
ρ	Density	kg/m ³
ω	Mass fraction	-
ϕ	Electric potential	V

Subscripts/Superscripts

O_a	Anode
O_{act}	Activation
O_{bp}	Bipolar plate
O_c	Cathode
O_{conc}	Concentration
O_e	Equilibrium state
O_f	Fixed charge
O_g	Gas phase
O_i	<i>i</i>). Internal, <i>ii</i>). species <i>i</i> ;
O_{ij}	Gas pair <i>i, j</i> in a mixture
O_{mem}	Membrane
O_l	<i>i</i>). Liquid phase, <i>ii</i>). Limiting current density;
O_{ohm}	Ohmic
O_p	Proton
O_{rev}	Reversible
O_s	Solid phase
O_w	Water
O_0	Reference conditions
O^{eff}	Effective value of parameter
O^{ref}	Reference value
O^{sat}	Saturation state
O^T	Thermal
O^0	Standard state

Chapter 1. Introduction

1.1. Background

A fuel cell is an electrochemical device that converts the energy of fuel-oxidant chemical reactions into electricity. It differs from a battery in that the fuel and oxidant are stored external to the cell, which can generate power as long as the fuel and oxidant are supplied. Fuel cells are usually classified by the type of electrolyte employed. Some common types of fuel cells are proton exchange membrane (also called polymer electrolyte membrane) fuel cell (PEMFC), solid oxide fuel cell (SOFC), alkaline fuel cell (AFC), direct methanol fuel cells (DMFC), phosphoric-acid fuel cell (PAFC), and molten carbonate fuel cell (MCFC). Some types of fuel cells work well for use in stationary power generation plants. Others may be useful for small portable applications or for powering vehicles. Among them, the PEM fuel cell is one of the most promising fuel cell types for widespread use and it will be the focus of this study.

PEM fuel cells convert hydrogen (fuel) and oxygen (oxidant) directly to electrical energy with by-products of water and heat only. Compared to the internal combustion engines, PEM fuel cells are exceptionally fuel-efficient. They convert nearly three times more energy from the fuel into usable power than the conventional automobile power system does. Other advantages of the PEM fuel cell include quiet operation, quick startup,

simple design and, of top importance, zero emissions, which directly leads to the reduction of air pollution and the greenhouse effect. All these advantages make it the prime candidate for automotive applications, as well as applications such as the cell phone or the laptop.

In extensive commercialization of PEM fuel cells, there are still a few hurdles to be overcome. Actually, the manufacturing of commercial PEM fuel cells today costs about 10 times more than that for internal combustion engine power plants. Another big challenge for PEM fuel cell applications is the generation and storage of hydrogen, which requires additional equipments and, thus, will further increase the cost. To reduce the cost, great efforts have been made to develop less expensive catalysts, new materials, and novel fabrication techniques. Another good way to reduce the cost is through engineering optimization, which requires a better understanding of the PEMFC's operation mechanism and the effect of various parameters on the PEMFC performance. Optimization can be performed experimentally or numerically. Though prototyping is an ideal method for fuel cell research, the prototyping implementation is fairly expensive and usually has limitations in revealing the details of transport phenomena occurring inside the fuel cell. Alternatively, numerical simulation of fuel cell operation is more cost effective and easier to implement when working conditions or material properties change; this strategy is also capable of producing detailed information of the underlying fuel cell working mechanism. In this thesis, accounting for the effects corresponding to variations of temperature as well as pressure, both two-dimensional and three-dimensional numerical models will be presented for a single

PEM fuel cell.

1.2. Operation Principle of a PEM Fuel Cell

Figure 1.1 illustrates the operational principle of a PEM fuel cell. Pure hydrogen or reformed hydrogen gas enters the anode channel and diffuses through the porous anode towards the platinum catalyst, where hydrogen molecules are stripped of their electrons and become positively charged hydrogen ions (protons), based on the following mechanism:

and the overall reaction is:

Here, the subscript *ads* denotes the adsorption of hydrogen ions onto the surface of platinum.

Figure 1.1 Operating scheme of a PEM fuel cell (Courtesy of U.S. Department of Energy)

Protons migrate through the membrane and the electrons travel through the external circuit to create electric current.

On the cathode side, a humidified air stream enters the cathode channel and diffuses towards the cathode-side catalyst layer. At the platinum catalyst surface, hydrogen ions recombine with electrons and oxygen molecules to produce water and heat. This reaction mechanism is more complicated and less understood. A proposed mechanism from [1] is:

here, M is the catalyst metal, the overall reaction of the above is:

Reaction (1.1) is slightly endothermic, and reaction (1.2) is strongly exothermic, so that the overall heat is generated. By combining the reactions (1.1) and (1.2), the overall reaction in the PEM fuel cell can be summarized as:

1.3. Fuel Cell Components

1.3.1. Polymer Electrolyte Membrane

The polymer electrolyte membrane (PEM) is a critical component of a working fuel cell. Its function is to conduct protons efficiently while repelling the electrons, thus making the electrons travel through the outer circuit to produce electric work. A desirable membrane in a

PEM fuel cell should possess the characteristics of high proton conductivity, good insulation of electronic, low fuel crossover properties, and it must also be robust enough to be assembled into a fuel cell stack and have high chemical and thermal stability. The most commonly used and investigated membrane material is Nafion, from Dupont, which is also the one considered in this study.

The nafion membrane belongs to a class of poly-perfluoro-sulfonic acids which consists of a hydrophobic tetrafluoroethylene backbone with pendant side chains of perfluorinated vinyl-ethers terminated by sulfonic acid groups [2]. Proton conductivity in Nafion and most other polymer electrolytes increases with the water activity. Sufficient water must be absorbed into the membrane to ionize the acid groups; whereas, excess water can flood the cathode of the fuel cell diminishing fuel cell performance and limiting the power output. Therefore, water management in the fuel cell is critical for PEM fuel cell operation, and it is one important task of this modeling study.

1.3.2. Catalyst Layer

Normally, electrochemical reactions (1.1) and (1.2) would occur very slowly at the low operating temperature of the PEM fuel cell, especially at the cathode side. In order to speed up these two reactions, the membrane is coated with a thin catalyst layer on each of the two electrode sides. The catalyst layer usually consists of microscale carbon particles, each of which can support nanoscale platinum (Pt) catalyst particles loosely embedded in a matrix of

ionomer. The ionomer microstructure and ionomer-catalyst layer interface are important factors for the performance of a fuel cell; they determine the ion exchange across the membrane that allows the fuel cell reaction to occur.

The optimum thickness of the catalyst layer is found to be around $10\ \mu\text{m}$ since almost all of the reactions occur within a $10\ \mu\text{m}$ thick layer [3]. On the other hand, electrochemical reaction is not evenly distributed over the catalyst layer; it occurs far more drastic at the electrode-catalyst interfaces than inside the layer towards the membrane; therefore, the Pt particles must be properly distributed in the catalyst to maximize the reaction efficiency and minimize the cost.

The platinum catalyst has strong affinity for CO. Therefore a common problem of the fuel cell is anode catalyst CO poisoning if the hydrogen is derived from an alcohol or hydrocarbon fuel. Developers are currently exploring platinum/ruthenium catalysts that are more resistant to CO. This problem does not exist if pure hydrogen is supplied.

1.3.3. Gas Diffusion Electrodes

Gas diffusion electrodes (GDE) consist of porous material carbon cloth or carbon fiber paper, with typical thicknesses between $100\ \mu\text{m}$ and $300\ \mu\text{m}$ [4]. They serve to provide structural support of the catalyst layer and transport the reactant gases towards the catalyst layer through its open wet-proofed pores. In addition, they provide an interface when ionization takes place and transfer electrons through the solid matrix. GDE also plays an

important role in heat removal from the reacting site. The electrodes (anode and cathode), catalyst, and polymer electrolyte membrane together form the membrane electrode assembly (MEA) of a PEM fuel cell.

1.3.4. Bipolar Plate

The most important role of the bipolar plate is to feed the reactant gases towards the GDE, and to assemble individual cells into a cell stack. Gas-flow channels are curved into bipolar plates to provide pathways for reactant gases and, in practice, straight, serpentine, or interdigitated flow fields are commonly used designs. The ratio between channel area and land area is important for any flow field. The channel area should be as large as possible to supply enough reactant gases and to reduce the cell weight and volume requirements; on the other hand, the greater the land area, the better the electrical connection between the bipolar plates and GDE, and the less contact resistance and ohmic losses. A sensible compromise between the above two factors should be sought to achieve the best possible cell performance.

The most commonly used materials in bipolar plate fabrication is graphite; it has good properties such as high electrical conductivity, high thermal conductivity, low corrosion rate, and light weight. However, it is expensive to machine the flow pathways inside graphite. Apart from graphite, metal alloy and carbon composites are also materials widely used for manufacturing bipolar plates.

1.4. Fuel Cell Electrochemistry and Performance

1.4.1. Gibb's Free Energy Change and Cell Potential: the Nernst Equation

The tendency for a reaction to reach equilibrium is driven by the Gibb's free energy, ΔG , which is defined as:

$$\Delta G = \Delta G^0 + RT \ln \left(\frac{\sum_i a_i^{v_i}}{\sum_j a_j^{v_j}} \right) \quad (1.4)$$

where a_i and a_j are activity coefficients of products and reactants, v_i and v_j are the stoichiometric coefficients, respectively, and the standard free energy change of the reaction, ΔG^0 , can be derived at the equilibrium state as $\Delta G = 0$, in the form of:

$$\Delta G^0 = -RT \ln \left(\frac{\sum_i a_{i,e}^{v_i}}{\sum_j a_{j,e}^{v_j}} \right) = -RT \ln K \quad (1.5)$$

where the subscript e 's in the activity terms indicate the values of the activities at equilibrium, and K is the equilibrium constant for this reaction.

On the other hand, the Gibb's energy can also be defined in terms of enthalpy and entropy in the form of:

$$\Delta G = \Delta H - T\Delta S \quad (1.6)$$

where ΔH and ΔS are the enthalpy change and entropy change in the system respectively.

For redox reactions, the Gibb's energy is an electric energy, which is the charge

transferred multiplied by the potential E when properly setup in an electric cell. Each mole of electrons has a charge of 1 *Faraday* (1 *Faraday*=96487 *Coulomb*), and n moles of electrons have the charge in an amount of nF . Since the voltage is usually a positive value, the Gibb's energy is then defined as:

$$\Delta G = -nFE \quad (1.7)$$

Combining equation (1.4) to (1.7) yields the common form of the so-called *Nernst equation*:

$$E_{rev} = E_{rev}^0 - \frac{RT}{nF} \ln \left(\frac{\sum_i a_i^{v_i}}{\sum_j a_j^{v_j}} \right) \quad (1.8)$$

In the case of the PEM fuel cell, the Nernst equation results in:

$$E_{rev} = E_{rev}^0 - \frac{RT}{2F} \ln \left(\frac{a_{H_2O}}{a_{H_2} a_{O_2}^{0.5}} \right) \quad (1.9)$$

where E_{rev} is the cell potential for the fuel cell, E_{rev}^0 is the cell potential in standard state.

1.4.2. Fuel Cell Performance

The fuel cell potential predicted by the Nernst equation is under the condition of the equilibrium (open circuit) state. The actual cell potential under operating conditions (i.e. when $i \neq 0$) is always smaller. Figure 1.2 shows a typical polarization curve of a PEM fuel cell, in which the difference between the top constant dash line and the bottom solid curve corresponds to the potential losses. The potential losses of a PEM fuel cell occurring during its operation can be ascribed to following factors:

(1) Fuel crossover and internal currents

In practical operation, the highly diffusive hydrogen can cross the membrane from the anode to cathode without being oxidized at the anode catalyst layer, which causes fuel crossover loss. Similarly, electrons can flow through the membrane from the anode to the cathode even when the outer circuit is disconnected, which results in the internal current loss.

Figure 1.2 Typical polarization curve and predominant loss mechanisms of a PEMFC

(2) Activation overpotential

The activation overpotential is the potential loss due to driving the electrochemical reactions from the equilibrium state. In a PEMFC, this loss occurs mainly at the cathode side, since the exchange current density i_0 of the anodic reaction is several orders of magnitude

higher than that of the cathodic reaction [5]. In most cases, the activation overpotential is described by the *Tafel equation* :

$$\eta_{act} = b \ln \frac{i}{i_0} \quad (1.10)$$

where i is the local current density and b is the Tafel-slope, which depends on the electrochemistry of the particular reaction.

(3) Ohmic losses

Ohmic losses are due to the internal resistance of the fuel cell. It is given by [6]:

$$\eta_{ohm} = i r_i \quad (1.11)$$

where r_i denotes the internal resistance. There are two types of internal resistance, one occurs due to electron transport through the electrode and bipolar plates, and the other results from the transport of protons through the membrane. Ohmic resistance also causes a heating effect of the cell, which is given by:

$$\dot{q}_{ohm} = i^2 r_i \quad (1.12)$$

(4) Mass transport losses or concentration overpotential

Concentration losses result from the change in concentration of the reactants at the surface of the catalyst layer as the reactants are being consumed. It is negligible at the anode compared to the cathode, due to the massive diffusivity of hydrogen compared to that of oxygen.

At a sufficiently high current density, the rate of oxygen consumption becomes equal to

that of oxygen diffusive supply, and no more current can be obtained from the fuel cell. This is denoted the limiting current density [7]. There are no established methods to quantify the effect of mass transport losses yet, while [7] gives an equation which relates the concentration overpotential with the limiting current, as follow:

$$\eta_{conc} = \frac{RT}{2F} \ln \left(1 - \frac{i}{i_l} \right) \quad (1.13)$$

where i_l is the limiting current density, R is the universal gas constant, and F is the Faraday's constant.

1.5. Literature Review

In the past fifteen years, the extensive study of fuel cell modeling has greatly helped to better understand the fuel cell working mechanism. Numerous researchers have focussed on different aspects of the fuel cell, and it is difficult to categorize all existing fuel cell models, since they vary in the modeling domains, component complexities, and number of dimensions. However, the general trend of fuel cell modeling efforts can be identified as: from one-dimensional to multi-dimensional, from single-phase to multi-phases, and from a single component to the entire fuel cell structure.

Mathematical modeling and computer simulation of PEMFC began with the pioneering work of Bernardi and Verbrugge as well as Springer et al. In 1991 and 1992, Bernardi and Verbrugge [8, 9] published a one-dimensional isothermal model of the gas-diffusion electrodes, the catalyst layer and membrane, providing valuable information about the

physics of the electrochemical reactions and the transport phenomena in these regions. Also in 1991, Springer et al [10, 11] published a one-dimensional isothermal model with the same domain, which was the first to account for a partially humidified membrane. In their model, the water content in the membrane had been measured experimentally as a function of relative humidity outside the membrane, and a correlation between the membrane conductivity and the humidification level of the membrane had been established. These data are also applied in this modeling work for the water transport in the membrane.

Fuller and Newman [12], Nguyen and White [13], and Yi and Nguyen [14, 15] subsequently developed pseudo-two-dimensional models accounting for compositional changes along the flow path. In their models, the MEA is greatly simplified by assuming ultra-thin gas-diffusion electrodes, and the volume of the liquid phase is assumed to be negligible. Such models are useful for small cells, while their applicability to large scale fuel cells, particularly under high fuel utilization and low humidity conditions, is limited. Nevertheless, the one-dimensional models of Bernardi and Verbrugge [8, 9] and Springer et al. [10, 11] provided a fundamental framework to build the multidimensional, multiphysics models that followed. The pseudo-two-dimensional models developed by Fuller and Newman [12], Nguyen and White [13], and later Yi and Nguyen [14, 15] further demonstrated the important roles played by water and heat management in maintaining high performance of PEMFCs. Effects of anisotropy and inhomogeneity on mass transport through GDE were also numerically investigated [16, 17].

The first model to use the methods of *Computational Fluid Dynamics* (CFD) for PEMFC modeling was published by Gurau et al. [18]. They developed a two-dimensional steady-state model of a whole fuel cell, i.e., both flow channels with MEA in between. The model considers the gas phase and the liquid phase in separate computational domains, which means that the interaction between both phases is not considered. In a separate development, Yi and Nguyen [14, 15] formulated a two-dimensional model to explore hydrodynamics and multicomponent transport in the air cathode of PEMFC with an interdigitated flow field. The concept of modeling PEMFC within CFD framework was proposed shortly thereafter. Two dimensional simulations of coupled electrochemical and transport processes were carried out using a CFD code [19], and the three-dimensional version of the same model was also demonstrated [20, 21]. Independently, Dutta et al. [22] presented three-dimensional simulation of the PEMFC using Fluent, a commercial CFD package. Subsequent work was presented in Dutta et al. [23] and Lee et al. [24]. In their model, the membrane electrode assembly (MEA) is not included in the computational domain but rather simplified as an interface without thickness. As such, water transport and ohmic potential drop across the membrane are treated using simplified linear relationships as in the early work of Nguyen and White [13].

Additional work on general purpose, fully three-dimensional models was performed by Zhou and Liu [25] using an in-house CFD code, Berning et al. [26] using the commercial package CFX, and Mazumder and Cole [27] using the commercial package CFD-ACE+.

Most recently, both STAR-CD and Fluent Packages have been applied to large-scale fuel cell modeling through their user-coding capability [28, 29].

Efforts have also been made to model two-phase flow and transport in PEMFC, a critical but difficult issue that has repeatedly been emphasized in the literature. There are generally two types of models to treat the liquid water transportation in a PEMFC. The simplest approach is a single-phase model in which the gas and liquid share the same velocity field and the interfacial tension effect is completely ignored. Most of the aforementioned modeling work falls into this category. The more rigorous approach for studying the liquid water transport is a true two-phase model in which two phases have different velocities. Meanwhile, the interfacial tension effect and GDE wettability are fully accounted for. The work of Nguyen et al. [30, 31, 32], Wang et al. [33], You and Liu [34], Mazumder and Cole [35], and Berning and Djilali [36] can be categorized as this type.

Overall, up to around 2000, most of the fuel cell models were one or two dimensional with certain simplifications and assumptions. Much effort has been expended in the last five years upon development of numerical models under a decreasing number of restrictive assumptions and with more physical complexities. Current development in the PEMFC modeling is in the direction of fully three-dimensional, electrochemical-transport-thermal coupled, two-phase, and realistic large-scale simulations.

1.6. Thesis Objective

The goal of this thesis is to develop a set of two-dimensional and three-dimensional comprehensive models that account for all important physical phenomena inside the PEM fuel cells. Transport processes of reactant gas flow, multi-species diffusion, conductive and convective heat transfer, water and proton transport, and electrochemical kinetics are investigated in detail. Specifically, a newly derived transport equation for water molar concentration in the membrane and an equation for the membrane potential loss that strictly accounts for variable water content are implemented, and the results obtained from these new equation models are validated against experimental results. Finally, the model developed in this thesis is used in a series of parametric studies to investigate the sensitivity of various operation and design parameters on the cell performance.

Chapter 2. Two-Dimensional Model of PEM Fuel Cell

2.1. Introduction

There are five primary transport phenomena during fuel cell operation, specifically, fluid flow of reactant gases, convection/diffusion of different species, heat transfer in the solids as well as in the gases, liquid water transport, and proton transport processes. These phenomena will be respectively described in detail in this chapter.

2.2. Modeling Domain and Geometry

For computation convenience, the above five transport phenomena are modeled using six computational sub-domains, as depicted in Figure 2.1:

Figure 2.1 Schematic illustration of computational sub-domains

Sub-domain I includes the whole domain. It is used to reveal the bulk fluid flow field.

Sub-domain II consists of two similar portions, which are composed of the gas channel and the electrode in each of the cathode and anode sides. It accounts for species convection/diffusion.

Sub-domain III has identical geometries as sub-domain II, but it accounts for heat transfer in gases.

Sub-domain IV covers the MEA, solid parts of a fuel cell, and it accounts for heat transfer in solids.

Sub-domain V covers the membrane only. It is used to describe liquid water transport.

Sub-domain VI covers the membrane only again, but it is used to describe proton transport.

x and y in Figure 2.1 represent the x -axis and y -axis, respectively.

2.3. Assumptions

The following assumptions will be invoked to make the model more tractable and the computation faster:

- (1) The transport processes are steady-state and two-dimensional.
- (2) The flow in the gas-distribution channels is laminar.
- (3) Gas density is assumed constant for bulk fluid flow in sub-domain I (but not in species transport sub-domain II); this approximation is well supported by the study of Dutta et al., [23] which predicts the variation range of main physical variables does

not exceed 5%.

- (4) According to Wang [37], the membrane can be considered impermeable for the gas-phase. Therefore a very small gaseous permeability is employed to make the gas concentration to be zero in the membrane.
- (5) On the cathode side, the gaseous mixture consists of O_2 , N_2 , and $H_2O_{(g)}$ only, while on the anode side, the gaseous mixture consists of H_2 , CO_2 (due to incomplete purification of the hydrogen product), and $H_2O_{(g)}$ only, all of these gases are assumed to be ideal gases.
- (6) Ohmic heating in electrodes is neglected due to their high conductivity.
- (7) Heat transfer inside the membrane is accomplished by conduction only, i.e., the enthalpy carried by the net movement of liquid water is currently omitted.
- (8) The catalyst layers are sufficiently thin to be considered as interfaces contributing only source/sink terms to the mass and heat transfer processes.
- (9) The water produced from electrochemical reaction is assumed to be in the liquid phase.
- (10) All water vapor at the surface of catalyst layer will convert to liquid water.
- (11) No phase change is taken into account for water transport within each component of the PEMFC.
- (12) Water in the membrane is in the liquid phase only, and the water pressure varies linearly in the membrane.

2.4. Modeling equations

Next, the governing equations for different physical phenomena will be described in their respective sub-domains.

2.4.1. Computational Sub-domain I (Bulk fluid flow)

Sub-domain I is used to derive the velocity profile in the whole cell. The first four assumptions are used and the flow behavior can be described by the equation of continuity:

$$\nabla \cdot (\rho \mathbf{U}) = 0 \quad (2.1)$$

and the momentum equation:

$$\rho (\mathbf{U} \cdot \nabla) \mathbf{U} = -\nabla P + \nabla \cdot \left[\eta (\nabla \mathbf{U} + (\nabla \mathbf{U})^T) \right] + \mathbf{F} \quad (2.2)$$

where η is the dynamic viscosity, ρ the constant density, $\mathbf{U}$ the velocity field, i.e., u and v in the 2D model, P the pressure, and $\mathbf{F}$ the volume force field. Equations (2.2) is often referred to as the Navier-Stokes (N-S) equations for an incompressible fluid.

The assumption of constant density yields decoupling of the flow field from the species, electric potential, and temperature fields, thereby significantly accelerating the computations. It should be noted that the traditionally used Darcy's law for velocity calculations in porous electrodes and membrane is abandoned here and the N-S equations are solved to obtain the bulk flow velocity field over the entire domain. The influences of porous zones are considered using volume force terms $\mathbf{F}$. These terms are summarized in Table 2-3 (see section 2.7).

2.4.2. Computational Sub-domain II (Stefan-Maxwell transport)

Sub-domain II accounts for multi-species convection/diffusion processes in the gas channel and porous electrodes.

Assumption 5 implies the applicability of *the state equation*, which relates density, temperature and pressure. That is, for each species i contained in the ternary system, such as the mixture of O_2 , N_2 and $H_2O_{(g)}$ in the anode side and the mixture of H_2 , CO_2 and $H_2O_{(g)}$ in the anode side, it obeys:

$$\rho_i = \frac{P_g M_i}{RT_g} \quad (2.3)$$

where M_i is the molecular weight of the species i , and R is the universal gas constant (8.314 J/(mol·K)). The relationship between the average density ρ_g and the density of each of the three components in the mixture, ρ_i , is:

$$\frac{1}{\rho_g} = \sum_{i=1}^3 \frac{\omega_i}{\rho_i} \quad (2.4)$$

where ω_i is the mass fraction of the species i in the mixture.

On the other hand, the interaction between the species of the ternary system is accounted for through the Stefan-Maxwell transport equation. This is based on the symmetric diffusivity definition proposed in [38]:

$$J_i = -D_i^T \nabla \ln T - \rho_i \sum_{j=1}^3 D_{ij} d_j \quad (2.5)$$

where J_i denotes the mass flux through diffusion of species i , D^T the thermal diffusivity, T

the temperature, D_{ij} the symmetric diffusivity, and d_j the diffusional driving forces for j . The symmetric diffusivities are related to the Stefan-Maxwell diffusivities through the expression:

$$\frac{x_i x_k}{D_{ik}} = -\omega_i \omega_k \frac{\sum_{j \neq i} (adj B_i)_{jk}}{\sum_{j \neq i} D_{ij} (adj B_i)_{jk}} \quad (2.6)$$

where x denotes the molar fraction, D the Stefan-Maxwell diffusivity, and adj the adjugate matrix of B . B is given by the equation below:

$$(B_i)_{kj} = D_{kj} - D_{ij} \quad i \neq j \quad (2.7)$$

Ultimately, the resulting mass balance for each species in the ternary system obeys the following equation:

$$\nabla \cdot \left[-\rho_g \omega_i \sum_{j=1}^N D_{ij} \left\{ \frac{M}{M_j} \left(\nabla \omega_j + \omega_j \frac{\nabla M}{M} \right) + (x_j - \omega_j) \frac{\nabla P}{P} \right\} + \omega_i \rho U + D_i^T \frac{\nabla T}{T} \right] = S_i \quad (2.8)$$

where S_i denotes the mass source ($kg/(m^2s)$) of species i , M denotes the total mole mass of the mixture; it is a function of mole fraction x :

$$M = \sum_{i=1}^n M_i x_i \quad (2.9)$$

while the molar fraction x can be related to the mass fraction by [39]:

$$x_i = \frac{\frac{\omega_i}{M_i}}{\sum_{j=1}^n \frac{\omega_j}{M_j}} \quad (2.10)$$

which can also be inverted:

$$\omega_i = \frac{x_i M_i}{\sum_{j=1}^n x_j M_j} = \frac{x_i M_i}{M} \quad (2.11)$$

This implies that the only dependant variable in equation (2.8) is the mass fraction ω , while the temperature T , pressure P , and velocity field U are obtained from other computational sub-domains.

Equation (2.8) is applied to each species except the last one, i.e., CO_2 at the anode side or N_2 at the cathode side. These two ingredients are derived from the mass conversation equation on the two sides, respectively:

$$\omega_n = 1 - \sum_{i=1}^{n-1} \omega_i \quad (2.12)$$

In practice, the mole fraction of water vapor $x_{H_2O(g)}$ is replaced by employing the saturation assumption:

$$x_{H_2O(g)} = \alpha \frac{P_g^{sat}}{P_g} \quad (2.13)$$

Here, the saturation pressure, P_g^{sat} , can be expressed using the following empirical formula [11]:

$$P_g^{sat} = 10^{-2.1794 + 0.02953(T-273) - 9.1837 \times 10^{-5}(T-273)^2 + 1.4454 \times 10^{-7}(T-273)^3} \quad (2.14)$$

P_g is the gas pressure and α is relative humidity, which is 1 if the gaseous mixture is fully humidified.

Note that the diffusivities D_{ij} in equation (2.8) have to be corrected for the porosity in porous electrode domain. This is often treated by applying the Bruggemann correction [40]:

$$D_{ij}^{Por} = D_{ij} * \varepsilon^{1.5} \quad (2.15)$$

where, ε is the gas-phase porosity of the electrode.

2.4.3. Computational Sub-domain III (Heat transfer of gases)

According to assumption 4, gas species do not appear in the membrane and the heat transfer of gases occurs in the gas channel and electrode only. This process obeys the general conduction and convection heat transfer equation:

$$\rho c_p U \cdot \nabla T_g - \nabla \cdot (\lambda_g^{eff} \nabla T_g) = Q \quad (2.16)$$

where ρ is the density, c_p the heat capacity, λ_g^{eff} the effective heat conductivity. All three parameters are overall estimation values of the gas mixture. T_g denotes the temperature of gases, and Q the heat source. In the gas channel, no heat sources present; hence, Q is equal to zero. In the porous electrodes, heat is transferred from the solid material to the gas phase, and the heat exchange can be expressed in terms of a source:

$$Q = \beta(T_s - T_g) \quad (2.17)$$

where β denotes the heat transfer coefficient ($W/(m^3K)$) which accounts for an estimated heat transfer coefficient between the solid and the gases, as well as the specific surface area per unit volume of the electrode [41]; T_s is the temperature of electrode solid, which is obtained from the next sub-domain.

2.4.4. Computational Sub-domain IV (Heat transfer in solid MEA)

Sub-domain IV is composed of membrane, two electrodes, as well as the two catalyst layers. Assumption 6, 7, and 8 are invoked in this sub-domain.

Heat transfer in this sub-domain obeys the generic heat conduction equation:

$$-\nabla \cdot (\lambda_s \cdot \nabla T_s) = Q \quad (2.18)$$

where λ_s is the thermal conductivity and, similar to equation (2.15), Q denotes the heat source.

The heat source Q has different patterns in different solid domains. In the electrode, heat transfers from solid to gases; therefore, Q is present as a heat sink, and its value is numerically equal to the heat source in the gaseous equation, but with a negative sign:

$$Q = -\beta(T_s - T_g) \quad (2.19)$$

Heat generation mainly occurs in the catalyst layer due to entropy changes during the chemical reactions and irreversibilities associated with the charge transfer [42]:

$$\dot{q} = \left[\frac{T(-\Delta\bar{s})}{n_e F} + \eta_{act} \right] i \quad (2.20)$$

where $\Delta\bar{s}$ is the entropy change in the chemical reactions, n_e is the number of electrons transferred, F is the Faraday's constant (96487 C/mol), i is the local current density, and η_{act} is the activation overpotential which reads as follows:

$$\eta_{act} = 2.303 \frac{RT}{\alpha_c F} \ln \left(\left| \frac{i}{i_0} \right| \right) \quad (2.21)$$

the definition of i and i_0 along with other unknown parameters in equation (2.20) and (2.21) will be discussed specifically in section 2.5. Numerically, a heat source term has to be added only covering the cathodic catalyst layer, representing the local heat generation due to exothermic electrochemical reaction.

In the membrane, as assumption 6 states, the heat transfer associated with net water flux is neglected and only the ohmic heating due to the limited conductivity of the membrane is accounted for. The heat source Q is calculated using:

$$Q = k|i|^2 \quad (2.22)$$

where k denotes the protonic conductivity of the membrane.

2.4.5. Computational Sub-domain V (Water transport)

Although the exact mechanism of water behavior in the membrane is still unknown, the molar flux of water is believed to be governed by the balance between concentration gradient, pressure gradient, and electro-osmotic drag, i.e.,

$$N_w = -D_w \nabla c_w - c_w \varepsilon_w^m \frac{k_h}{\mu_l} \nabla P_l + \frac{n_d i}{F} \quad (2.23)$$

where N_w denotes the molar flux of water, c_w the molar concentration of water, D_w the diffusion coefficient, ε_w^m the volume fraction of water in the membrane, k_h the hydraulic permeability of the membrane, μ_l the liquid water viscosity, P_l the water pressure, n_d the elector-osmotic drag coefficient, F the Faraday's constant, and i is the local current density in the membrane. In contrast with other models published in the open literature, this equation

accounts for back diffusion processes induced by the concentration gradient, which provides the model with an improved ability to predict humidification schemes.

Taking into account the mass and current density conservation principles:

$$\nabla \cdot \mathbf{N}_w = 0 \quad (2.24)$$

and:

$$\nabla \cdot \mathbf{i} = 0 \quad (2.25)$$

then invoking assumption 12, which states that the water pressure is linearly distributed in membrane, i.e.,

$$\nabla^2 P_l = 0 \quad (2.26)$$

a new equation through combination of equations (2.24), (2.25), (2.26) and (2.23) is obtained:

$$\nabla \cdot \mathbf{N}_w = -D_w \nabla^2 c_w - \varepsilon_w^m \frac{k_h}{\mu_l} (\nabla c_w \cdot \nabla P_l) + \frac{\nabla n_d \cdot \mathbf{i}}{F} = 0 \quad (2.27)$$

Springer et al. [11] proposed a function which relates the electro-osmotic drag coefficient n_d with the membrane water content for Nafion117, i.e.,

$$n_d = \frac{2.5}{22} \lambda \quad (2.28)$$

where λ denotes membrane water content, defined as water molecules per sulfonic-acid group (SO_3^-). They also present an empirical formula relating c_w to λ as follows:

$$c_w = \frac{e\lambda}{f\lambda + 1} \quad (2.29)$$

where f is the swelling coefficient of the membrane, which is experimentally determined,

and e is the ratio between the dry membrane density, ρ_m^{dry} , and the equivalent membrane weight, E_m , i.e.,

$$e = \frac{\rho_m^{dry}}{E_m} \quad (2.30)$$

Substituting equation (2.30) into (2.29) leads to:

$$\lambda = \frac{c_w}{e - fc_w} \quad (2.31)$$

Then, equation (2.28) can be re-written as:

$$n_d = \frac{2.5}{22} \frac{c_w}{e - fc_w} \quad (2.32)$$

Substituting the above equation into equation (2.27) yields:

$$-D_w \nabla^2 c_w - \varepsilon_w^m \frac{k_h}{\mu_l} (\nabla c_w \cdot \nabla P_l) + \frac{5}{44} \frac{e}{F(e - fc_w)^2} (\nabla c_w \cdot i) = 0 \quad (2.33)$$

2.4.6. Computational Sub-domain VI (Proton transport)

Flow of charged species is the intrinsic reason of electric current. In the PEM fuel cell membrane, the only mobile ion is the hydrogen proton; hence, it has:

$$i = F \sum Z_i N_i = F N_p \quad (2.34)$$

where Z_i is the charge number of ion, N_i is the molar flux of ion. It is noted that $i=1$, and $Z_i=1$ in this scenario.

Similar to the water transport, the proton obeys the principle of mass conservation, i.e.,

$$\nabla \cdot N_p = 0 \quad (2.35)$$

Meanwhile, the flux of proton is governed by the general *Nernst-Planck equation*, which accounts for the processes of diffusion, migration, and convection [9, 43, 44], as follows:

$$N_p = -D_p \nabla c_p - Z_p D_p \frac{F}{RT} c_p \nabla \phi + c_p U_l \quad (2.36)$$

where D_p is the diffusion coefficient, c_p the molar concentration of protons, Z_p the charge number of ion, ϕ the electric potential, and U_l is the convective velocity of the liquid water.

As suggested in [43, 44] the velocity of liquid water can be further described by employing the Schlögl equation, which indicates that the convection is driven by the electric potential and the pressure gradient:

$$U_l = \varepsilon_w^m \left(\frac{k_\phi}{\mu_l} Z_f c_f F \nabla \phi - \frac{k_h}{\mu_l} \nabla P_l \right) \quad (2.37)$$

where k_ϕ is the electric permeability, Z_f is the charge number of the fixed charges, c_f is the fixed charge concentration, and k_h is the hydraulic permeability.

The membrane also satisfies the electro-neutrality condition, which states:

$$Z_f c_f + \sum Z_i c_i = 0 \quad (2.38)$$

In the membrane, proton is the only charged ion, hence, $Z_i=1$, and equation (2.38) reduces to:

$$Z_f c_f = -c_p \quad (2.39)$$

Substituting equations (2.39) and (2.37) into equation (2.36) followed by its combination with equations (2.34) and (2.35) leads to:

$$-\Delta \phi = -\frac{RT}{F^2 D_p c_p} \left(\nabla (\ln c_p) \cdot i \right) + \frac{RT}{F} \nabla \cdot \left(\nabla (\ln c_p) \right) \quad (2.40)$$

The membrane conductivity is defined as:

$$k = \frac{F^2}{RT} \sum Z_i^2 D_i c_i \quad (2.41)$$

Hence, equation (2.40) can be further simplified:

$$-\Delta\phi = -\frac{1}{k} \left(\nabla (\ln c_p) \cdot i \right) + \frac{RT}{F} \nabla \cdot \left(\nabla (\ln c_p) \right) \quad (2.42)$$

The proton concentration c_p varies inside the membrane due to the presence of internal liquid water, and its relation can be described as:

$$c_p = \frac{c_w}{\lambda} \quad (2.43)$$

Here, invoking the expression of λ in equation (2.31), it turns out:

$$c_p = e - fc_w \quad (2.44)$$

Substituting the above equation into equation (2.42) yields:

$$-\Delta\phi = \frac{f}{k(e - fc_w)} (\nabla c_w \cdot i) - \frac{RT}{F} \frac{f}{(e - fc_w)} \Delta c_w - \frac{RT}{F} \left(\frac{f}{e - fc_w} \right)^2 (\nabla c_w \cdot \nabla c_w) \quad (2.45)$$

Then, the above equation is combined with the water content equation (2.33) to eliminate the term Δc_w , i.e., $\nabla^2 c_w$. Finally, the electric potential in the membrane, ϕ , obeys the following equation:

$$\begin{aligned} -\nabla^2 \phi = & \frac{f}{e - fc_w} \left(\frac{1}{k} - \frac{5}{44} \frac{RTe}{F^2 (e - fc_w)^2} \right) (\nabla c_w \cdot i) \\ & + \frac{RT}{F} \frac{f}{e - fc_w} \frac{\varepsilon_w^m k_h}{D_w \mu_l} (\nabla c_w \cdot \nabla P_l) \\ & - \frac{RT}{F} \left(\frac{f}{e - fc_w} \right)^2 (\nabla c_w \cdot \nabla c_w) \end{aligned} \quad (2.46)$$

Compared to the traditionally used Laplace's equation, $-\nabla^2 \phi = 0$, the newly derived

equation (2.46) exhibits the membrane potential distribution with the variation of water content fully considered.

2.5. Boundary Conditions

Corresponding to the equation systems, boundary conditions will be illustrated in separate sub-domains. For the sake of convenience, all boundaries in the model are numbered as shown in Figure 2.2, and they are named as B1, B2, etc.

Figure 2.2 Schematic illustration of boundary numbering

Computational sub-domain I :

For the bulk fluid flow sub-domain, the velocities at the anode and cathode inlet (B1, B9) are both prescribed using *Dirichlet* boundary conditions. The pressure at both outlet sides (B12, B16) are prescribed using *Dirichlet* boundary conditions as well. All other boundaries use the *no slip* condition for the velocity.

Computational sub-domain II :

Boundary conditions for sub-domain II are relatively complicated, due to the mass sink terms caused by chemical reactions at catalyst layers (B6, B8).

At the anode and cathode inlet (B1, B9), the mass fraction of H_2 and O_2 are prescribed using constant values; the mass fraction of water vapor is prescribed through combination of equation (2.11) and equation (2.13), i.e.,

$$\omega_{H_2O(g)} = \alpha \frac{P_g^{sat} M_{H_2O}}{P_g M} \quad (2.47)$$

At the anode and cathode outlet (B12, B16), the *convective flux* condition, which neglects the transport by diffusion in the flow direction, is set for mass fractions of all species. This type of boundary condition yields:

$$\tilde{n}_i \cdot \mathbf{n} = \omega_i \rho \mathbf{U} \cdot \mathbf{n} \quad (2.48)$$

where $\tilde{n}_i$ is the mass flux of species i , and $\mathbf{n}$ is the normal to the boundary.

At the anode-side catalyst layer (B8), hydrogen is oxidized due to electrochemical reaction and the local sink term is given by the Faraday's law:

$$S_{H_2} = -\frac{M_{H_2}}{2F} i \quad (2.49)$$

where M_{H_2} is the molecular weight of hydrogen, F the Faraday's constant, and i the local current density. The factor 2 in denominator indicates that each hydrogen molecule produces two electrons in the reaction.

At the cathode-side catalyst layer (B6), a similar sink term which accounts for oxygen

depletion is employed:

$$S_{O_2} = -\frac{M_{O_2}}{4F}i \quad (2.50)$$

The local current density i in the above equation is given by the Butler-Volmer equation:

$$i = ai_0 \left[\exp\left(\frac{\alpha_a F}{RT}\eta\right) - \exp\left(-\frac{\alpha_c F}{RT}\eta\right) \right] \quad (2.51)$$

where a is the electrochemically active area per unit of electrode volume, i_0 the apparent exchange current density, α_a and α_c are the anodic and cathodic transfer coefficients, respectively, η the surface overpotential, R the universal gas constant, and T the cell temperature. The apparent exchange current density, i_0 , is related to the concentration of dissolved reactants in catalyst layer. On the cathode side, according to [42], it obeys:

$$i_0 = i_0^{ref} \left(\frac{C_{O_2}}{C_{O_2}^{ref}} \right)^{\gamma_{O_2}} \left(\frac{C_{H^+}}{C_{H^+}^{ref}} \right)^{\gamma_{H^+}} \quad (2.52)$$

where the concentration of hydrogen proton is assumed homogenously distributed over the catalyst layer so that the second term in the right hand side can be omitted.

Note that the surface overpotential, η , represents the driving force for an electrochemical reaction, and is highly negative on the cathode side (B6). Hence, the Butler-Volmer equation (2.51) can be simplified to:

$$i_c = -ai_{0,c}^{ref} \left(\frac{C_{O_2}}{C_{O_2}^{ref}} \right)^{\gamma_{O_2}} \exp\left(-\frac{\alpha_c F}{RT}\eta\right) \quad (2.53)$$

On the contrary, the overpotential η at anode-side catalyst layer (B8) is fairly small, and the Butler-Volmer equation (2.51) is linearized to:

$$i_a = -ai_{0,a}^{ref} \left(\frac{C_{H_2}}{C_{H_2}^{ref}} \right)^{\gamma_{H_2}} \left(\frac{\alpha_a + \alpha_c}{RT} F \eta \right) \quad (2.54)$$

where γ denotes concentration parameter, ai_0^{ref} is the reference exchange current density, and C^{ref} is the reference concentration of reactants. These parameters are all input parameters of the model.

Once the local current densities are known, the sink terms in equation (2.49) and (2.50) can be easily implemented in terms of outward *mass flux* at boundaries B6 and B8. For all other boundaries, the *insulation/symmetry* conditions are simply used.

Computational sub-domain III:

For the gaseous heat transfer sub-domain, the ambient temperature is prescribed at channel inlets (B1, B9) and external channel wall (B2, B11), as *Dirichlet* boundary condition.

At both outlet sides, boundary conditions are set as *convective flux* conditions.

At all other boundaries, the *thermal insulation* conditions are used.

Computational sub-domain IV:

In a practical three-dimensional fuel cell, the porous electrode is assembled with a part called a bipolar plate (Refer to 3D model in Chapter 4). The graphite made bipolar plate has very good heat conductivity and it actually functions as a heat sink. However, it is impossible to include the bipolar plates in a 2D model; therefore, the ambient temperature has to be prescribed on the internal channel wall (B4, B10) as *Dirichlet* boundary condition.

At all other boundaries, the *thermal insulation* conditions are used.

Computational sub-domain V :

The improved water equation (Eq.(2.33)) in this model allows quantitative evaluation of the fuel cell operation with a partially hydrated membrane.

For a specific hydration study, a constant water content (c_w) value, i.e., a *Dirichlet* boundary condition, is specified along the anode side boundary (B8). However, the implementation of the boundary condition at the cathode side boundary (B6) is a bit troublesome. Assumption 10 indicates that source terms of liquid water are present in the catalyst layers. Hence, at the anode-side catalyst layer (B8), the source is:

$$S_{H_2O,anode} = \left(\nabla \cdot N_{H_2O(g)} \right) \frac{M_{H_2O}}{\rho_{H_2O}} \quad (2.55)$$

and at the cathode-side catalyst layer (B6), it is:

$$S_{H_2O,cathode} = \nabla \cdot \left(\frac{i}{2F} + N_{H_2O(g)} \right) \frac{M_{H_2O}}{\rho_{H_2O}} \quad (2.56)$$

where $N_{H_2O(g)}$ is the molar flux of water vapor, the term $\frac{i}{2F}$ at the cathode side equation represents the molar flux of water which is produced by electrochemical reactions. Once the source terms are known, the water content c_w at cathode-side catalyst layer (B6) can be prescribed in such a way that the water balance condition described by equation (2.55) and (2.56) is satisfied on point by point basis throughout the length of the membrane.

At the left and right boundary sides of the membrane (B5, B14), *Neumann* boundary conditions are used.

$$\mathbf{n} \cdot \nabla c_w = 0 \quad (2.57)$$

where $\mathbf{n}$ denotes the unit vector normal to the boundaries.

Computational sub-domain VI:

Consistent with the boundary condition of water content equation (2.33), where a constant value of c_w is prescribed at anode side boundary (B8), a zero electric potential is specified at B8 for potential equation (2.46) accordingly. At cathode side boundary (B6), a *Neumann* boundary condition is applied according to [45], which states:

$$\nabla \phi = -\frac{i - Fc_f U_l}{k} \quad (2.58)$$

where k is the membrane conductivity. The study of Springer et al. [11] shows that, for Nafion117, the conductivity can be expressed as a function of water content and temperature:

$$k = \left(0.5139 \frac{c_w}{(e - fc_w)} - 0.326 \right) \exp \left(1268 \left(\frac{1}{303} - \frac{1}{T} \right) \right) \quad (2.59)$$

During the computation, k in equation (2.46) and (2.58) will be updated using equation (2.59) after every iteration.

2.6. Computational Procedure

Due to the nature of strongly complicated coupling between different computational sub-domains, the commercial software, FEMLABT3.0, is selected as the simulation tool to implement the model developed in this study. FEMLAB offers a complete multiphysics

modeling environment where any combination of physical processes can be solved simultaneously using finite element methods. For this fuel cell model, all of the transport phenomena are implemented using FEMLAB's predefined application modes, except for the newly derived water and proton equations, which are implemented through customized equation-based modeling functions.

In the numerical solution of the entire set of modeling equations, it is impractical to employ a direct method since six computational sub-domains are involved and a large number of nodes have to be distributed onto each sub-domain to ensure a satisfactory level of numerical solution accuracy. In particular, when solving the water content and potential on the membrane using sub-domains V and VI, respectively, an extremely large amount of mesh nodes has to be used so that the resulting finite element solutions are sufficiently accurate for further analysis on water management. In the current simulation, the total number of elements corresponding to the mesh shown in Figure 2.3 is about 30,000, and the total associated degrees of freedom are approximately 450,000. However, the upper limit of degrees of freedom in FEMLAB 3.0 is only 120,000 [46]. Therefore, it is impossible to simultaneously solve all variables over all six sub-domains using the current version of

Figure 2.3 Mesh of the computational domain

FEMLAB.

To overcome this difficulty, a properly designed iteration strategy is employed in the numerical solution. Two levels of iterations are performed for the model: an inner iteration to solve for the spatial coupling of each of the variables involved in each sub-domain, and an outer iteration to solve for the coupling between variables on different sub-domains. Thus, each sub-domain is treated in sequence using the *stationary nonlinear solver* that regards all variables in other sub-domains as fixed. The non-linearity of the original system is circumvented by reforming the coefficients using the most recently calculated variable values before each outer iteration. Figure 2.4 illustrates the flow chart of the computation procedure.

Figure 2.4 Flow chart of the solution procedure

2.7. Modeling Parameters

Determination of modeling parameters is one of the most important and difficult parts of the modeling work. However, very limited experimental results are available in the literature with detailed specification of the cell geometry and experimental conditions. Therefore, most of the parameters present here are taken from *Berning's* numerical model [41]; other available original references are quoted when employed.

Table 2-1 groups the basic dimensions of the computational domain. All parameters in the table are taken from the model of *Bernardi et al.* [8], except the cell length, for which only half length of a cell is used to simplify and accelerate the computation. All values in Table 2-1 refer to both anode and cathode sides.

Table 2-1 Physical dimension of the PEM fuel cell (refer to Figure 2.1)

Parameter	Value	Unit
Gas channel length (half) (x-direction)	0.025	<i>m</i>
A_{MEA} : full active MEA area	0.00005	m^2
Gas channel thickness (y-direction)	0.001	<i>m</i>
Electrode thickness (y-direction)	0.00026	<i>m</i>
Membrane thickness (y-direction)	0.00023	<i>m</i>

Table 2-2 lists the base case operational parameters for the current model. All these

values are taken from the experiments performed by *Ticianelli et al.* [47]. Operational parameters have great effects on fuel cell performance and parametric studies will be performed and discussed.

Table 2-2 Operational parameters at base case conditions

Variable	Symbol	Value	Unit
Temperature	T	353	K
Anode channel pressure	P_a	3	atm
Cathode channel pressure	P_c	5	atm
Horizontal gas velocity at anode inlet	u_a	0.5	m/s
Horizontal gas velocity at cathode inlet	u_c	0.1185	m/s
Hydrogen mass fraction at inlet	ω_{H_2}	0.1	—
Oxygen mass fraction at inlet	ω_{O_2}	0.218	—
Relative humidity of inlet gases	α	1	—
Oxygen/Nitrogen ration	—	0.79/0.21	—

All source terms in different transport processes are summarized in Table 2-3. The momentum source terms are taken from Um et al. [19] that represent the Darcy's drag for flow through a porous medium. Note that the source term in the membrane is slightly revised according to their recent work [37], which can more effectively render the fluid

velocity to zero. Source terms of liquid water are based on assumption 10 and hence are specific to the current model. Other source terms are in generic patterns and can be easily found in most literatures on fuel cell research, for instance, [18, 19, 41].

Table 2-3 Source terms for momentum, species, and energy equations in various regions

Region	Momentum	Species	Energy
Anode	$-\frac{\mu}{k_p} \varepsilon^2 U$ [19]	—	—
Catalyst layer (anode)	—	$S_{H_2} = -\frac{M_{H_2}}{2F} i$ $S_{H_2O(l)} = \left(\nabla \cdot N_{H_2O(s)} \right) \frac{M_{H_2O}}{\rho_{H_2O}}$	—
Membrane	$-\frac{\mu}{k_p} U$ [19,37]	—	$k i ^2$
Catalyst layer (cathode)	—	$S_{O_2} = -\frac{M_{O_2}}{4F} i$ $S_{H_2O(l)} = \nabla \cdot \left(\frac{i}{2F} + N_{H_2O(s)} \right) \frac{M_{H_2O}}{\rho_{H_2O}}$	$\left[\frac{T(-\Delta \bar{s})}{n_e F} + \eta_{act} \right] i$
Cathode	$-\frac{\mu}{k_p} \varepsilon^2 U$ [19]	—	—

Electrode properties used in this model are listed in Table 2-4. Among them, the value of the heat transfer coefficient β is a trial number, obtained by assuming that the temperature

difference between the solid and gas-phase is no more than 0.1K [41].

Table 2-4 Electrode properties

Parameter	Symbol	Value/Unit	Ref.
Electrode porosity	ε	0.4	[8]
Permeability of electrode	k_p	1.76E-11 m^2	[19]
Electrode thermal conductivity (Ballard AvCarb [®] -P150)	λ_s	1.3 $W/(m \cdot K)$	[48]
Anode side charge transfer coefficient	α_a	0.5	[41]
Cathode side charge transfer coefficient	α_c	1	[47]
Anode ref. exchange current density	$ai_{0,a}^{ref}$	0.14 A/m^3	[8]
Cathode ref. exchange current density	$ai_{0,c}^{ref}$	1.0E-11 A/m^3	[8]
Hydrogen concentration parameter	γ_{H_2}	0.5	[49]
Oxygen concentration parameter	γ_{O_2}	1	[18]
Entropy change of cathode reaction	$\Delta \bar{s}_{Pt}$	-326.36 $J/(mol \cdot K)$	[50]
Heat transfer coefficient	β	1.0E8 W/m^3	[41]

The gas-pair diffusivities shown in Table 2-5 are taken from [51]. They correspond to the experiment conditions used in [51] and now should be converted to actual working conditions used in this study. The conversion formula [51] is:

$$D_{ij}^{eff} = D_{ij}(T_0, P_0) \frac{P}{P_0} \left(\frac{T}{T_0} \right)^{1.75} \quad (2.60)$$

where P_0 denotes the reference pressure, 1 atm , P and T are the working pressure and temperature, respectively.

Table 2-5 Binary diffusivities at 1atm and reference temperatures

Gas-Pair	Ref. Temperature T_0 (K)	Binary Diffusivity D_{ij} (cm^2/s)
$D_{H_2-H_2O}$	307.1	0.915
$D_{H_2-CO_2}$	298.0	0.646
$D_{H_2O-CO_2}$	307.5	0.202
$D_{O_2-H_2O}$	308.1	0.282
$D_{O_2-N_2}$	293.2	0.220
$D_{N_2-H_2O}$	307.5	0.256

The membrane is the most important domain in this present modeling since almost all variables are solved in the membrane. A proper choice of membrane properties will directly enhance the accuracy of the modeling work. Physical parameters corresponding to the membrane material, Nafion 117, along with some crucial transport properties used in the water and potential equations, are summarized in Table 2-6.

Table 2-6 Transport properties and physical parameters of the membrane

Parameter/Property	Symbol	Value/Unit	Ref.
Permeability of membrane	k_p	$1\text{E-}30 \text{ m}^2$	[37]
Fixed charge concentration	c_f	$1,200 \text{ mol/m}^3$	[8]
Fixed site charge	z_f	-1	[8]
Hydraulic permeability	k_h	$1.8\text{E-}18 \text{ m}^2$	[8]
Electrokinetic permeability	k_ϕ	$7.18\text{E-}20 \text{ m}^2$	[8]
Thermal conductivity	λ_s	$0.67 \text{ W/(K}\cdot\text{m)}$	[52]
Dry membrane density	ρ_m^{dry}	$1,980 \text{ kg/m}^3$	[53]
Equi. membrane weight	E_m	1.1 kg/mol	[53]
Membrane swelling coef.	f	0.0126	[11]
$e = \rho_m^{dry} / E_m$	e	1800 mol/m^3	[11]
Water diffusion coef.	D_w	$2.5 \times 10^{-7} e^{\frac{-2436}{T}} c_w / (48(e - fc_w)) \text{ m}^2/\text{s}$	[54]
Volume fraction of water	ε_w^m	$c_w / (48(e - fc_w))$	[11]
Water viscosity	μ	$1.788 \times 10^{-3} e^{\left(-1.704 - 5.306 \frac{273}{T} + 7.003 \left(\frac{273}{T}\right)^2\right)} \text{ kg/(m}\cdot\text{s)}$	[55]
Membrane conductivity	k	<i>Equation 2.59 A/(V·m)</i>	[11]

Chapter 3. Base Case Results and Parametric Study

3.1. Validation Comparisons

The polarization curve is one of the most important measurements in fuel cell studies. Figure 3.1 compares the results of the model at base case conditions with the experimental results obtained by a CFD research group [56]. The two sets of results have good agreement at low and intermediate current densities. The increasing discrepancies for high current densities can be explained by mass transport losses, for which there is no established mathematical model to accurately quantify their effect as yet. The numerical results also clearly demonstrate the limiting current density effect through the steep decrease of cell voltage beyond a current density of 1.2 A/cm^2 (see the solid curve in Figure 3.1). The

Figure 3.1 Comparison of polarization curves between numerical model and experiments [56]

available experimental data [56] are provided up to the limit of 1.2 A/cm^2 . Thus, no comparison beyond this limiting current density is shown in Figure 3.1.

Figure 3.2. demonstrates different types of loss behavior. The top horizontal curve represents the theoretical cell voltage; the area between two subsequent lines corresponds to a potential loss; from the top to the bottom, the potential losses considered are: membrane loss, anode and cathode concentration loss, electrode ohmic loss, anode and cathode activation loss, respectively. It can be seen that the most remarkable loss is the activation loss at the cathode side, since the electrochemical reaction at this side is slow and a large amount of overpotential is needed to drive the reaction to happen. On the contrary, the anode side reaction is far faster than at the cathode side; hence, its activation potential loss is smaller. One possible method to alleviate activation losses is using improved catalyst deposition.

The membrane loss and electrode ohmic loss also contribute a lot to the overall potential loss. Due to the ohmic nature of membrane and electrodes, these two losses are relatively small at low current density but increase linearly with current density; when approaching a limiting current density, the two losses become significant and can be comparable to the cathode activation loss.

The concentration loss is quantitatively small in Figure 3.2 whether at the anode side or the cathode side. However, the cathode concentration loss increases very fast at the limiting current density; this also explains why the cell voltage decreases steeply when the current density is close to its limit (see Figure 3.1).

Figure 3.2 Different potential loss mechanisms

In addition to the polarization curve, power density is another commonly used measurement to compare a numerical model with experiment results. In consistency with the polarization tendency, the two sets of power density results shown in Figure 3.3 have good agreement up to a current density of $1.0 A/cm^2$. The increasing discrepancies towards the limiting current density shown in Figure 3.3 can also be ascribed to the concentration losses caused by the reactants' transport limitations. Once again, the numerical model can help predict the limiting current density through the examination of power density behavior since an obvious decrease of power density after $i = 1.2 A/cm^2$ is seen in Figure 3.3.

Figure 3.3 Comparison of power density between numerical and experiment results [56]

3.2. Base Case Results

A great advantage of numerical modeling over experiment measurements is that numerical simulations can shed light on some transport phenomena and electrochemical mechanisms inside a fuel cell that are usually hard or even impossible to examine by *in situ* measurements. In the following sections, distributions of different physical variables, such as the velocity, mass fractions of various reactants, cell temperature, catalyst-layer current density, membrane water content and potential loss, will be explored for better understanding the fuel cell working mechanism. All of these results are based on the presence of a pressure drop (3 *atm* on the anode-side channel and 5 *atm* on the cathode-side channel) and fully humidified incoming stream; other parameters are listed in Table 2-2 unless otherwise specified.

3.2.1. Velocity Profiles

In Figure 3.4, the upper plot depicts the velocity profile over the length of the cell. The velocity profiles in both cathodic and anodic channels become unchanged shortly after entering the inlets, which indicates that the flow here easily gets fully developed and keeps a laminar pattern till the end. Besides, the flow becomes fairly slow in the porous electrodes and membrane, due to the extremely low permeabilities of the porous materials used for these components. The lower plot in Figure 3.4 shows the cross section velocity profile midway along the cell length. As convention for all figures that follow, the origin is located

Figure 3.4 Velocity profile in the fuel cell (upper) and cross section velocity profile at $x=0.0125\text{m}$ (lower)
(Refer to Figure 2.1 for coordinate system)

at the mid-point of the cell height in the inlet section. Corresponding to each of the two channel heights, the velocity profile looks parabolic with its peak slightly shifting from the central line of the channel towards to its neighboring electrode. This is because the flow is not symmetric along the channel height: the velocity is nil at the solid channel wall due to the no slip boundary condition, but does not yet reduce to zero at the channel-electrode interface, as demonstrated in Figure 3.4 through local enlargement around the channel-electrode interface ($y = 0.00375 \text{ m}$); the flow remains weak at the channel-electrode interface location and then gradually diminishes after passing over a short vertical distance ($\Delta y = 0.00075 \text{ m}$ as shown in the local enlargement part of Figure 3.4) within the electrode.

3.2.2. Reactants Distribution

Although there is convection inside the two electrodes, the convective velocity is quite small and vanishes very quickly. As a result, diffusion processes eventually dominate the transport of the species in the electrodes.

Figure 3.5 shows the hydrogen mass fraction distribution inside the anode-side gas channel and porous electrode for three different nominal current densities. In all cases, the hydrogen mass fraction decreases gradually from the inlet to the outlet and from the solid wall towards the catalyst layer; this is because the hydrogen is consumed through the oxidation reaction at the anode-side catalyst layer. Hydrogen has high diffusivities whether in carbon-oxide (CO_2) or in water vapor. Therefore, no significant diminution of hydrogen

mass fraction is found in Figure 3.5; even at the high current density of $i = 1.2 \text{ A/cm}^2$, the variation of hydrogen mass fraction is less than 15.5%.

Figure 3.5 Hydrogen mass fraction in anode-side channel and GDE for three loading conditions: 0.4 A/cm² (top), 0.8 A/cm² (middle), and 1.2 A/cm² (bottom) (Refer to Figure 2.1 for coordinate system)

Figure 3.6 illustrates the distribution of the oxygen mass fraction. Since the diffusivity of oxygen is several times smaller than hydrogen, oxygen diffuses slower in the cathode, causing dramatic oxygen mass fraction gradients as shown in Figure 3.6. At the high current

density of $i = 1.2 \text{ A/cm}^2$, the supply of oxygen is not sufficient to maintain the electrochemical reactions, and the oxygen mass fraction is close to nil nearby the catalyst layer, indicating the limiting current density has almost been reached. This plot reveals that the diffusion of the oxygen towards the catalyst layer is the main impediment for reaching high current densities.

Figure 3.6 Oxygen mass fraction in cathode-side channel and GDE for three loading conditions: 0.4 A/cm^2 (top), 0.8 A/cm^2 (middle), and 1.2 A/cm^2 (bottom) (Refer to Figure 2.1 for coordinate system)

3.2.3. Current Density Distribution

Once the distributions of the two gaseous reactants are obtained, it is possible to determine local current density distributions on the two catalyst layers using equation (2.53) and equation (2.54).

Figure 3.7 shows the local current density distributions on both catalyst layers for three different nominal current densities. It can be seen that the local current density at the anode side is evenly distributed for all three nominal current densities, since hydrogen is almost homogeneously distributed on the anode-side catalyst layer.

Figure 3.7 Comparison of current density distributions on the two catalyst layers for three different nominal current densities

However, the variation of nominal current density has a great impact on the local current

density distribution at the cathode-side catalyst layer. At the nominal current density of 0.4 A/cm^2 , the local current density is almost uniformly distributed with its maximum and minimum offsets no more than 10% of the nominal value. As the nominal current density increases, the reaction on the cathode-side catalyst layer becomes starved of oxygen due to low oxygen diffusivities, except for the inlet area where fresh oxygen can be supplied timely. At the nominal current density of 1.2 A/cm^2 , for the current density over the catalyst length, the maximum can exceed the average by approximately 50% at the inlet while the minimum is 30% below the average at the outlet.

3.2.4. Temperature Distribution

In Figure 3.8, three temperature profiles in the order of increasing current densities are demonstrated. There is a common feature in all three plots that the highest temperature appears at the leading zone (inlet) of the cathode-side catalyst layer, where the exothermic reaction is the strongest due to the presence of the richest oxygen in that zone, then heat disperses to the rest of the membrane and electrodes, and ultimately becomes uniform inside the gas channels.

It is also noticed from Figure 3.8 that the nominal current density has an influence on the increasing of temperature during fuel cell operation. The amount of heat generated in the lower current density (0.4 A/cm^2) case is fairly small, and the maximum temperature is only 1K higher than the ambient temperature value. However, corresponding to the high current

Figure 3.8 Temperature distribution in the cell for three loading conditions: 0.4 A/cm² (top), 0.8 A/cm² (middle), and 1.2 A/cm² (bottom) (Refer to Figure 2.1 for coordinate system)

density (1.2 A/cm^2), substantial heat is released due to the active reaction at the leading area of the cathode-side catalyst layer, and the maximum temperature in that zone is 5K greater than the ambient temperature. This situation would become even worse for a real full size fuel cell and especially if serpentine channels and multi layer structures are employed.

As mentioned in Chapter 2, heat generation highly depends on current density. Hence, at the catalyst layer, the temperature should be distributed in accordance with the distribution of current density, which can be verified by comparing Figure 3.9 with Figure 3.7. This comparison suggests that redistributing the catalyst deposition may help reform the current density distribution and, consequently, control the temperature distribution effectively.

Figure 3.9 Temperature distribution on the cathode-side catalyst layer

3.2.5. Water Content in Membrane

Based on the assumption that all water vapor condenses on the catalyst layer and only liquid water is present in the membrane, a pseudo two-phase flow model is developed and examined in this study.

In the current model, the water flux in the membrane is governed by three factors: electro-osmotic drag associated with proton transport from the anode side to the cathode side, back-diffusion by the concentration gradient of liquid water, and convection by the pressure gradient between the anode-side and cathode-side channels. Among them, pressure gradient and back diffusion drive the flow of water from the cathode side to the anode side, while the electro-osmotic drag plays a role of reversing the water flow direction.

Figure 3.10 shows the water distribution inside the membrane for three typical current density loadings. At the lower current density of 0.4 A/cm^2 , electro-osmotic drag is small and the convection process dominates the transport of water throughout the whole domain. The electro-osmotic drag increases with the current density, and the liquid water molecules at the anode side will have the tendency to move towards the cathode side under the effect of electro-osmotic drag; hence, a reduced water content value is found at the anode-side boundary. It can be seen that the water content decreases from 6 to 1.95 as current density increases from 0.4 A/cm^2 to 1.2 A/cm^2 . If the current density keeps increasing, electro-osmotic drag would eventually outweigh the pressure gradient and back-diffusion

effects, causing the anode to dry out.

Figure 3.10 Water content in membrane for three loading conditions: 0.4A/cm² (top), 0.8A/cm² (middle), and 1.2A/cm² (bottom) (Refer to Figure 2.1 for coordinate system)

3.2.6. Membrane Potential Loss

The membrane material usually has quite a high electric resistance due to its fairly low electric permeability. That results in significant potential losses through the membrane.

Figure 3.11 shows the membrane potential loss in percentage of the total loss, it can be seen that the potential loss in the membrane occupies a large portion of the whole losses at high loading conditions. Therefore, an accurate model for proton transport is crucial for examination of membrane potential loss. Closely related to the water content variation inside the membrane, an equation for proton transport accounting for migration, diffusion, and convection of dissolved proton is presented and implemented in this work.

Figure 3.11 Membrane potential loss as a percent of the total loss vs. cell current density

Figure 3.12 compares both the maximum and averaged potential solutions along the cathode-side boundary using the new potential model presented here with those resulting from the solution of the conventional Laplace's equation. From the comparisons, it is noticed

that, with increasing current densities, the membrane potential loss resulting from the new model is increasing at a higher rate than that using Laplace's equation; also, the difference between the two sets of potential solutions is going up as the current density is increasing. This warns the fuel cell designer of the remarkable effect of water content variation especially at higher current densities.

Figure 3.12 Comparison of the maximum and average membrane potential loss on the cathode-side boundary between the new model and the model using Laplace's equation

Figure 3.13 illustrates the potential distribution inside the membrane for three different current densities. At the low current density of $0.4 A/cm^2$, the potential loss is small and the iso-potential lines are horizontal and parallel to each other, which indicate the linearity of the membrane potential loss. However, when the current density is increased to $1.2 A/cm^2$, the membrane potential loss becomes significant compared to the lower current density loading;

meanwhile, the iso-potential lines are no longer parallel to each other, revealing that the water content varies in a nonlinear pattern inside the membrane which, in turn, causes a nonlinear distribution of membrane potential loss.

Figure 3.13 Potential distribution inside membrane for three loading conditions: 0.4A/cm² (top), 0.8A/cm² (middle), and 1.2A/cm² (bottom) (Refer to Figure 2.1 for coordinate system)

3.3. Parametric Study

Numerous experiments show that working conditions, e.g., environment pressure, ambient temperature, humidification of the incoming streams, etc., have a great influence on the performance of a fuel cell. In the previous sections, validation through some base case studies has been performed, and good agreement with available experiment results testifies to the reliability of the current model. Next, using this model, various working conditions will be examined to exhibit the effects of gas humidification, environment pressure, and ambient temperature. A series of parametric studies will be carried out. To assess the effect of each individual parameter on the overall performance of the fuel cell, in each case study, only one parameter is allowed to vary while all others are kept unchanged.

3.3.1. Effect of Partial Humidification

To achieve an efficient water management scheme, a series of numerical experiments corresponding to a range of relative humidity values are conducted using the new membrane model developed in this study.

Figure 3.14 depicts the polarization curves at different relative humidities ranging from 30% to 100% for nominal current densities varying from 0.4 A/cm^2 to 1.2 A/cm^2 . It clearly shows that cell performance deteriorates with decreasing relative humidity and the more humidified stream that the cell receives, the smaller the decreasing slope appears in the cell voltage. It can be seen that the cell can work at a higher current density interval from 0.4

A/cm^2 to $1.2 A/cm^2$ as long as the cell is maintained at a higher relative humidity over 80%; on the contrary, at a lower relative humidity interval such as 30% to 40%, the figure shows that the cell can only operate at a very low current density. For other high/low relative humidity cases, the numerical procedure failed to converge in the extremes of low current densities (activation regime) or high current density (mass transport limited regime). This is not critical, as in normal operation it is the range of intermediate current densities (Ohmic region) that is typically of interest and exhibits the expected linear behavior.

Figure 3.14 Polarization curves corresponding to different relative humidity

Figure 3.15 demonstrates the behavior of membrane potential loss under three different humidification conditions. In all three cases, the potential linearly increases with the current

density but with different slopes; the higher the relative humidity, the smaller the potential loss slope.

Figure 3.15 Membrane potential loss vs. current density corresponding to three different humidities

From Figure 3.14, it is easily seen that the cell can operate over a wide range of relative humidities if the current density is low. Using the low current density of $0.4 A/cm^2$ as an example, Figure 3.16 shows the relationship between relative humidity and membrane potential loss, and hence the cell voltage from another point of view. The electric potential loss decreases significantly as relative humidity increases from 30% to 100% and the decrease is most evident over the interval of $[0.5, 0.8]$.

Figure 3.16 Cell voltage and membrane potential loss vs. relative humidity at current density of $0.4\text{A}/\text{cm}^2$

3.3.2. Effect of Pressure Loading

In fuel cell modeling, there are lots of parameters correlated with the inlet stream pressure, e.g., reactant gases composition, binary diffusion coefficients, water content inside membrane, and exchange current density, etc. The effect of pressure on the exchange current density and gas composition has been examined in [48], whereas the variation of water content under different pressure conditions is little studied. In this thesis, the effects of different pressure loadings on water content distribution will be assessed.

According to Wang et al. [37], the pressure is nearly constant from the gas channel to the porous electrode; the pressure drop occurs mainly through the membrane due to the low hydraulic permeability of the membrane. Therefore, the water distribution inside the membrane will be greatly affected by the pressure gradient, which can be clearly seen from Figure 3.17. The bottom curve in the figure is the result produced by Springer et al., who

Figure 3.17 Water content at the mid-section of the cell length using different model and pressure conditions corresponding to current density at $0.8\text{A}/\text{cm}^2$

used a 1D model without pressure drop between the two gas channels. In their model, water content drops more steeply near the cathode side and less rapidly close to the anode side. For comparison convenience, the water content values at the section midway between the cell inlet and outlet are extracted from the 2D simulation results. The middle curve in Figure 3.17

is obtained by using the current 2D model but with the pressure effects turned off. Consequently, water content almost linearly decreases from the cathode to the anode. At last, when the pressure effects are turned on, the top curve in Figure 3.17 exhibits a water content variation tendency in contrast to that of Springer's: the water content drops slowly at the cathode side but decreases quickly approaching the anode side. This indicates that imposing a pressure drop helps maintain a higher level of hydration over a larger part of the membrane.

Figure 3.18 depicts the polarization curves under different pressure conditions. For the three polarization curves without pressure drop, the slope decreases as the pressure is elevated at the two sides; this reveals that pressurizing the incoming gaseous streams to a

Figure 3.18 Polarization curves corresponding to different pressure conditions

higher degree helps to enhance the performance of a fuel cell. When letting both sides work under atmosphere pressure, cell performance looks poor and the operation is allowed only at the lower current density interval from 0.4 A/cm^2 to 0.6 A/cm^2 . On the other hand, Figure 3.18 demonstrates that, when a pressure drop is present from the cathode side (5 atm) to the anode side (3 atm), the cell voltage decreases at a lower rate than that with the pressure of 3 atm for both sides. In fact, owing to the presence of a pressure drop, the membrane is hydrated on a better level, which reduces the total membrane potential loss and, in turn, elevates the cell voltage.

3.3.3. Effect of Temperature

Generally, physical phenomena inside a PEM fuel cell, such as gas transport in the channel, proton and water transport in the membrane, and electrochemical reactions, etc., are correlated with the temperature condition. More specifically, the following influences of temperature are considered in this study:

(1) Composition of the incoming gas stream.

The molar fraction of water vapor in the coming gas mixture is governed by equation (2.13):

$$x_{H_2O, in} = \alpha \frac{P^{sat}}{P_{in}}$$

where α is the relative humidity, P_{in} the inlet gas pressure, and P^{sat} the saturation pressure of water. It is a function of temperature and is governed by equation (2.14)

$$P_g^{sat} = 10^{-2.1794 + 0.02953(T-273) - 9.1837 \times 10^{-3}(T-273)^2 + 1.4454 \times 10^{-7}(T-273)^3}$$

The mass fraction of hydrogen is always premixed to a constant value for the anode-side incoming gas stream. Therefore, the variation of water vapor does not affect the proportion of hydrogen. However, on the cathode side, oxygen is usually supplied using a humidified air stream. Dry air has the composition of 79% nitrogen and 21% oxygen; hence, the incoming oxygen molar fraction can be decided using:

$$x_{O_2, in} = \frac{1 - x_{H_2O, in}}{1 + \frac{79}{21}} \quad (3.1)$$

and the molar fraction of nitrogen can be determined using the conservation rule:

$$x_{N_2, in} = 1 - x_{H_2O, in} - x_{O_2, in} \quad (3.2)$$

Figure 3.19 Air stream compositions corresponding to different working temperature (°C)

The results based on equation (3.1) and equation (3.2) are shown in Figure 3.19. It illustrates the variation of gas compositions with increasing temperature.

(2) Binary diffusivities of the gas mixture.

Experiment values of gas-pair diffusivities are fitted to an empirical formula (equation (2.60)) with pressure and temperature variables, which has been illustrated in detail in section 2.7.

(3) Reaction kinetics.

The exchange current density of the oxygen reduction reaction (ORR) strongly depends on temperature, which can be seen from Table 3-1 derived by P. T. Nguyen [48].

Table 3-1 Variation of exchange current density with temperatures at 3atm

T (K)	323	333	343	353
$ai_{0,c}^{ref} (A/m^3)$	3.7235×10^{-12}	5.1039×10^{-12}	7.9031×10^{-12}	1.0×10^{-11}

(4) Transport parameters in membrane.

Effects of temperature are also implicitly accounted for when calculating some coefficients, e.g., membrane conductivity in equation (2.59), water diffusion coefficient and water viscosity in equation (2.33), etc. Water viscosity is purely a function of temperature; therefore, it can be used here as an example to illustrate the effect of temperature, as shown in Figure 3.20. The upper plot assumes the cell is isothermal ($T=353$ K); therefore, the resulting water viscosity is constant over the domain. Then, the temperature effect is

switched on in the lower plot; the resulting water viscosity varies in the space and it is coincident with the distribution of temperature, larger at the cathode inlet and smaller at the anode outlet.

Figure 3.20 Water viscosity in membrane using isothermal (upper) and anisothermal (lower) models (Refer to Figure 2.1 for coordinate system)

Chapter 4. Three-Dimensional Model of PEM Fuel Cell

4.1. Modeling Domain and Geometry

To reduce the computational cost, a straight channel instead of an actual serpentine channel is used in the present 3D numerical experiments. Since a unit cell is symmetric with respect to its middle plane in z -direction, only half of a cell is modeled to further simplify the geometry, as shown in Figure 4.1.

Figure 4.1 Computational domain of half unit cell

Compared to the 2D model, a new component, the bipolar plate, has to be added in the 3D model. Using the same strategy as in the 2D simulations, the 3D domain is still divided into six computational sub-domains. The membrane is assumed impenetrable to gas reactants, allowing for water and proton transport only; transport of gaseous reactants is considered in the gas channels and electrodes of both cathode and anode sides; heat transfer is simulated throughout the entire domain.

4.2. Assumptions

Assumptions made in the 2D model are still in effect in this chapter. Furthermore, there are two extra assumptions specifically suiting the 3D scenario as summarized below:

- (1) The potential drop across the bipolar plate is neglected due to its high electric conductivity.
- (2) Ohmic heating in the bipolar plate is neglected due to its high thermal conductivity.

4.3. Modeling Equations

The system of 3D modeling equations is fundamentally the same as the 2D system, except that one new equation accounting for heat conduction in the bipolar plate is added.

$$\nabla \cdot (\lambda_{bp} \nabla T_s) = 0 \quad (4.1)$$

where λ_{bp} is the thermal conductivity of a graphite bipolar plate.

4.4. Boundary Conditions

Firstly, *insulation/symmetry* boundary conditions are applied on the symmetric cross-section (see Figure 4.1) for all computational sub-domains.

For the computational sub-domain used for heat transfer simulation, the ambient temperature is prescribed at the channel inlet for the incoming stream and at the upper/bottom outer surfaces of the bipolar plate. *Convective flux* conditions are applied at the channel outlets and, at the interface of the gas channel and the bipolar plate, *heat flux* conditions are prescribed based on equation (2.17) and equation (2.19). For all other boundaries, *insulation* conditions are used. A further study regarding heat transfer in stack modeling is also conducted and illustrated later in this chapter, where *thermal insulation* conditions are used for the upper/bottom outer surfaces of bipolar plates.

For all other computational sub-domains, the 2D boundary condition set-up remains in effect for the 3D case, and the boundary conditions corresponding to the wall surface (which reduces to a line in the 2D case) are now extended for use on all wall surfaces appearing in the 3D scenario.

4.5. Modeling Parameters

Only a few parameters need to be added for 3D modeling. These parameters are listed in Table 4-1. Note that the thermal conductivity may vary significantly from one graphite material to another. Here, the thermal conductivity is assumed at 500 W/(mK) .

Table 4-1 Complementary parameters for 3D model

Channel width (z-direction)	Bipolar plate thickness (y-direction)	Land area width (z-direction)	λ_{bp}
$1.0 \times 10^{-3} \text{ m}$	$0.5 \times 10^{-3} \text{ m}$	$1.0 \times 10^{-3} \text{ m}$	500 W/(mK)

4.6. Results and Analysis

Corresponding to the 2D simulation results, the distributions of reactants, temperature, current density, water content and membrane potential loss resulting from the 3D model will be demonstrated in sequence. All 3D simulations continue to use the base case conditions (refer to Table 2-2) unless otherwise specified.

4.6.1. Reactants Distribution

As observed through 2D simulations, oxygen is consumed far more quickly than hydrogen, and oxygen transport will play a dominant role during the fuel cell operation. Here, both oxygen and hydrogen distributions will be investigated, and the oxygen distribution results will be examined and analyzed in detail.

Figure 4.2 shows the mass fraction of hydrogen for three different nominal current densities. The minimum mass fraction corresponding to current density 1.2 A/cm^2 is approximately 0.8, which is 4% smaller compared to the value 0.84 obtained from 2D modeling. This decrease occurs mainly due to the extra consumption of hydrogen under the

land area which can not be considered in 2D modeling.

Figure 4.3 shows the mass fraction of oxygen, revealing the oxygen concentration decreases not only in the cell length (x) and height (y) directions, which are intensively investigated in the 2D modeling, but also in the width direction (z) (refer to Figure 4.1 for the coordinate system). Figure 4.4 further demonstrates the concentration gradient on the yz plane. It clearly shows that the oxygen concentration changes tremendously in the y -direction over the whole electrode zone; however, in the z -direction, the oxygen concentration gradient is present mainly under the land area where oxygen can not be supplied directly from the flow stream and has to diffuse from the interface of the cathode and the cathode-side gas channel.

The oxygen distribution in the gas channel and electrode changes in response to the consumption of the electrochemical reaction and the diffusion driven by the oxygen concentration gradient. As demonstrated in Figure 4.4, at the lower current density of 0.4 A/cm^2 , the oxygen consumption is small and the oxygen is maintained in rich amounts everywhere; then, as the current density increases to 1.2 A/cm^2 , the oxygen is consumed so significantly at the catalyst layer that the diffusion, which is the only mechanism driving the transport of oxygen in the cathode, is hard to effectively maintain the electrochemical reaction over the entire width (the z -direction in Figure 4.1) of the catalyst layer, though the fresh oxygen can always be supplied timely in the vicinity of the inlet.

Figure 4.5 depicts the oxygen distribution on catalyst layer (on the xz plane of Figure

4.1) at a current density of 1.2 A/cm^2 . Oxygen is almost depleted under the land area and in the downstream region of the gas channel, indicating the limiting current density has almost been reached.

Figure 4.2 Hydrogen mass fraction in anode gas channel and electrode for three loading conditions: $0.4\text{A}/\text{cm}^2$ (top), $0.8\text{A}/\text{cm}^2$ (middle), and $1.2\text{A}/\text{cm}^2$ (bottom) (Refer to Figure 4.1 for coordinate system)

Figure 4.3 Oxygen mass fraction in cathode gas channel and electrode for three loading conditions: $0.4\text{A}/\text{cm}^2$ (top), $0.8\text{A}/\text{cm}^2$ (middle), and $1.2\text{A}/\text{cm}^2$ (bottom) (Refer to Figure 4.1 for coordinate system)

Figure 4.4 Iso-line of oxygen mass fraction on channel inlet section at current density: $0.4\text{A}/\text{cm}^2$ (top left), $0.8\text{A}/\text{cm}^2$ (top right) and $1.2\text{A}/\text{cm}^2$ (bottom) (Refer to Figure 4.1 for coordinate system)

Figure 4.5. Oxygen mass fraction on cathode-side catalyst layer at current density $1.2\text{A}/\text{cm}^2$

4.6.2. Temperature Distribution

In 2D modeling, the thermal conductivity in the z -direction is assumed infinite, i.e. the heat transfer ability in that direction is overvalued. Therefore, in terms of the 3D heat transfer simulation, the main task is to examine the z -direction heat transport process. Same as in the 2D simulation, isotropic thermal conductivities are used for each part of the cell in the present 3D modeling.

Figure 4.6 illustrates the temperature distribution for three different current densities. Similar to the 2D case, the temperature distribution resulting from the 3D simulation is relatively even at low current densities but gets unbalanced as current density increases. The highest temperature always occurs at the cathode-side catalyst layer and nearby the channel inlet; then, the temperature decreases gradually towards the outlet. Figure 4.7 depicts the temperature variation on the cathode-side catalyst layer (on the xz -plane of Figure 4.1), which confirms the location of the maximum temperature as aforementioned. Compared to the 2D modeling results, the maximum temperature in the 3D modeling gets an increase of 0.4K, 1K, and 1.9K corresponding to 0.4 A/cm^2 , 0.8 A/cm^2 , and 1.2 A/cm^2 , respectively. This indicates the heat transfer in the 2D modeling has been overrated.

Figure 4.8 shows the temperature distribution of the fuel cell stack modeling at a current density of 1.2 A/cm^2 . A stack is a multi-layer structure which is combined by unit cells in height and width directions. Infinite height and width dimensions are assumed in the present

stack modeling, which simplify the boundary conditions of the bipolar plate outer surface to *thermal insulation* conditions; thus, a single cell can be used to representatively simulate the whole stack. The resulting temperature distribution of stack modeling is totally different from the unit cell modeling. For a unit cell, heat is released to the environment by convective gas flows through gas channel, and by conductive transfer through the bipolar plate. In the fuel cell stack case, heat is released through gas flow only. Both plots in Figure 4.8 clearly show that the air stream (gas mixture on the cathode side) is heated up greatly upon leaving the gas channel; this is because the gas velocity is lower, leading to heat convection at a lower rate, while heat generation is significant during the exothermic reaction at the cathode-side layer.

Figure 4.9 depicts the temperature distribution on the cathode-side catalyst layer at a current density of 1.2 A/cm^2 . Temperature increases along the flow direction firstly and reaches a maximum at about $2/3$ of the channel length; then it decreases gradually towards the outlet due to heat transfer with the ambient air.

The maximum temperature of the infinite dimension stack modeling is 361.4 K , 1.4 K above unit cell's 360 K . For an actual fuel cell stack, the maximum temperature is expected to be a value in between, depending on stack dimensions and material properties.

Figure 4.6 Temperature distribution inside the cell for three loading conditions: 0.4A/cm² (top), 0.8A/cm² (middle), and 1.2A/cm² (bottom) (Refer to Figure 4.1 for coordinate system)

Figure 4.7 Temperature distribution on cathode-side catalyst layer for three loading conditions: 0.4 A/cm² (top), 0.8 A/cm² (middle), and 1.2 A/cm² (bottom)

Figure 4.8 Temperature distribution of infinite dimension stack modeling at current density $1.2\text{A}/\text{cm}^2$, slice plot (upper), tetrahedron plot (lower) (Refer to Figure 4.1 for coordinate system)

Figure 4.9 Temperature distribution on cathode-side catalyst layer of infinite dimension stack modeling at current density $1.2\text{A}/\text{cm}^2$

4.6.3. Current Density Distribution

As mentioned before, the current density distribution has a close relation with the hydrogen or oxygen distributions on the catalyst layers. The variation of hydrogen concentration is small at the anode catalyst layer; hence, the current density is uniformly distributed there. However, the oxygen distribution at the cathode-side catalyst layer varies significantly; accordingly, the local current density at the cathode-side catalyst layer changes with location in a great range.

Figure 4.10 shows the dimensionless local current density distribution for three different nominal current densities. The range of local current densities over the catalyst layer extends with the increasing of nominal current densities. At a current density of 0.4 A/cm^2 , the upper limit is 20% above the nominal and the lower limit is 17% below. The range increases to 50% higher and 36% lower than the average when the current density increases to 0.8 A/cm^2 . Furthermore, when the current density reaches 1.2 A/cm^2 , the local current density under the land area is just 20% of the nominal value, but it can be 178% higher than the nominal current density at the inlet. This highly uneven distribution of current density has great impact on overall cell performance and should always be avoided. These simulation results illuminate that a more effective catalyst utilization can be achieved by depositing a larger fraction of the catalyst under the land area and less nearby the cell inlet.

Figure 4.10 Dimensionless current density distribution i/i_{ave} on cathode-side catalyst layer for three loading conditions: 0.4 A/cm² (top), 0.8 A/cm² (middle), 1.2 A/cm² (bottom)

4.6.4. Water Content and Potential loss inside Membrane

Figure 4.11 demonstrates the distribution of water content for three nominal current densities. In all three plots, the lowest water contents occur at the upper boundary of the membrane, and they have exactly the same values as the 2D modeling results because the same constant value boundary conditions are applied there. On the other hand, the highest water contents occur at the lower boundary of membrane and near the channel inlet; these

values are slightly larger than the 2D modeling results, implying that in the 3D case the total amount of water production (condensation) is bigger than in the 2D simulations.

Consistent with the boundary condition setting for water transport, the electric potential on the upper boundary of the membrane is assumed to be a constant value - zero. The potential on the lower boundary satisfies equation (2.58), which is a function of current density. Figure 4.12 shows the potential distribution inside the membrane for three different loading conditions. Since the biggest local current density in the 3D modeling is higher than in the 2D modeling for each of the nominal current densities tested, the maximum potential loss in 3D modeling increases 15.2%, 16.4%, and 18.7% at current densities 0.4 A/cm^2 , 0.8 A/cm^2 , and 1.2 A/cm^2 , respectively, compared to the 2D case. Figure 4.13 compares the results of the maximum potential loss using different mathematical models. Overall, the potential loss in the 3D modeling is larger than in the 2D modeling, and the loss resulting from the new potential equation model is larger than that using the conventional Laplace's equation. At lower current densities, there is no big difference in the potential loss among these models, but when the current density approaches the limiting current density, discrepancies between these curves become significant and can not be neglected.

Figure 4.11 Water content in membrane for three loading conditions: $0.4\text{A}/\text{cm}^2$ (top), $0.8\text{A}/\text{cm}^2$ (middle), and $1.2\text{A}/\text{cm}^2$ (bottom) (Refer to Figure 4.1 for coordinate system)

Figure 4.12 Potential distribution inside membrane for three loading conditions: $0.4\text{A}/\text{cm}^2$ (top), $0.8\text{A}/\text{cm}^2$ (middle), and $1.2\text{A}/\text{cm}^2$ (bottom) (Refer to Figure 4.1 for coordinate system)

Figure 4.13 Comparison of maximum potential losses using different mathematical models

4.6.5. Polarization Curve

In the 3D simulations, after examining individual physical variables involved in the transport phenomena during fuel cell operation, the polarization curve is plotted to illustrate the overall performance of the fuel cell. As shown in Figure 4.14, the polarization curve resulting from the 3D simulation appears to be in good agreement with the 2D case. The 3D polarization curve remains below the 2D one, the reason being that various potential losses, such as the membrane potential loss investigated in the previous subsection, turn out to be bigger in the 3D simulation than in the 2D case; as a result, the cell voltage corresponding to the 3D case generally becomes smaller than in the 2D case. Nevertheless, Figure 4.14

confirms that both 2D and 3D models developed in this study can serve as a good tool for predicting fuel cell performance, as the biggest discrepancy is less than 4% when the nominal current density reaches its limiting value of 1.2 A/cm^2 in all numerical experiments performed in this thesis work.

Figure 4.14 Comparison of polarization curves using different models

Chapter 5. Conclusions and Outlook

5.1. Conclusions

Both two-dimensional and three-dimensional PEM fuel cell models have been developed in this work. These models are capable of predicting the bulk flow velocity background, the distribution of reactant gases, temperature, local current density, membrane water concentration and membrane potential loss. Parametric studies were performed using the 2D model, which revealed the effect of various operating conditions on the fuel cell performance. Modeling results were compared with the experimental results and good overall agreement was achieved.

5.2. Contributions

Three main contributions made in this thesis work are summarized as follows:

- I. A previous two-dimensional model was refined. The new water content equation and membrane potential equation were originally developed by Dr. J. Cao and Dr. N. Djilali [45]. In this thesis study, this new model was completed and refined. Changes and assumptions made to the existing model led to an overall increase of the computation speed without any compromise of accuracy.
- II. A detailed parametric study was conducted using the refined two-dimensional model.

Lots of transport details presented in Chapter 3 have not been published yet, which

constitutes an original contribution.

III. A three-dimensional model was developed and a 3D base case study was performed.

5.3. Recommendations

The results presented in this thesis are in good agreement with experimental results, and the model is able to provide insight into many of the physical phenomena which is hard to capture through experiments. However, there are still a number of improvements that may enhance the capabilities of the model to achieve better prediction for optimization of fuel cell design and reduction of its manufacturing cost:

- I. A more detailed catalyst layer model which can account for the variation of activation overpotential should be established. This model will help obtain a more accurate local current distribution.
- II. Develop a two-phase flow model that can account for liquid water transport in the porous electrodes after the liquid water removal mechanism is clearer.
- III. Conduct industrial-scale fuel cell stack modeling using parallel processing.

References

1. A. Parthasarathy, S. Srinivasan, A. J. Appleby, and C. R. Martin. "Pressure Dependence of the Oxygen Reduction Reaction at the Platinum Microelectrode/Nafion Interface: Electrode Kinetics and Mass Transport", *J. Electrochem. Soc.*, 139(10):2856-2862, 1992.
2. T. D. Gierke, G. E. Munn, and F. C. Wilson. "The Morphology in Nafion Perfluorinated Membrane Products, as Determined by Wide- and Small-Angle X-Ray Studies", *J. Polymer Science*, Polymer physics edition, 19:1687-1704, 1981.
3. E. A. Ticianelli, J. G. Beery, and S. Srinivasan. "Dependence of Performance of Solid Polymer Electrolyte Fuel Cells with Low Platinum Loading on Morphologic Characteristics of the Electrodes", *J. Electroanal. Chem.*, 251:275-295, 1988.
4. M. Mehta, J. S. Cooper, "Review and Analysis of PEM Fuel Cell Design and Manufacturing", *J. Power Sources*, 114:32-53, 2003.
5. A. J. Appleby and F. R. Foulkes. *Fuel Cell Handbook*. Krieger Publishing Company, Florida, 1993.
6. J. O'M Bockris and S. Srinivasan. *Fuel Cells: Their Electrochemistry*. McGraw Hill, New York, 1969.
7. J. Larminie and A. Dicks. *Fuel Cell Systems Explained*. Wiley, Chichester, 2000.
8. D. M. Bernadi and M. W. Verbrugge. "A Mathematical Model of the Solid Polymer Electrolyte Fuel Cell". *J. Electrochem. Soc.*, 139(9):2477-2491, 1992.
9. D. M. Bernardi and M. W. Verbrugge. "Mathematical Model of a Gas Diffusion Electrode Bonded to a Polymer Electrolyte". *AIChE J.*, 37(8):1151-1162, 1991.
10. T. E. Springer, M. S. Wilson, S. Gottesfeld, "Modeling and Experimental Diagnostics in Polymer Electrolyte Fuel Cells", *J. Electrochem. Soc.*, 140(12):3513-3526, 1993.
11. T. E. Springer, T. A. Zawodzinski, and S. Gottesfeld, "Polymer Electrolyte Fuel Cell Model", *J. Electrochem. Soc.*, 138(8):2334-2342, 1991.
12. T. F. Fuller, J. Newman, "Water and Thermal Management in Solid Polymer Electrolyte Fuel Cells", *J. Electrochem. Soc.*, 140(5):1218-1225, 1993.
13. T. V. Nguyen, R. E. White, "A Water and Heat Management Model of Proton Exchange Membrane Fuel Cells", *J. Electrochem. Soc.*, 140(8):2178-2186, 1993.
14. J. S. Yi, T. V. Nguyen, "An Along-the Channel Model for Proton Exchange Membrane Fuel Cells", *J. Electrochem. Soc.*, 145(4):1149-1159, 1998.
15. J. S. Yi, T. V. Nguyen, "Multicomponent Transport in Porous Electrodes of Proton Exchange Membrane Fuel Cells Using the Interdigitated Gas Distributors", *J. Electrochem. Soc.*, 146(1):38-45, 1999.
16. K. Promislow, J. M. Stockie, "Adiabatic Relaxation of Convective-Diffusive Gas Transport in a Porous Fuel Cell Electrode", *SIAM J. Appl. Math.*, 62(1):180-205, 2001.

17. J. M. Stockie, K. Promislow, B. R. Wetton, "A Finite Volume Method for Multicomponent Gas Transport in a Porous Fuel Cell Electrode", *Int. J. Numer. Methods Fluids*, 41:577-599, 2003.
18. V. Gurau, H. Liu, and S. Kakac. "Two-Dimensional Model for Proton Exchange Membrane Fuel Cells", *AIChE J*, 44(11):2410-2422, 1998.
19. S. Um, C. Y. Wang, and K. S. Chen, "Computational Fluid Dynamics Modeling of Proton Exchange Membrane Fuel Cells", *J. Electrochem. Soc.*, 147(12):4485-4493, 2000.
20. S. Um, C. Y. Wang, Proceedings of the ASME Heat Transfer Division, 1:19-25, 2000.
21. S. Um, C.Y. Wang, "Three-Dimensional Analysis of Transport and Electrochemical Reactions in Polymer Electrolyte Fuel Cells", *J. Power Sources*, 125:40-51, 2004.
22. S. Dutta, S. Shimpalee, J. W. Van zee, "Three-dimensional Numerical Simulation of Straight Channel PEM Fuel Cells", *J. Appl. Electrochem.*, 30:135-146, 2000.
23. S. Dutta, S. Shimpalee, J. W. Van zee, "Numerical Prediction of Mass Exchange between Anode and Cathode Channels in a PEM Fuel Cell", *Int. J. Heat Mass Transfer*, 44:29-40, 2001.
24. W. K. Lee, S. Shimpalee, J. W. Van Zee, "Verifying Predictions of Water and Current Distributions in a Serpentine Flow Field PEMFC", *J. Electrochem. Soc.*, 150(3):A341-A348, 2003.
25. T. Zhou, H. Liu, "A General Three-Dimensional Model for Proton Exchange Membrane Fuel Cells", *Int. J. Transport Phenom.*, 3:177-198, 2001.
26. T. Berning, D. M. Lu, N. Djilali, "Three-Dimensional Computational Analysis of Transport Phenomena in a PEM Fuel Cell", *J. Power Sources*, 106(1-2):284-292, 2002.
27. S. Mazumder, J. V. Cole, "Rigorous Three Dimensional Mathematical Modeling of Proton Exchange Membrane Fuel Cells. Part 1: Model Predictions without Liquid Water Transport", *J. Electrochem. Soc.*, 150:A1503-A1509, 2003.
28. H. Meng, C. Y. Wang, "Electron Transport in PEMFCs", *J. Electrochem. Soc.*, 151(3):A358-A367, 2004.
29. U. Pasaogullari, C. Y. Wang, 203rd Electrochemical Society Meeting, Paris, May 2003.
30. W. He, J. S. Yi, T. V. Nguyen, "Two-Phase Flow Model of the Cathode of PEM Fuel Cells Using Interdigitated Flow Fields", *AIChE J.*, 46(10): 2053-2064, 2000.
31. D. Natarajan, T. V. Nguyen, "A Two-Dimensional, Two-Phase, Multi-Component, Transient Model for the Cathode of a PEM Fuel Cell Using Conventional Gas Distributors", *J. Electrochem. Soc.*, 148:1324-1335, 2001.
32. D. Natarajan, T. V. Nguyen, "Three-Dimensional Effects of Liquid Water Flooding in the Cathode of PEM Fuel Cell Using Conventional Gas Distributors," *J. Power Sources*, 115:66-80, 2003.
33. Z. H. Wang, C. Y. Wang, K. S. Chen, "Two Phase Flow and Transport in the Air Cathode of Proton Exchange Membrane Fuel Cells", *J. Power Sources*, 94(1):40-50,

- 2001.
34. L. You, H. Liu, "A Two-Phase Flow and Transport Model for the Cathode of PEM Fuel Cells", *Int. J. Heat Mass Transfer*, 45(11):2277-2287, 2002.
 35. S. Mazumder, J. V. Cole, "Rigorous Three Dimensional Mathematical Modeling of Proton Exchange Membrane Fuel Cells. Part 2: Model Predictions with Liquid Water Transport", *J. Electrochem. Soc.*, 150:A1510-A1517, 2003.
 36. T. Berning, N. Djilali, "A 3D, Multi-Phase, Multicomponent Model of the Cathode and Anode of a PEM Fuel Cell", *J. Electrochem. Soc.*, 150(12):A1598-A1598, 2003.
 37. C. Y. Wang, "Fundamental Models for Fuel Cell Engineering", *Chemical Reviews*, 2004, in press.
 38. R. Perry, D. Green, *Perry's Chemical Engineering Handbook*, 7th edition, McGraw-Hill, 1997.
 39. R. B. Bird, W. Steward, and E. N. Lightfoot. *Transport Phenomena*. Wiley, New York, 1960.
 40. R. E. De La Rue and C. W. Tobias. "On the Conductivity of Dispersions", *J. Electrochem. Soc.*, 106:827-836, 1959.
 41. T. Berning, "Three Dimensional Computational Analysis of Transport Phenomena in a PEM Fuel Cell", Ph.D dissertation, University of Victoria, 2002.
 42. J. S. Newman. *Electrochemical Systems*. Prentice Hall, Englewood Cliffs, New Jersey, 1991.
 43. D. Singh, D. M. Lu, and N. Djilali, "A Two-Dimensional Analysis of Mass Transport in Proton Exchange Membrane Fuel Cells", *Inter. J. of Eng. Sci.*, 37:431-452, 1999.
 44. M. W. Verbrugge, R. F. Hill, "Ion and Solvent Transport in Ion-Exchange Membranes", *J. Electrochem. Soc.*, 140(5):1218-1225, 1993.
 45. J. Cao and N. Djilali, "Numerical Modeling of PEM Fuel Cells Under Partially Hydrated Membrane Conditions", *ASME J. Energy Resources Technology*, 127:26-36, 2005.
 46. Online support of Femlab, COMSOL Inc.
 47. E. A. Ticianelli, C. R. Derouin, A. Redondo, and S. Srinivasan. "Methodes to Advance Technology of Proton Exchange Membrane Fuel Cells", *J. Electrochem. Soc.*, 135(9):2209-2214, 1988.
 48. P. T. Nguyen, "A Three Dimensional Computational Model of PEM Fuel Cell with Serpentine Gas Channels", Master thesis, University of Victoria, 2003.
 49. A. Parthasarathy, B. Dave, S. Srinivasan, J. A. Appleby, and C. R. Martin. "The Platinum Microelectrode/Nafion Interface: An Electrochemical Impedance Spectroscopic Analysis of Oxygen Reduction Kinetics and Nafion Characteristics". *J. Electrochem. Soc.*, 139(6):1634-1641, 1992.
 50. M. J. Lampinen and M. Fomino. "Analysis of Free Energy and Entropy Changes for Half-Cell Reactions", *J. Electrochem. Soc.*, 140(12):3537-3546, 1993.

51. E. L. Cussler, *Diffusion-Mass Transfer in Fluid Systems*. Cambridge University Press, 1984.
52. F. P. Incropera and D. P. DeWitt. *Fundamentals of Heat and Mass Transfer*. Wiley, New York, fourth edition, 1996.
53. J. L. Fales and N. E. Vandeborough, "The Influence of Ionomer Channel Geometry on Ionomer Transport", *Electrochem. Soc. Proceedings*, 86(13):179-191, 1986.
54. A. C. West and T. F. Fuller, "Influence of Rib Spacing in Proton Exchange Membrane Electrode Assemblies", *J. of Appl. Electrochem.*, 26:557-565, 1996.
55. F. M. White, *Fluid Mechanics* (3rd edition), McGraw Hill, New Jersey, 1994.
56. http://www.cfdrc.com/bizareas/power/fuel_cell/pem.html