MULTIPLE EVIDENCE COMBINATION FOR WEB SITE SEARCH USING SERVER LOG ANALYSIS

TK
5105,884
Z46
2006

By

Jin Zhou

B.Sc. in Computer Science, Xidian University, China, July 1999

A thesis

Presented to Ryerson University

in partial fulfillment of the
requirements for the degree of

Master of Applied Science

in the program of
Electrical and Computer Engineering

Toronto, Ontario, Canada, 2006

© Jin Zhou 2006

UMI Number: EC53565

INFORMATION TO USERS

The quality of this reproduction is dependent upon the quality of the copy submitted. Broken or indistinct print, colored or poor quality illustrations and photographs, print bleed-through, substandard margins, and improper alignment can adversely affect reproduction.

In the unlikely event that the author did not send a complete manuscript and there are missing pages, these will be noted. Also, if unauthorized copyright material had to be removed, a note will indicate the deletion.

UMI[®]

UMI Microform EC53565
Copyright 2009 by ProQuest LLC
All rights reserved. This microform edition is protected against
unauthorized copying under Title 17, United States Code.

ProQuest LLC
789 East Eisenhower Parkway
P.O. Box 1346
Ann Arbor, MI 48106-1346

AUTHOR'S DECLARATION

I hereby declare that I am the sole author of this thesis.

I authorize Ryerson University to lend this thesis to other institutions or individuals for the purpose of scholarly research.

Signature

|

I further authorize Ryerson University to reproduce this thesis by photocopying or by other means, in total or in part, at the request of other institutions or individuals for the purpose of scholarly research.

Signature

|

u

|

Multiple Evidence Combination for Web Site Search Using Server Log Analysis

Master of Applied Science, 2006

Jin Zhou

Electrical and Computer Engineering
Ryerson University

ABSTRACT

In this thesis, a novel method is proposed to improve the retrieval performance by using web server logs. Web server logs are grouped into different sessions and then terms are extracted for each page in the session, meanwhile weights of terms are calculated. A new representation of web page from user's perspective is generated after going through the entire log. The new representation and the anchor-based representation are combined with original text-based representation. Two combination methods: combination of document representations and combination of ranking scores are investigated. In the experiments, three measurements are employed to evaluate the performance and the results show that for Cosine Similarity model, the highest improvement on top-10 precision is around 38%, for Okapi model, the highest improvement is around 13%, for TFIDF model, the highest improvement is around 48% and for Indri model, the highest improvement is around 17%.

ACKNOWLEDGEMENTS

Although this thesis represents my individual work, there are various people who, during the past two years, provided me with useful and helpful assistance and support. Without their care and support, this thesis would likely not have accomplished.

Firstly, I would like to express my deepest gratitude to my academic and research supervisor Dr. Cherie Ding for her guidance and constant support in helping me to conduct and complete this work. She discussed with me, kindly helped me solve problems I encountered when doing research work, and always gave me encouragement, which inspired me to keep stepping forward. To Cherie, heartfelt thanks.

I want to thank my co-supervisor Dr. Dimitri Androutsos for his kind help and encouragement when my supervisor was on vacation. He always shows his caring whenever we meet. He also invested time to review my thesis carefully and provide valuable comments. To Dr. Eric Harley, I would like to give the grateful thanks for his help in the experiment setup, providing undergraduate students to evaluate the experiment results. I also appreciate computer science department system administrators who provided web logs for this research. Without their support, the study could not be done.

I also would like to thank Romulo Velasquez and Vincent Wu, for their participation in this study work. Because of their help, I could speed up my research work. And also because of their efforts to evaluate the retrieval results, I could analyze the experimental results more accurately based on their evaluations. To those students who were involved in the final experiment evaluation, I appreciate their time and careful cooperation.

Many thanks to all the people I have come to know in computer engineering department, whose friendship and companionship I will always enjoy and get refreshed. I owe my sincere appreciation to my wife Zhuoyan Huang, who gave me space and consistently encouraged me while I was studying. These acknowledgements would not be complete without recognizing my parents. I could not do this without their unfailing love, affection and invaluable support in my life and studies. To each of them, my thanks and my love.

TABLE OF CONTENTS

AUTHOR'S DECLARATION	ii
ABSTRACT	iii
ACKNOWLEDGEMENTS	iv
TABLE OF CONTENTS	v
LIST OF TABLES	vii
LIST OF FIGURES	viii
CHAPTER 1 INTRODUCTION	1
1.1 Background	2
1.1.1 The Retrieval Process	2
1.1.2 General Issues of Web Search	3
1.2 Motivation	4
1.3 Research Goals and Approaches	6
1.4 Thesis Outline	7
CHAPTER 2 LITERATURE REVIEW	9
2.1 Click-through Data	9
2.2 Document Transformation	10
2.2.1 Document Expansion	11
2.2.2 Document Surrogates	12
2.2.3 Other Ways of Document Transformation	13
2.3 Web Logs for Web Site Search	14
2.4 Link Analysis	15
2.5 Combination Methods	16
2.6 Relevance Propagation	17
CHAPTER 3 WEB LOG BASED REPRESENTATION GENERATOR (WLBRG)	18
3.1 Web Log Purge	18
3.2 Session Detection and Representation	20
3.3 Extracting Entry Terms and Propagating to Other Pages	24
3.4 Page Merging	28
CHAPTER 4 RETRIEVAL MODELS AND COMBINATION OF MULTIPLE SOURCES	32
4.1 Cosine Similarity Model	32
4.1.1 Similarity Measurements	32
4.1.2 Weighting Schemes	34
4.1.3 Ranking Documents	35
4.2 TFIDF Model	35
4.3 Okapi Model	36
4.4 Indri Model	38
4.4.1 Inference Network	38
4.4.3 Indri Model Overview	39
4.5 Anchor Database	43
4.6 Combination of Multiple Evidential Sources	45
4.5.1 Combination of Ranking Scores	45
4.5.2 Merging of Document Representations	48

CHAPTER 5 EXPERIMENT AND ANALYSIS.....	51
5.1 Data Set.....	51
5.1.1 Databases	51
5.1.2 Database Summary	56
5.1.3 Query.....	57
5.2 Implementation	58
5.2.1 Retrieval Models.....	58
5.2.2 Summary of Models and Databases.....	61
5.3 Evaluation Method.....	61
5.3.1 Top 10 Precision	62
5.3.2 R-Precision.....	63
5.3.3 Average Precision	63
5.3.4 Notes	63
5.4 Results and Analysis.....	63
5.5 Discussion.....	75
CHAPTER 6 CONCLUSIONS	78
REFERENCES	80
APPENDICES	87
A. Top 10 Precision	87
B. R-precision	88
C. Average Precision	89

LIST OF TABLES

Table 5- 1. Format list of web pages. 51

Table 5- 2. Database list used in the experiment. 56

LIST OF FIGURES

Figure 1- 1. The process of retrieving information [3]	2
Figure 3- 1. The workflow of WLBRG.	18
Figure 3- 2. Web access logs in www.scs.ryerson.ca web server.	19
Figure 3- 3. Web referrer logs in www.scs.ryerson.ca web server.....	20
Figure 3- 4. The merged access logs and referrer logs from in www.scs.ryerson.ca web server.....	22
Figure 3- 5. The merged access logs and referrer logs grouped by users.....	22
Figure 3- 6. Session detection algorithm in WLBRG.....	23
Figure 3- 7. The web pages visited by the web user in one session.	24
Figure 3- 8. The propagation process in one session.....	25
Figure 3- 9. Terms extracted in the search engine as a new representation for the web page.....	26
Figure 3- 10. Session information extracted from web logs.....	28
Figure 3- 11. Page extracted from different sessions.	29
Figure 3- 12. The algorithm of page merging from different sessions.....	30
Figure 3- 13. The new representation of page from web log data.....	31
Figure 4- 1. The cosine is adopted as similarity value between document and query.	33
Figure 4- 2. The explanation for the formula (4-19) – (4-21).	37
Figure 5- 1. Web page content database with SGML format.	52
Figure 5- 2. Anchor text database with SGML format.	53
Figure 5- 3. Web pages propagation in the session.	53
Figure 5- 4. Log-based database with SGML format with propagation depth = 3.....	54
Figure 5- 5. Combined web page content and anchor text database with SGML format.	54
Figure 5- 6. Combined web page content, anchor text and web logs database with SGML format.....	55
Figure 5- 7. Combined web page content and anchor text database with SGML format for the Indri Model.	56
Figure 5- 8. Query with SGML format.....	57
Figure 5- 9. Query with fields for indri retrieval.....	60
Figure 5- 10. Query without field for indri retrieval.	60
Figure 5- 11. Precision and Recall for a given example information request.	62
Figure 5- 12. Precisions of different retrieval models and methods.....	66
Figure 5- 13. Precisions of different retrieval models and methods based on queries.	68
Figure 5- 14. R-precisions of different retrieval models and methods.....	70
Figure 5- 15. Average precisions of different retrieval models and methods	73

CHAPTER 1 INTRODUCTION

The World Wide Web has been growing explosively since its creation and no one could have imagined its current impact. The web has permeated our daily lives and is changing the way we think, work, and live. Each day there are hundreds of millions of users who generate over a billion clicks through the myriad of accessible web sites. This triggers the need for efficient tools to manage, retrieve and organize information from these huge web spaces. In recent years, global search engines, such as Google (google.com), AltaVista (altavista.com) , Yahoo! (yahoo.com) and MSN (msn.com) , have been a great help for users to search information on the growing web. Millions of searches are conducted on these search engines.

After people obtain the retrieved results from global search engines, they usually click some URLs to enter these particular web sites, and once at a site, they might find information they are searching for in a linked page immediately or they might browse or conduct a web site search to further their information seeking tasks [1]. For example, a student searches some courses or professor information in a departmental web site; a potential customer of Amazon searches for a specific book or DVD on the Amazon website. Recently, web site search has been getting more and more of the spotlight in industry. For example, Google Search Appliance (google.com/enterprise/) deployed and running directly in the local web site allows searching action to restrict search results to a specific web site.

However, users often suffer from the performance issues of web site search. When a query is submitted, a lot of irrelevant results are returned or the most relevant pages are not listed in the top 10 results. In the Forrester survey [2], the search facilities of 50 websites were tested, but none of them produced a satisfactory result according to the query. For example, the most relevant pages were rarely put in the first page of results; the best matched web pages were not retrieved and many irrelevant results were returned.

The primary focus of this thesis is to investigate web site search technology and attempt to improve the performance of web site search by using more complete and more detailed complementary information in addition to full text content.

1.1 Background

1.1.1 The Retrieval Process

To clearly demonstrate the basic retrieval process, there is a simple software architecture shown in Figure 1-1. First of all, before allowing user submit query, the search engine has to prepare data for searching. In the left bottom in Figure 1-1, web crawlers, the programs that traverse the web starting from a set of URLs, are running to download the original web pages. After the crawlers download the web pages, parsing programs perform the text operations on the web pages. The text operations deal with the original web pages and generate a text based database.

Figure 1- 1. The process of retrieving information [3]

Once the database is created, indexing programs build an index of all web pages. Here different retrieval model may use different approaches to build index. The index determines the speed of search against large volumes of data. Among different index structures the most popular one is the inverted file [3].

After the web page database is indexed, the search engine is ready to accept user's query. Users submit their queries through the visual interface, these queries submitted by users are pre-processed by query operation programs which is similar to text operations. Once the process is done, the search engine starts to compare each web page with queries.

Before returning the results to the user, the search engine ranks the web page according to a likelihood of relevance to the user need or query. Here again, the methods to compute similarity between web page and query may vary in different retrieval models. Once user obtains the results, he or she may click on some of results to go into for details. The search engine could record these click information and initiate a user feedback cycle. In such a cycle, the search engine uses the web pages selected by the user to expand the query information to better represent what the user really wants to search.

1.1.2 General Issues of Web Search

In the real world, when a query is submitted, search engines return a list of ranked web pages with the most relevant documents on top, but also include many irrelevant documents. There are two major reasons for this.

- Shortness of queries: Existing web search engines often calculate the correlations between web pages and given queries by counting the search keywords contained in the web pages. This method works well only if the user has full knowledge about the web pages and submits a clear and specific query. However, in reality, web users typically submit short queries to search engines – less than 3 words [4].
- Ambiguity of terms: Web pages are created by innumerable persons independently. The terms they use vary greatly. For example, “extra exercise” and “extra practice” might express the same meaning. On the other hand, users usually tend not to use the words appearing in the web pages as search terms so web queries are often

ambiguous. The gap between the query space and the web page space [5], [6] raises a fundamental problem of term mismatch in information retrieval.

However, the performance of web search can be improved by using link analysis algorithms such as PageRank [7] and HITS [8] which use eigenvector calculations to identify authoritative pages based on hyperlink structures.

Click-through based algorithms such as DirectHit (directhit.com) can also partially solve the problems mentioned above. Click-through data normally contain user-submitted search queries, followed by the URL of web pages which are clicked by users. If a user clicks on a web page, it is likely that the web pages are relevant to the query to some extent. Using click-through data as the additional metadata can narrow the gap between user's query space and the web page space and reduce the risk of losing relevant web pages.

As mentioned before, since users like to submit short queries, normally between two to three terms in length, which traditional search interfaces also encourage them to do [9], relevance feedback would be an effective way to improve retrieval accuracy [10], [11]. However, in the real world, users are usually reluctant to engage additional activities to provide their feedback [12]. For this reason, implicit feedback has attracted much attention [12], [13], [14], [15], [16]. In fact, since click-through analyzes information from a user's operation, it can also be considered as a kind of implicit feedback.

1.2 Motivation

In reality, when web users conduct a search, they usually perform the mixed action of searching and browsing. Normally a user would like to submit a general query, for example "java programming course", and when the web search returns a list of ranked pages, the user will probably click some URLs in the results thus conducting web browsing. When a user stays on a certain web site, he or she may be interested in other courses, such as Data Communications, thus he or she will conduct the web site search for the course description of Data Communications. This situation happens quite often. However, web site search has not been very successful even although it has made

significant progress in recent years. The IDC company's white paper entitled "The high cost of not finding information" [17] reports that information workers spend from 15% to 35% of their work time on searching for information and 40% of information workers complain that they cannot find the information they need to do their jobs on their company web site.

Many commercial systems [18], [19], [20], [21] have been developed for web site search and most of them view the web site search problem as web search problem described above in 1.1.2. But it is necessary to look into the differences between web search and web site search before trying to improve the performance of web site search.

Web search is used to conduct a search on the entire web, while web site search is used to conduct a search in one particular web site. Although the whole web and web site have the same basic overall structure, (each being a collection of documents connected by hyperlinks), there are a few qualitative differences between them.

Firstly, web site is often designed to be informative and functional rather than to contain extra irrelevant descriptions; while web is more general. A small number of individuals such as employees, or IT contractors are assigned to create and maintain the web pages for certain web site. In this sense, the content creation in the web site tends to grow more autocratic while the whole web tends to grow more democratically. Within a web site, there is not much incentive for a web page designer or creator to strive to design a particularly good web page that attracts traffic from the users of the web site. All documents are well organized and there is no competition to attract web visitors' attention among different web pages.

Secondly, the information contained in the web site is much more narrow as compared to the whole web since the web pages in the web site are just a tiny portion of the whole web. In addition, the web page creators construct web pages using their own "vocabularies" or terms. If a user uses a search term outside of this vocabulary, it is possible that no result is returned since they use different terms to express the same meaning. While in the whole web, the situation rarely happens because whole web has many web pages which together consist of more diverse "vocabulary".

Thirdly, since a web site contains a limited number of web pages, when users search for a certain topic, there are small sets of relevant pages. So pages in the top

position are especially important. However, when retrieving information from the web, there may be lots of relevant pages. So pages in top positions may all be relevant but not most important to the topic that the user wants to search.

Lastly, entire interaction logs of a web site are available. For the web, it is nearly impossible to get the entire operation logs of different web sites.

Because of these differences between the web and a specific web site, link analysis algorithms designed for whole web search, such as PageRank [7] and HITS [8], cannot be used equally effectively for web site search as for web search. Click-through based algorithms assume that a page is relevant to a query if it is visited by a web user. If a user accesses one page unintentionally, it is not valid to give this page a higher score just because it has been visited. So in this sense, click-through data may introduce noise to the database about web page content. This also happens in web site search. Since a web site has its own web logs which contain more complete information than click-through data, web logs are a good resource to use for web site search.

Web Usage Mining [22] is the “automatic discovery of user access patterns from web servers”. The performance of web site search can be improved by taking advantage of web logs, because these logs can save the browsing behaviors of users, which reflect the importance of a web page from a web user’s point of view and also relationships among web pages. Prior to this research, there has been no effort devoted to improving retrieval accuracy for web site search by creating a new document representation using web logs.

1.3 Research Goals and Approaches

In this thesis, a new algorithm for web site search is proposed. The novel algorithm - Web Log Based Representation Generator (WLB RG), is applied to web server logs to generate a new document representation for each page appearing in web server logs. In the algorithm, session detection and term propagation in each session are conducted. When propagating terms in the session, the algorithm considers access time of pages visited, duration of visit and also similarity between two pages. After the new

document representation based on web logs is generated, some retrieval models are applied, and ranking scores of web pages can be computed.

In many cases, anchor text, which is defined as the “highlighted clickable text displayed for a hyperlink in the web page” [23], shares the same characteristic with query terms. Since anchor text is typically very short, and provides a summarization of the target web page, the process of creating anchor text for a web page is a close approximation to the kind of summarization presented to users by a search engine for most queries. When anchor text terms match a query, the target web page is usually quite relevant to the query. Since anchor text is proved to be useful for improving web site searching, anchor text is extracted to be used as further evidence to support web site search in this thesis.

The objectives of this thesis are:

- To develop and implement the WLBRG algorithm.
- To investigate combining multiple sources for web site search: document representation based on (1) original text, (2) web logs and (3) anchor text.
- To experiment with several retrieval models: Cosine Similarity, Okapi, TFIDF, and Inference Networks and with different parameter settings for each model.

1.4 Thesis Outline

This thesis consists of six chapters in total. Chapter 1 has given a brief introduction about this study, including background, motivation, and research goals and approaches. Chapter 2, literature review, will give a description of related work which has been carried out in the area of web site search. The topics will cover web log based, link-based, click-through data based algorithms, and combination methods of multiple data sources.

A model of web log analyzer is described in chapter 3. This model is based on access logs and referrer logs recorded by the web server. The model transforms data from the raw logs to a new log-based document representation for web pages.

Chapter 4 presents several retrieval models, and methods for combining multiple data sources.

Experimental design and experiment analysis will be covered in chapter 5, where the methods of evaluation of the new algorithm are discussed. Finally, chapter 6 is the conclusion where the thesis is summarized and recommendations for future research are given. Some original experimental data is attached in the Appendix.

CHAPTER 2 LITERATURE REVIEW

Most internet searches are launched by casual users making simple queries on popular topics. Because such vague queries can generate tens of thousands of hits, the ranking of a document's relevance to a query is a key technology for search engines. Common information retrieval theory offers models for measuring the similarity between user-defined query and document content. These models include the Vector Space Model, probabilistic models, and fuzzy logic models [24].

Recently the retrieval models not only apply to the original web page content but also to new content such as additional metadata to enhance the performance of IR systems. For example, anchor text [23], [25], [26], [27] was used to enhance web search. These methods improve the retrieval accuracy of web search to some extent. For instance, Google's search engine [25] takes the anchor text as its metadata to improve the performance of its search engine.

The following subsections will give more details about research which is closely related to the work in this thesis: click-through data, document transformation, web logs, link analysis, combination, relevance propagation.

2.1 Click-through Data

Click-through data in search engines can be thought of as triplets (q, r, c) consisting of the query q , the ranking r presented to the user, and the set c of links the user clicked on in the result page. It is assumed that users do not click on links at random, but make some informed choice. The key point of click-through data is that although these clicks don't reflect the exact relevance to the query, they provide valuable indications to the user's intention by associating a set of query terms with a set of web pages. If a web page's URL is hit by the user, it is likely that this web page is relevant to the query.

Joachims [12] described the approach to store the click-through data by using a proxy system. He developed an approach, Support Vector Machine, to learning ranking functions over a finite domain by using click-through data.

Brian et al. [28] used the co-visited method to apply user click-through data and the basic assumption of the method is that two web pages are similar if they are co-visited by users with similar queries, and the associated queries of the two web pages can be merged as the metadata for each other.

Based on this method, Xue et al. [29] proposed an iterative reinforcement algorithm for computing the similarity between web pages and queries, which fully explores the relations between web pages and queries. After the similarity between web pages and queries are computed, two web pages can share queries if their similarity value is greater than a threshold value. They assign the queries of one page to its similar pages as extra metadata. Although their experimental results on a set of MSN click-through data demonstrated an improvement of search performance, the click-through data has limitations – it is noisy, incomplete and sparse. Xue et al. didn't consider the similarity of the content of the queries and the web pages while implementing the iterative algorithm. So if one page is irrelevant to query, all following pages in the iterative process are irrelevant to the query. In this sense, the algorithm is not accurate enough. Furthermore, they only considered web pages which were clicked following at least one query while there may be many web pages without click-through data.

2.2 Document Transformation

The hope of IR systems in the vector space model is that the vector of a document relevant to the user's query is located close to the vector of the query. Document transformation approaches aim to narrow the gap between the document space and query space from the document's perspective by moving the document vectors in the direction of the query. Those which are irrelevant are moved away. There are different ways to do document transformation as described below.

2.2.1 Document Expansion

Document expansion (DE), changing the document by adding more terms based on queries, has recently been applied in various areas of IR systems. DE was firstly used by Pereira [30] in the context of speech retrieval. Li and Meng [31] used DE for spoken document retrieval. They found a 56% improvement in Cantonese monolingual retrieval and 14% in Mandarin cross-language retrieval. Both Lester and Williams [32] as well as Levow and Oard [33] have used DE for topic tracking. Lester and Williams used DE to enrich topic profiles and the latter got consistent improvements in Mandarin cross-lingual retrieval by using DE techniques.

Billerbeck and Zobel [34] proposed two ways to expand documents: document centric DE and Term centric DE.

Document Centric DE

For the DE technique, each complete document is run as a query q , the ranked results are returned based on the query q , and then the top N expansion terms determined from the top 10 results through local analysis are appended to the document. This process is similar to the conventional query expansion [35]. In their experiments, they found that augmenting a document with 10% of the number of tokens in a document works best, rather than adding a fixed number of terms or using a global threshold value for the selection value of each candidate term. However, the potential problem with DE is that terms which are used for augmenting documents tend to be quite rare across the collection. Adding rare terms to documents means that, after expansion, those terms will be less rare, which may have an effect on retrieval performance.

Term Centric DE

Assuming that a query only has one term, the role of query expansion [35] is to identify documents that are about this term, but do not necessarily include this term. Firstly, top 10 ranked results to the query are taken as the local document set, and then top N terms from the local document set are extracted and added to the query which now has no term. Secondly, the expanded query is run again to retrieve documents that do not contain the query term but that do contain expansion terms. DE inverts this scenario: it

puts the query term into those documents that contain the expansion terms. This has the effect of adding potential query terms that are on the same topic as the document but are missing in that document. A problem arising in this approach arises in a situation where the collection grows, such as the web. Since the basis for selecting expansion terms changes with the addition of new documents, the terms previously chosen for a particular document might be sub-optimal. Furthermore, it is difficult to determine the best expansion terms for added documents, since they did not exist when the collection was originally ranked according to terms.

2.2.2 Document Surrogates

Document surrogate is another representation of a document that differs from the full text content. These approaches have been examined for many applications including summarization [36], [37], graphical display of results [38], and document browsing [39], etc.

Surrogates using Anchor Text

Based on the assumption that the *anchor text* of a hyperlink, which links to another page from current page, describes its target web page, Craswell et al. [40] have investigated constructing *document replacements* composed of the anchor text that points at a page. Document replacements are surrogates where the new content replaces the original content of the document. In their approach the anchor text is treated as though it represents the target document in some degree and is then used to replace its content. Experiments demonstrated that the use of anchor text can significantly improve retrieval effectiveness for named page finding tasks where the subject of the search is a known resource. Therefore, in-link anchor text is well-known as an alternative method of creating document surrogates.

Surrogates using Query Association

Query association is a technique to store the relationship between past queries and documents. For document summarization, Scholer, Williams, and Turpin [41] found that each query should be associated with the three top-ranked documents and that five

queries should be stored per document. With these settings, document summaries are composed only of queries that have high similarity to each document, while the cognitive load for the user is kept low. This way, the simplest approach of surrogate creation using query association is to associate each query with a fixed number of documents and to limit the number of associations stored in each document. They imposed an upper limit of M associations per document, which serves two purposes. First, it affords a predictable space and time requirement for managing associations. Second, once this maximum number is reached, existing associations can be updated or replaced by new queries with higher similarity to the document, which allows the associations to evolve and adapt to any temporal shift in user queries, and also allows dissimilar queries to be unassociated.

In their experiments, they showed that the document surrogates using query associations improved the accuracy of topic finding searches by 4%-7%. However, the problem is that associations must be created and updated during query evaluation process, and for large collections, time and space to calculate the query associations become significant. In addition, associated queries also need to update if the web page changes occur. It is always necessary to investigate the tradeoffs and determine how associations can be used to speed the web search.

2.2.3 Other Ways of Document Transformation

In literature some other algorithms for document transformation can be found. For example several approaches for document transformation are listed in [42]:

$$D = (1 - \alpha)D + \alpha \frac{|D|}{|Q|} Q \quad (2-1)$$

$$D = D + \beta Q \quad (2-2)$$

$$D = D_{original} + D_{learned}, \text{ whereas} \quad (2-3)$$

$$D_{learned} = \begin{cases} D_{learned} + \beta Q, & \text{if } |D_{learned}| < l \\ (1 - \alpha)D_{learned} + \alpha \frac{|D_{learned}|}{|Q|} Q, & \text{otherwise} \end{cases}$$

Here Q is the vector of user query and D is the vector for the relevant document. $|D|$ is the norm of D , i.e. the sum of all term weights in D . l is a threshold.

The strategy in equation (2-1) ensures that the length of the document vector keeps constant. This strategy has been shown to be able to improve the retrieval results on small and middle sized document collections.

The strategy in equation (2-2) is the most simple, but it performs well on a low quantity (less than 2000) of queries [42]: terms of Q are weighted with β and then appended to the document vector D . In [42] the method appears unaffected by document vector saturation and achieves a stable improvement of around 8% over the control system. But it should be noted that this strategy causes the length of the document to grow without limits.

Both strategies are sensitive to a super saturation. If many queries are associated with a relevant document then the effect of the initial document terms is decreased with the growing amount of terms from associated queries. Thus, document saturation is a serious problem in search engines. To solve this issue, an upper bound M is used to restrict the growing of the document as mentioned in the Document Surrogates section. The strategy in equation (2-3) has also been developed for this purpose.

2.3 Web Logs for Web Site Search

Generally, the process of discovering useful patterns from web logs is called *log mining* [43] or *usage mining*. Log mining involves straightforward statistical methods, such as page access frequency, as well as more sophisticated forms of analysis, such as association rule mining, sequential pattern mining, and clustering.

Xue et al. [44] developed a general log mining model based on rule mining [45] to discover generalized association rules for web site search. They assume that consecutive accesses from the same host during a certain time interval come from the same user. First, they group consecutive entries into a user session or transaction. After that, they construct a taxonomy which is initialized with only the root which represents the top level of the website. Then their model uses the log files and taxonomy as the input, and output a set of association rules. When a user submits a query, a full-text search engine finds all the relevant web pages and these web pages are then re-ranked by the association rules. In the experiments, their proposed algorithm outperforms the “full text

search” and DirectHit algorithm. But they assume the underlying page organization reflects the semantics of the web pages when constructing the taxonomy. In fact, this assumption is not accurate. It is better to construct the taxonomy based on the semantics of the web page content rather than hierarchy of the web site.

2.4 Link Analysis

Link analysis technology has been widely used to analyze a page’s importance, such as HITS [8] and PageRank [7]. Link analysis algorithms use eigenvector calculations to identify authoritative pages based on hyperlink structure. In the structure, each hyperlink represents a recommendation relationship. Formally, there is the following recommendation assumption [46]: a hyperlink in page X pointed to page Y stands for the recommendation of page Y by the author of page X . For the global web, the recommendation assumption is generally correct because hyperlinks encode a considerable amount of author’s judgment. However, in a small web, hyperlinks are created by a small number of authors, usually content is organized in a hierarchical or linear structure, and thus the recommendation assumption is not valid for the site search.

In a specific web site, hyperlinks could be divided into *navigational links* and *recommendation links*. The latter is useful for link analysis to enhance site search. In fact, there are many *implicit recommendation links*, or *implicit links*, in a small web that could be discovered by mining user access patterns. In [47], the authors proposed an approach to utilize implicit link analysis to improve the site search. They generated implicit link structure based on user access pattern from web server logs. After obtaining the implicit link structure, a link analysis algorithm similar to PageRank [7] is used to re-rank the web page. The re-ranking mechanism is based on two types of linear combinations: score based re-ranking and the order based re-ranking. The score based re-ranking uses a linear combination of content-based similarity score and the PageRank value of all web pages. The order based re-ranking is based on the rank orders of the web pages.

From their experiments, their algorithm based on link analysis outperforms the other algorithms they used. Their solutions to cluster web pages are based on the content and explicit links of web pages, but the explicit links in web site are only for content

organization, so it is difficult to get good clustering results by using the explicit links. There is still space to research on using implicit links within web logs.

Cui and Dekhtyar [48] proposed the LPageRank algorithm for web site search. First they analyzed web logs and constructed a probabilistic graph of the web site. Then LPageRank was performed on the graph. From their preliminary experimental results, it can be seen that LPageRank combined with TFIDF is not good enough to out-perform Google's web site search.

2.5 Combination Methods

Combination of multiple sources [49], [50], [51] is very effective for web search. Linear combination is mostly used combination model. Lee [50] evaluated a variety of combination methods, such as CombMIN (minimum of individual similarity), CombMAX (maximum of individual similarity), CombSUM (summation of individual similarity), CombANZ ($\text{CombSUM} / \text{number of nonzero similarities}$), CombMNZ ($\text{CombSUM} * \text{number of nonzero similarities}$), and also investigated the effect of rank order instead of similarity in combining multiple evidences. In the experiments, he found that CombMNZ provided better retrieval effectiveness and using rank gave better results than using similarity in combining multiple evidences in some circumstances.

Ogilvie and Callan [52] investigated combination of document representations. They introduced two ways to combine document representations in IR system. The first one called meta-search approach treats each document representation as a unique search model which may use different search algorithms, and then combine retrieval results from these multiple search models to generate one ranked result. The second one called language modeling approach combines the document representations into one language model, and then applies a certain search algorithm to the mixed language model. They also proposed a mixture-based retrieval model and experiment the use of citations, which used link text and additional structure information on the web [53], [40], [54]. In their results they found that using link text is beneficial for site search. Another approach of combining representations within a retrieval model was proposed in [54]. Myaeng et al. [55] used Bayesian inference networks to combine terms found in the different document

representations. Fagin et al. [56] proposed a novel architecture that combined various ranking heuristics through the use of a rank aggregation algorithm. Their aggregation algorithms take as input multiple ranked lists from various heuristics and produce an ordering of the pages.

2.6 Relevance Propagation

Many relevance propagation methods [25], [57], [58] have been proposed recently to enhance relevance weighting schemes. Qin et al. [59] provided a comparison study on the effectiveness and efficiency of various propagation models and also proposed a generic relevance propagation framework. Through their experiments, they found that relevance propagation can significantly boost the performance of web information retrieval.

CHAPTER 3 WEB LOG BASED REPRESENTATION GENERATOR (WLBRG)

Web server logs are an important source to benefit web site search because they reflect the judgments on the page content from web users. In this chapter, we introduce WLBRG and show how it generates a document representation based on web server logs. Figure 3-1 illustrates the workflow of WLBRG. As we can see in Figure 3-1, the model uses web server logs as input, and outputs a new document representation. There are several steps involved including session detection, term propagation and page merging.

Figure 3- 1. The workflow of WLBRG.

3.1 Web Log Purge

A user may be identified as a real person, a computer or automated software, such as a web Crawler (i.e. a spider), accessing files from different servers over the WWW. For security reasons, the web server logs never record the user name and password, so the simple way to identify users is to consider that one IP address corresponds to one distinct user. This is simplified but not accurate since different users may share an IP address when using the same computer or several computers being behind the same firewall.

Web logs contain the following fields: *client IP, user name and password* (normally represented by “-”), *access time, HTTP request method used, URL, protocol used* (HTTP/1.0, HTTP/1.1), *status code, number of bytes transmitted, referrer*. An

example is shown below, which is composed of access log and referrer log. In this example, a user with IP 164.164.164.164 (IP is not real for privacy) has requested web page /~mth108/fractals/index.html on September 1st, 2005 at 01:15:57. The size of the page transmitted is 6006 bytes. The client is referred from http://scs.ryerson.ca/~mth108/, which is recorded in the referrer log.

```
164.164.164.164 - - [01/Sep/2005:04:10:21 -0400] "GET /~mth108/fractals/index.html
HTTP/1.1" 200 6006 http://scs.ryerson.ca/~mth108
```

In Figure 3-2, there are altogether five users, IPs are not complete for privacy reasons. A click-stream can be defined as a time-ordered list of page views. Figure 3-3 shows the referrer logs where the first column is URL in the access logs and the third column shows the referrer of the URL.

```
x.x.x.163 - - [26/Sep/2005:19:59:09 -0400] "GET /~mth110/F05/Labs/index.shtml HTTP/1.1" 200 4046
x.x.x.163 - - [26/Sep/2005:19:59:19 -0400] "GET /~mth110/F05/Labs/lab2.shtml HTTP/1.1" 200 3315
x.x.x.65 - - [26/Sep/2005:19:59:30 -0400] "GET /~aferworn HTTP/1.1" 301 330
x.x.x.65 - - [26/Sep/2005:19:59:30 -0400] "GET /~aferworn/ HTTP/1.1" 200 3038
x.x.x.65 - - [26/Sep/2005:19:59:31 -0400] "GET /~aferworn/clouds.gif HTTP/1.1" 200 14259
x.x.x.65 - - [26/Sep/2005:19:59:31 -0400] "GET /~aferworn/images/ryerson.gif HTTP/1.1" 200 2664
x.x.x.65 - - [26/Sep/2005:19:59:31 -0400] "GET /~aferworn/images/N-CARTlogo.jpg HTTP/1.1" 200 53793
x.x.x.65 - - [26/Sep/2005:19:59:31 -0400] "GET /~aferworn/alexwork.gif HTTP/1.1" 200 49162
x.x.x.65 - - [26/Sep/2005:19:59:31 -0400] "GET /favicon.ico HTTP/1.1" 404 299
x.x.x.65 - - [26/Sep/2005:19:59:38 -0400] "GET /~aferworn/courses/CPS607/INDEX.HTML HTTP/1.1" 200 2426
x.x.x.65 - - [26/Sep/2005:19:59:38 -0400] "GET /~aferworn/courses/CPS607/IMAGES/RYERSON.GIF HTTP/1.1" 200 2661
x.x.x.65 - - [26/Sep/2005:19:59:38 -0400] "GET /~aferworn/courses/CPS607/IMAGES/welcome.gif HTTP/1.1" 200 3694
x.x.x.65 - - [26/Sep/2005:19:59:38 -0400] "GET /~aferworn/courses/CPS607/IMAGES/trired.gif HTTP/1.1" 200 901
x.x.x.65 - - [26/Sep/2005:19:59:38 -0400] "GET /favicon.ico HTTP/1.1" 404 299
x.x.x.65 - - [26/Sep/2005:19:59:43 -0400] "GET /~aferworn/courses/CPS607/ANNOUNCE/CPS607AN.HTML HTTP/1.1" 200 1821
x.x.x.65 - - [26/Sep/2005:19:59:47 -0400] "GET /favicon.ico HTTP/1.1" 404 299
x.x.x.149 - - [26/Sep/2005:20:00:02 -0400] "GET /~b3pham/12.jpg HTTP/1.1" 200 30817
x.x.x.170 - - [26/Sep/2005:20:00:35 -0400] "GET /~b3pham/12.jpg HTTP/1.1" 200 30817
x.x.x.65 - - [26/Sep/2005:20:01:58 -0400] "GET /favicon.ico HTTP/1.1" 404 299
x.x.x.65 - - [26/Sep/2005:20:02:01 -0400] "GET /~aferworn/courses/CPS607/LABS/CPS607LA.HTML HTTP/1.1" 200 1053
x.x.x.65 - - [26/Sep/2005:20:02:01 -0400] "GET /favicon.ico HTTP/1.1" 404 299
x.x.x.65 - - [26/Sep/2005:20:02:02 -0400] "GET /~aferworn/courses/CPS607/LABS/CPS607L01.HTML HTTP/1.1" 200 2855
x.x.x.65 - - [26/Sep/2005:20:02:02 -0400] "GET /favicon.ico HTTP/1.1" 404 299
x.x.x.92 - - [26/Sep/2005:20:03:48 -0400] "GET /jpanar HTTP/1.1" 301 327
```

Figure 3- 2. Web access logs in www.scs.ryerson.ca web server.

Since there is much irrelevant information web logs are purged by filtering out all image, video, audio and failed page requests. For example, if the HTTP status code is 3xx or 4 xx, or the URL has the extension: jpg, pdf, doc, wav, mp3, gif, etc., the corresponding log entry will be removed.

```

http://scs.ryerson.ca/~mth110/ -> /~mth110/F05/Labs/index.shtml
http://scs.ryerson.ca/~mth110/F05/Labs/index.shtml -> /~mth110/F05/Labs/lab2.shtml
- -> /~aferworn
- -> /~aferworn/index.html
http://scs.ryerson.ca/~aferworn/ -> /~aferworn/clouds.gif
http://scs.ryerson.ca/~aferworn/ -> /~aferworn/images/ryerson.gif
http://scs.ryerson.ca/~aferworn/ -> /~aferworn/images/N-CARTlogo.jpg
http://scs.ryerson.ca/~aferworn/ -> /~aferworn/alexwork.gif
- -> /favicon.ico
http://scs.ryerson.ca/~aferworn/ -> /~aferworn/courses/CP5607/INDEX.HTML
http://scs.ryerson.ca/~aferworn/courses/CP5607/INDEX.HTML -> /~aferworn/courses/CP5607/IMAGES/RPERSON.GIF
http://scs.ryerson.ca/~aferworn/courses/CP5607/INDEX.HTML -> /~aferworn/courses/CP5607/IMAGES/welcome.gif
http://scs.ryerson.ca/~aferworn/courses/CP5607/INDEX.HTML -> /~aferworn/courses/CP5607/IMAGES/trired.gif
- -> /favicon.ico
http://scs.ryerson.ca/~aferworn/courses/CP5607/INDEX.HTML -> /~aferworn/courses/CP5607/ANNOUNCE/CP5607AN.HTML
- -> /favicon.ico
http://www.asiafinest.com/forum/index.php?showtopic=44954 -> /~b3pham/12.jpg
http://www.asiafinest.com/forum/index.php?showtopic=44954 -> /~b3pham/12.jpg
- -> /favicon.ico
http://scs.ryerson.ca/~aferworn/courses/CP5607/INDEX.HTML -> /~aferworn/courses/CP5607/LABS/CP5607LA.HTML
- -> /favicon.ico
http://scs.ryerson.ca/~aferworn/courses/CP5607/LABS/CP5607LA.HTML -> /~aferworn/courses/CP5607/LABS/CP5607L01.H
- -> /favicon.ico
- -> /ipamar

```

Figure 3- 3. Web referrer logs in www.scs.ryerson.ca web server.

3.2 Session Detection and Representation

A user session is defined as a set of clicks over a limited time by a user. In this work, the user is assumed to be uniquely defined by the IP address recorded in each http request. The whole web log file is composed of a set of sessions $S = \{S_1, S_2, \dots, S_n\}$, where n is the number of sessions in the log file. Each session S_j consists of a certain amount of information, such as session ID, user ID, entry URL, entry referrer, URLs, referrers, etc. Entry URL is the first web page visited in a session and entry referrer is the referrer of the entry URL. If the entry referrer is "-", then user has typed the URL directly in a browser window, that is, there is no referrer for the entry URL. URLs is a set of URLs the user visited in a session. Referrers are a set of referrers corresponding to URLs. The set of URLs is defined as $\{url_1, url_2, \dots, url_m\}$ and the set of referrers is defined as $\{ref_1, ref_2, \dots, ref_m\}$, where m is the number of web pages the user visits in a session.

Duration is the time spent on each web page. A list of durations can be represented as $\{urld_1, urld_2, \dots, urld_m\}$. Duration on each page except the last one can be calculated by:

$$urld_i = itime_{i+1} - itime_i \quad (3-1)$$

Where $itime$ is the time when the user accesses a web page. So the duration of the current web page is the difference between the time when the user accesses the next web page and the time when the user accesses the current web page. Duration of the last web page in the session can be approximated by the average duration:

$$urld_m = \frac{\sum_{i=1}^{m-1} urld_i}{m-1} \quad (3-2)$$

Also the duration of the session can be calculated after getting each web page's duration:

$$SD_j = \sum_{i=1}^m urld_i \quad (3-3)$$

Before implementing the session detection algorithm, there are two steps. The first one is to merge access logs and referrer logs together. Figure 3-4 shows the results of merging access logs and referrer logs. For example, in the first row, <http://scs.ryerson.ca/~mth110/>, which comes from the referrer logs, is the referrer of the URL: <http://scs.ryerson.ca/~mth110/F05/Labs/index.shtml> and other fields in this row come from access logs. The second step is to group the merged logs by users and order them by start time of visit. Figure 3-5 shows the results grouped by users, where user id is 65.

user_id	ctime	url
	referer	
163	2005-09-26 19:59:09	http://scs.ryerson.ca/~mth110/F05/Labs/index.shtml
163	2005-09-26 19:59:19	http://scs.ryerson.ca/~mth110/F05/Labs/lab2.shtml
65	2005-09-26 19:59:30	http://scs.ryerson.ca/~aferworn/index.html
65	2005-09-26 19:59:38	http://scs.ryerson.ca/~aferworn/courses/CPS607/INDEX.HTML
65	2005-09-26 19:59:43	http://scs.ryerson.ca/~aferworn/courses/CPS607/ANNOUNCE/CPS607AN.HTML
65	2005-09-26 20:02:01	http://scs.ryerson.ca/~aferworn/courses/CPS607/LABS/CPS607LA.HTML
65	2005-09-26 20:02:02	http://scs.ryerson.ca/~aferworn/courses/CPS607/LABS/CPS607L01.HTML
92	2005-09-26 20:03:49	http://scs.ryerson.ca/jpanar/index.html

Figure 3- 4. The merged access logs and referrer logs from in www.scs.ryerson.ca web server.

65	2005-09-22 11:13:00	http://scs.ryerson.ca/~aferworn/courses/CPS607/LABS/CPS607LA.HTML	http://scs.ryerson.ca/~aferworn/course s/CPS607/INDEX.HTML
65	2005-09-22 11:13:03	http://scs.ryerson.ca/~aferworn/courses/CPS607/LABS/CPS607L01.HTML	http://scs.ryerson.ca/~aferworn/course s/CPS607/LABS/CPS607LA.HTML
65	2005-09-26 19:59:30	http://scs.ryerson.ca/~aferworn/index.html	-
65	2005-09-26 19:59:38	http://scs.ryerson.ca/~aferworn/courses/CPS607/INDEX.HTML	http://scs.ryerson.ca/~aferworn/
65	2005-09-26 19:59:43	http://scs.ryerson.ca/~aferworn/courses/CPS607/ANNOUNCE/CPS607AN.HTML	http://scs.ryerson.ca/~aferworn/course s/CPS607/INDEX.HTML
65	2005-09-26 20:02:01	http://scs.ryerson.ca/~aferworn/courses/CPS607/LABS/CPS607LA.HTML	http://scs.ryerson.ca/~aferworn/course s/CPS607/INDEX.HTML
65	2005-09-26 20:02:02	http://scs.ryerson.ca/~aferworn/courses/CPS607/LABS/CPS607L01.HTML	http://scs.ryerson.ca/~aferworn/course s/CPS607/LABS/CPS607LA.HTML
65	2005-09-27 19:36:41	http://scs.ryerson.ca/~mfiume/index.html	

Figure 3- 5. The merged access logs and referrer logs grouped by users.

Figure 3-6 illustrates the session detection algorithm. In the figure, $\log_i$ represents one log record in the log file, also shown as one row in Figure 3-5. $Max_Duration_Page$ is the maximum time staying on one web page, set to 20 minutes,

so if user stays on one page longer than 20 minutes, the current row recording the user's operation will be considered as the first record in a new session. *Max_Duration_Session* is the maximum duration of one session, set to 3 hours, so if the current page's duration makes the session duration greater than 3 hours, the current row is also considered as the first record in a new session, to **update** SD_j means that every time the algorithm computes the duration of the current session based on formula (3-1), (3-2) and (3-3), to **new a session** means to create a new session, where entry URL is the URL of $\log_i$, and entry referrer is the referrer of $\log_i$, to **add** $\log_i$ into the session means to append the URL of $\log_i$ into the URL list of this session, and append the referrer of $\log_i$ into referrers of this session. And there is one attribute in the session called *No_Page*, which indicates the number of web pages in the session.

The basic idea of the session detection algorithm is to check current log information. It will be a new session if the page duration or session duration is greater than a certain value, or the current referrer of the current page is empty or is not one of the urls previous visited .

-
1. **for each** $\log_i$ with the same user
 2. **if** $urld_i > Max_Duration_Page$ or
 $SD_j > Max_Duration_Session$ or
 $ref_i == "-"$ or
 $ref_i \notin \{url_1, url_2, \dots, url_{i-1}\}$
 3. new a session S_{j+1}
 4. update SD_j
 5. **else**
 6. add $\log_i$ into the current session S_j
 7. update SD_j
 8. **end if**
 9. **end for**
-

Figure 3- 6. Session detection algorithm in WLBRG.

3.3 Extracting Entry Terms and Propagating to Other Pages

Figure 3-7 shows a list of URLs that a user (user ID 65) visits in one session. After session detection, there are two steps to extract terms for every page in the session. The first step is to extract terms for entry pages, and the second is to propagate terms to the rest of the pages in the session. Figure 3-8 shows the basic idea of the propagation process.

As shown in Figure 3-8, in a session, terms for the entry page are extracted from the anchor text in the entry referrer which links to the entry page or query terms if the entry referrer is a search engine result page, and for other pages in the session, terms are from two parts: one is from anchor text in their referrer pages and the other is propagated from the previous pages. So in Figure 3-8, “+” means the “append” operation. There are three types of entry referrer: empty, normal web page, and search engine result page. The propagation is slightly different for each type. If the entry referrer is empty, there are no terms for the first page. If the entry referrer is a normal web page, the propagation is to extract the anchor terms. If the entry referrer is a search engine result, the query terms submitted to search engines are extracted.

Figure 3- 7. The web pages visited by the web user in one session.

Figure 3- 8. The propagation process in one session.

In this work, when extracting terms from normal web pages, the anchor window text (certain number of text before and after anchor text and plus anchor text itself) is extracted for the entry page. If the entry referrer is the search engine result page, the title of the page and summary provided by search engines are extracted for the entry page. For example, in Figure 3-9 the texts highlighted are extracted to represent the page <http://www.scs.ryerosn.ca/scs/>. So $TermVector_url_0 = \{\text{computer science in ryerson Ryerson university department of computer science the computer science program is designed to produce graduates who can work effectively as software practitioners in the wide variety of professional areas}\}$.

Figure 3- 9. Terms extracted in the search engine as a new representation for the web page.

During the propagation, the term weight is calculated by the following formula:

$$TW_i = \alpha_0 S(p_0, p_i) R(p_0, p_i) TW_0 + \beta_0 \sum_{j=1}^{i-1} S(p_j, p_i) R(p_j, p_i) TW_{j-1} + \gamma_0 TW_{i-1} \quad (3-4)$$

$$\alpha_0 + \beta_0 + \gamma_0 = 1 \quad (3-5)$$

where, TW_i is the weight for terms propagated from page p_i , TW_0 is the term weight for the first web page in the session. $S(p_j, p_i)$ represents the similarity between two pages p_j, p_i . The similarity is computed by the cosine method [3]:

$$S(p_j, p_i) = \frac{p_j^T \cdot p_i}{\|p_j\| \|p_i\|} \quad (3-6)$$

where $\|p_j\|$ and $\|p_i\|$ are the norms of vectors of page p_j and p_i .

Function R computes the distance between two pages. The formula is:

$$R(p_j, p_i) = \frac{1}{i - j + 1} \quad (3-7)$$

So for each url_i of web page p_i in the session, its terms and corresponding weights are represented as

$$Vector_url_i = \{(TermVector_url_0, Weight_url_0), \dots, (TermVector_url_i, Weight_url_i)\}$$

Where $TermVector_url_i$ represents terms in anchor window which lies in the previous page of page p_i , $Weight_url_i$ is the corresponding weights of terms in $TermVector_url_i$.

So in a session, URLs' vector is represented by

$$Vector_URL = \{Vector_url_0, Vector_url_1, \dots, Vector_url_m\}$$

Where $(m + 1)$ is the total number of web pages in a session. If the similarity $S(p_j, p_i)$ of two pages p_j, p_i is less than one threshold, the propagation is stopped. So in this case, $(m + 1)$ is the number of pages propagated.

Sessions are assigned weight according to their importance. Session weight is based on two factors: One is that how long the session continues, measured by session duration; another is that how long ago the session occurred, measured by session recency. The main idea is that if a session is long, it implies that the user is serious about the browsing, and if a session occurs more recently, it reflects the current access pattern more, and thus is more important. The session weight can be expressed as:

$$Session_Weight_j = \log(SD_j \times SR_j \times factor) \quad (3-8)$$

where SD_j is the session duration, computed by (3-3), and SR_j is the session recency, computed by (3-9), factor is for scaling purposes, set to 100.

$$SR_j = \frac{1}{\log(T_{now} - T_{itime_j})} \quad (3-9)$$

where, T_{now} is the current system time, T_{itime_j} is the start time of visiting the entry page.

Thus the sooner the web user visits the page, the lower the recency is. Finally, there is information for one session shown in Figure 3-10.

Figure 3- 10. Session information extracted from web logs.

3.4 Page Merging

In one session, a web page may appear more than once, and in the whole log, a page may appear in different sessions. These situations are illustrated in Figure 3-11. In

one page, there is one attribute named *session_ids* which includes all sessions which contain this page.

$$session_ids = \{session_id_0, session_id_1, ..., session_id_i\}$$

Figure 3- 11. Page extracted from different sessions.

Because each web page in one session is represented by a term vector and a corresponding weight vector, when merging pages from different sessions, it is necessary to merge the term vectors and weight vectors into one term vector and weight vector. Therefore the page is finally represented by one term vector and one corresponding weight vector respectively *Term_Vector* and *Weight_Vector*.

$$Term_Vector = \{Term_0, Term_1, ..., Term_n\} \quad \text{and}$$

$$Weight_Vector = \{Weight_0, Weight_1, ..., Weight_n\}$$

The following figure shows the algorithm which merges the term vectors and weight vectors when merging pages from different sessions. For example, merge p_i .

```

1. for each session  $s \in \{session\_id_0, \dots, session\_id_n\}$ 
2.   for each  $u \in \{url_0, \dots, url_m\}$  in the session  $s$ 
3.     if  $u == url(p_i)$ 
4.       for each term vector  $tv \in \{TermVector\_url_0, \dots, TermVector\_url_m\}$  in  $u$ 
5.         for each term  $t \in \{Term_0, \dots, Term_j\}$  in  $tv$ 
6.           if term  $t \notin Term\_Vector$ 
7.             term  $t$  appends into the Term Vector of  $p_i$ :  $Term\_Vector$ 
8.             term weight  $w = Weight\_url(u) \times Session\_Weight(s)$ 
9.           else
10.            term weight  $w = w + Weight\_url(u) \times Session\_Weight(s)$ 
11.          end if
12.        end for
13.      end for
14.    end if
15.  end for
16. end for

```

Figure 3- 12. The algorithm of page merging from different sessions.

In Figure 3-12, every session in session list $\{session_id_0, \dots, session_id_n\}$ includes url_i of page p_i . The weight of each term in the vector is proportional to the current session weight and current term weight. For example, for $(TermVector_url_i, Weight_url_i)$ in the session s , the weight of each term from $TermVector_url_i$ is given by

$$weight = Weight_url_i \times Session_Weight \quad (3-10)$$

Eventually, the two vectors $Term_Vector$ and $Weight_Vector$ are merged into the $Term_Weight_Vector$ for each page.

$$Term_Weight_Vector = \{(Term_0, Weight_0), \dots, (Term_m, Weight_m)\}$$

Figure 3-13 shows the new representation for each page based on web log analysis.

Figure 3- 13. The new representation of page from web log data.

CHAPTER 4 RETRIEVAL MODELS AND COMBINATION OF MULTIPLE SOURCES

In this chapter, some traditional IR models are explained which are the basis of this thesis. Multiple evidential sources besides the original web page content are obtained by using WLBRG and anchor text extracting algorithm. Multiple evidence combination models are applied to these sources and the final results are returned to the user by ranking the similarities between the query and the web page.

4.1 Cosine Similarity Model

The task of an IR system is to retrieve documents which are relevant to a given query from a fixed set of documents, i.e. a document collection. When returning results to the user, IR systems use ranking functions to order documents according to the documents' estimated match with the user query. To facilitate the relevance evaluation process, both user queries and documents need to be transformed into a form that can be effectively processed by IR systems. One common form is to represent documents and queries using a set of index terms, ignoring term positions in the documents and queries.

In the following, a term and a document in the collection can be respectively represented by $t_i (1 \leq i \leq m)$ and $d_j (1 \leq j \leq n)$, where m is the number of unique terms in the collection and n is total number of documents in the collection.

One of the most successful models is Vector Space Model (VSM) introduced by Salton [3], [60], [61].

4.1.1 Similarity Measurements

In the VSM model, a document is represented as an m dimensional vector:

$$d_j = (w_{1j}, w_{2j}, \dots, w_{mj})^T$$

where T indicates the transpose, and w_{ij} is the weight of a term t_i in a document d_j . A query is likewise represented as follows:

$$q = (w_{1q}, w_{2q}, \dots, w_{mq})^T$$

Where w_{iq} is the weight of a term t_i in a query q , $w_{iq} \geq 0$.

Therefore, a document d_j and a user query q can be represented as vectors in m -dimensional term space as shown in Figure 4-1.

Figure 4- 1. The cosine is adopted as similarity value between document and query.

The results returned to web users are represented as a list of documents ranked according to the degree of similarity of the documents and the query. The selection of a similarity or ranking function is a central problem that affects the performance of IR systems the most. A detailed overview of similarity functions can be found in [62].

A common similarity function used in text-based IR system is the cosine similarity measure [3]. For this measure, the similarity is calculated by:

$$\begin{aligned} \text{sim}(d_j, q) &= \frac{d_j^T \cdot q}{\|d_j\| \|q\|} \\ &= \frac{\sum_{i=1}^m w_{i,j} w_{i,q}}{\sqrt{\sum_{i=1}^m w_{i,j}^2} \sqrt{\sum_{i=1}^m w_{i,q}^2}} \end{aligned} \quad (4-10)$$

Where $\|d_j\|$ and $\|q\|$ are the norms of the document and query vectors. The factor $\|q\|$ does not affect the similarity because it is the same for all documents. The factor $\|d_j\|$ provides a normalization in the space of the document.

Since $w_{i,j} \geq 0$ and $w_{i,q} \geq 0$, $\text{sim}(d_j, q)$ varies from 0 to 1. The cosine similarity measure can be used to rank the documents according to their degree of similarity to the query. A document might be retrieved even if it matches the query only partially. In the retrieval process, a threshold on $\text{sim}(d_j, q)$ is set, and only those documents with a degree of similarity above that threshold are retrieved. In this work, we use the cosine similarity method to compute the similarity scores of the documents and queries.

4.1.2 Weighting Schemes

Effectively weighting the terms in document and query is the most important factor for the performance of IR system in the vector space model.

In IR systems, intra-clustering similarity, which means the similarity between documents in the same cluster, is quantified by measuring the raw frequency of a term t_i appearing in a document d_j . Such term frequency is usually referred to as the *tf* factor and provides one measure of how well that term describes the document contents. Inter-clustering dissimilarity, which means difference between documents from different clusters, is quantified by measuring the inverse of the frequency of a term t_i among the documents in the collection. This factor is referred to as the inverse document frequency or *idf* factor.

Let $tf_{i,j}$ represent the term frequency of term t_i in document d_j , that is the number of times the term t_i is mentioned in the text of the document d_j . If term t_i does not appear in d_j , then $tf_{i,j} = 0$. The inverse document frequency given by

$$idf_i = \log \frac{N}{n_i} \quad (4-11)$$

where N is the total number of documents in the collection, n_i is the number of documents in which the term t_i appears.

By using the Lemur Toolkit [63], idf_i is computed by:

$$idf_i = \frac{\log(N+1)}{0.5 + n_i} \quad (4-12)$$

And the weighting scheme is given by:

$$\begin{aligned} w_{i,j} &= tf_{ij} \times idf_i \\ &= tf_{ij} \times \frac{\log(N+1)}{0.5 + n_i} \end{aligned} \quad (4-13)$$

4.1.3 Ranking Documents

Based on the cosine similarity measure and weight scheme, given a query, all documents in the collection can be ranked by the degree of similarity score between the document and the user query. In the following, $score(d,q)$ and $sim(d,q)$ is interchangeable. In this study, the score is given by:

$$score(d,q) = \frac{\sum_{i=1}^k w_{i,j} w_{i,q}}{\sqrt{\sum_{i=1}^k w_{i,j}^2} \sqrt{\sum_{i=1}^k w_{i,q}^2}} = \frac{\sum_{i=1}^k (tf_{i,q} \times idf_i)(tf_{i,d} \times idf_i)}{\sqrt{\sum_{i=1}^k (tf_{i,q} \times idf_i)^2} \sqrt{\sum_{i=1}^k (tf_{i,d} \times idf_i)^2}} \quad (4-14)$$

where $tf_{i,q}$ is the term frequency of term t_i in query q , $tf_{i,d}$ is the term frequency of term t_i in document d , idf_i is given by formula (4-12), k is the number of terms in the query q . All documents with scores greater than 0 are retrieved as the results.

4.2 TFIDF Model

The TFIDF model is often used as a baseline model for comparison with other retrieval models. In this thesis, the TFIDF model implemented in Lemur Toolkit [63], is relatively robust and performs empirically well. The model is based on the Okapi TF formula originally derived from a probabilistic model [64].

In this model, the inverse document frequency, idf has the same definition as (4-12) in the cosine similarity model. However, the document function tf is given by the Okapi TF formula with parameters $k1$ and b :

$$tf(x) = \frac{k1 \times x}{x + k1(1 - b + b \times \frac{l_d}{l_{av}})} \quad (4-15)$$

Where l_d is the document or query length, l_{av} is the average document length in the collection and x is the term weight in a document or a query.

When calculating the tf for the query q , the formula is given by

$$tf(q_i) = \frac{k1 \times tf_{iq} \times idf_i}{tf_{iq} \times idf_i + k1(1 - b + b \times \frac{l_d}{l_{av}})} \quad (4-16)$$

where tf_{iq} is the term frequency of t_i in the query q , idf_i has the same definition as (4-12), $k1$ is set to 1000 and b is set to 0.

When calculating the tf for the document d , the formula is given by

$$tf(d) = \frac{k1 \times tf_i \times idf_i}{tf_i \times idf_i + k1(1 - b + b \times \frac{l_d}{l_{av}})} \quad (4-17)$$

where tf_i is the term frequency of t_i in the document d , idf_i has the same definition as (4-12), $k1$ is set 1 and b is set 0.3.

So finally the score function of the document and query is given by

$$score(d, q) = \sum_{i=1}^m tf(q_i) \times tf(d) \quad (4-18)$$

4.3 Okapi Model

The symmetry of the retrieval situation between documents and queries suggests that we could treat within-query term frequency in a similar fashion to within-document term frequency. This concept brought rise to the BM25/Okapi weighting scheme. Virtually all the major systems in TREC now use the BM25/Okapi formula. The following formula also comes from Lemur Toolkit [63].

The term weight in query q is given by the following formula:

$$w_{i,q} = \frac{(k3 + 1)tf_{i,q}}{(k3 + tf_{i,q})} \quad (4-19)$$

And the term weight in document d is given by:

$$w_{i,d} = \frac{(k1+1)tf_{i,d}}{(tf_{i,d} + k1(1-b + \frac{b \times l_d}{l_{av}}))} \quad (4-20)$$

And based on the formula (4-19) and (4-20), the score function of the document and query is written as:

$$score(d, q) = \sum_{i=0}^m \log\left(\frac{(r+0.5)(N \times w_{i,d} \times w_{i,q} - n - R + r + 0.5)}{(R-r+0.5)(n-r+0.5)}\right) \quad (4-21)$$

The parameters and characters are explained in Figure 4-2.

$K3$	= parameter
$K1$	= parameter
b	= parameter
$tf_{i,q}$	= the term (t_i) frequency in the query q
$tf_{i,d}$	= the term (t_i) frequency in the document d
l_d	= the document length
l_{av}	= the average document length in the collection
R	= the total number of relevant to the query or feedback documents in the collection
r	= the total number of relevant to the query or feedback documents in which the term (t_i) occur
N	= the total number of documents in the collection
n	= the number of the documents in the collection which contain the term (t_i)
m	= the total number of terms in the query q

Figure 4- 2. The explanation for the formula (4-19) – (4-21).

Normally, R and r are initially set to 0. So combining the formula (4-19), (4-20) and (4-21) into one formula, we arrive at the following equation:

$$\begin{aligned}
score(d, q) &= \sum_{i=0}^m \log \left(\frac{(0 + 0.5) \left(N \times \frac{(k1 + 1) \times tf_{i,d}}{(tf_{i,d} + k1 \times (1 - b + \frac{b \times l_d}{l_{av}}))} \times \frac{(k3 + 1) \times tf_{i,q}}{(k3 + tf_{i,q})} - n - 0 + 0 + 0.5 \right)}{(0 - 0 + 0.5)(n - 0 + 0.5)} \right) \\
&= \sum_{i=0}^m \log \left(\frac{(N \times \frac{(k1 + 1) \times tf_{i,d}}{(tf_{i,d} + k1 \times (1 - b + \frac{b \times l_d}{l_{av}}))} \times \frac{(k3 + 1) \times tf_{i,q}}{(k3 + tf_{i,q})} - n + 0.5)}{(n + 0.5)} \right) \quad (4-22)
\end{aligned}$$

4.4 Indri Model

The Indri model is implemented in Lemur Toolkit [63], and it is based on a combination of language modeling [65] and the inference network [66] retrieval framework. The combined model was first introduced in [67]. Since its introduction, this combined model has been enhanced and expanded to handle a wide range of applications, such as the TREC Terabyte Track [68].

4.4.1 Inference Network

The inference network retrieval model is based on the formalism of Bayesian networks which are directed, acyclic graphical models (DAGs). Each node in the graph represents a random variable with either a discrete or continuous set of outcomes. Furthermore, each non-root node stores a conditional probability table that fully describes the probability of the outcomes associated with that node occurring given its parent nodes. Each outcome associated with a root node, which is without parents, is assigned a prior probability. Given a DAG, priors, conditional probability tables and any observed variables (evidence), the probability, or belief, of an outcome at any node can be calculated by propagating beliefs through the network (Pearl, 1988).

4.4.3 Indri Model Overview

Model

Figure 4-3 is a graphical model depiction of a typical instantiation of the Indri model. As [69] states: “The graph represents an inference network (also known as a Bayesian network), which is a succinct way of defining a joint probability distribution over a collection of random variables. Each node in the graph represents a random variable. The shaded nodes mean they are ‘observed’ and the un-shaded nodes mean they are not ‘observed’”. The edges in the graph define a set of independence assumptions over the random variables.

In this network, there are the following types of nodes.

- Document Node (D)
- Smoothing Parameter Nodes (α , β)
- Model Nodes (M)
- Representation Concept Nodes (k)
- Belief Nodes (q)
- Information Need Node (I)

(A). *Document Node*

The document node represents a random variable in the document collection. A document may have different forms depending on different document features. In this model, “a document is represented as multi-sets of binary vectors, where each entry in the binary vector represents the presence or absence of some feature of the text. One such vector is ‘extracted’ for every term position within the document. This treats the document as a sample from a Multiple-Bernoulli distribution” [69].

(B). *Smoothing Parameter Nodes*

“These nodes represent model hyper-parameters, which correspond to smoothing parameters in the framework. There is one set of smoothing parameter nodes for each model node.” More discussion about smoothing is given in [69].

Figure 4- 3. An example of Indri Model based on [69]

(C). Model Nodes

The model nodes such as M_{title} in Figure 4-3 represent *feature language models*. In this framework, they are smoothed multiple-Bernoulli distributions that model document representations. Depending on how many representations in the document, there may be more than one model node to correspond to these representations in the network. In the example above, there are three model nodes, corresponding to different representations of the same document. For instance, the title model corresponds to the pseudo-document made up of all of the title text from the original document, the body model corresponds to all of the text within the main body of the original document, and the h1 model corresponds to all of the text within the h1 tags of the original document. “Therefore this allows models to be estimated across various document representations and evidence from the different representations to be combined.” [69].

(D). *Representation Concept Nodes*

The representation concept nodes are binary random variables which directly represent the features extracted in the document representation, such as index terms, phrase, etc. The likelihood of an event occurring depends entirely on the parent model nodes. The same representation concept node may appear under different parent model nodes with multiple times in this framework. This allows the structure query to run in the network. For example, some queries are built by taking some terms from title of the document, and some terms from body of the document. More detail with query is introduced in the next section.

(E). *Belief Nodes*

“Belief nodes are binary random variables that are used to combine beliefs (probabilities) within the network. Each belief node stores a different conditional probability table, allowing beliefs to be combined in a number of ways. The belief nodes may be used to combine beliefs about representation concept nodes or other belief nodes as long as the graph remains acyclic.” [69].

The belief nodes are dynamically added to the network according to the structured indri query. Therefore, the network topology or structure changes with the different query, thus making the framework very powerful. This study takes advantage of these characteristics of providing a wide range of scoring functions based on the different query formulations.

(F). *Information Need Node*

The information need node is simply a belief node that combines all of the evidence within the network into one single belief which is used as the basis for ranking document to the query.

(G) *Summary of Indri Retrieval Process*

- a. Given a structure indri query, construct inference network
- b. For each document in the collection, calculate the similarity.
- c. Rank documents according to the similarity.

Query Language Overview

Indri query language was designed to handle both simple keyword queries and extremely complex queries. “It allows complex phrase matching, synonyms, weighted expressions, Boolean filtering, numeric (and dated) fields, and the extensive use of document structure (fields), among others.” [69].

Figure 4- 4. An example of Indri Model with node names.

“Terms are the basic building blocks of indri queries.” [70]. Terms are composed of “single term, ordered and unordered phrases, synonyms, among others. In addition, there are a number of options that can specify if a term should appear within a certain field, or if it should be scored within an assigned context.” The details can be found in [70].

In this study, #wsum and #combine are most used in the query. For example, user wants to search these keywords: cps109 exam bank. He or she can construct the query:

#combine(#wsum(0.8 cps109.(title) 0.1 cps109.(body) 0.1 cps109.(h1))

#wsum(0.8 exam.(title) 0.1 exam.(body) 0.1 exam.(h1))

#wsum(0.8 bank.(title) 0.1 bank.(body) 0.1 bank.(h1)))

In this example, the #wsum operator constructs a mixture model from the title, body, h1 language models and gives weight of 0.8 to title language model, weight of 0.1 to body language model and weight of 0.1 to h1 language model. Finally, the score of three terms are then #combined together.

4.5 Anchor Database

Anchor text is to the text that appears within the bounds of an <A> tag [71] . For example, on the web, one source page would contain text such as:

```
<a href=http://www.scs.ryerson.ca/People/students.shtml>students</a>
```

The target web page is the one referred to by the link, in this example <http://www.scs.ryerson.ca/People/students.shtml>. The link's anchor text appears to the user in the source page, in this example with underlined text: students. If the user clicks the anchor text, his or her browser will display the target page.

The reason why anchor is used in this study is that it was proved helpful for web site search. As analyzed in chapter 2, users tend to submit very short queries, only a few terms on average. "In many ways, anchor text shares this characteristic, since anchor text is typically short, and provides a summarization of the target document within the context of the source document being viewed. Thus, the process of creating anchor text for a document is a close approximation of the type of summarization presented by web users to a search engine in most queries. When anchor text terms match a query, the target document will usually be very relevant to the query terms." [71].

To get the anchor text database, two steps are taken. The first step is to parse each web page in the web site and extract all hyperlinks with their corresponding anchor texts. The process of extracting target documents and their anchor text is shown in Figure 4-5.

The second step is to process the anchor text list, merging the same page appeared in the list and merging the anchor text if they are within the same page. Here the same

terms are still kept in the anchor text list because these same terms reflect term frequency tf in one page. In this way, the database can be obtained which includes page URL and its corresponding anchor text terms as its representation. Figure 4-6 shows the merging process.

Figure 4-5. The process of extracting target document with its anchor text and writing into one document.

In this work, anchor window text is employed instead of simply anchor text. Anchor window text is the text within a window before and after the anchor text plus the anchor text itself. The window size is set as 80 since the window can cover the texts which are related to the current hyperlink.

Figure 4-6. The process of merging documents in the anchor text list.

4.6 Combination of Multiple Evidential Sources

There are two approaches to combine document representations: combination of ranking scores and combination of document representations. Generally speaking, the first approach is to apply a certain retrieval model to each of the document representations and combine the results from these different document representations to produce a single ranked list. The second approach is to first combine the different document representations into single document representation and then apply a retrieval model to the single document representation to produce the result list. In this study, there are three document representations: original web page database, log-based database by using WLBRG proposed in chapter 3 and the database based on anchor text.

4.5.1 Combination of Ranking Scores

Although there are three different document representations, and different retrieval models such as TFIDF, cosine similarity, Okapi and Indri, only one single

retrieval model is applied to these document representations every time. Each document is represented differently by the three document representations, so the degree of the similarity to the query in the three document representations may be different. The core of the combination of ranking scores is to combine the three scores contributed by three databases and weight them differently to get the best results. The following is the formula used to compute the final score for one document.

$$\begin{aligned} score(p, q) &= \alpha \times score_{content}(p, q) + \beta \times score_{anchor}(p, q) + \gamma \times score_{log}(p, q) \\ \alpha + \beta + \gamma &= 1 \end{aligned} \quad (4-24)$$

$score_{content}$, $score_{anchor}$ and $score_{log}$ are the similarity scores based on original web page, anchor window text and web logs respectively.

To get the best results in which the most relevant documents are listed in the top positions, we can modify the three tuning factors α , β and γ when combining these three scores linearly.

Figure 4-7 demonstrates the process of combination of ranking scores from three databases. The retrieval models in the figure are kept consistent when retrieving the documents based on the query. For example, if the Okapi model is applied to get the score from original web page content database, the same model is applied to the anchor text database.

Aslam [72] and Montague [55] summarize the combination by stating: “The systems being combined should (1) have compatible output (e.g., on the same scale), (2) each produce accurate estimates of relevance, and (3) be independent of each other.” Because the same retrieval model is applied to different document representations every time, the requirement (1), (2) and (3) are met for web page representation and anchor window text representation. But for web log representation, since the term weights are calculated differently, it is necessary to consider the requirement (1), compatible output. In our experiments, the Cosine Similarity, TFIDF, Okapi models are used to compute the similarity scores between queries and web pages, so we have to calculate the scores from web log representation individually to keep them on the same scale with the other two.

Figure 4-7. The process of combination of ranking scores.

(A). Cosine similarity model

Since the two scores from the original web page content database and anchor text database are in the range of 0 to 1 in the cosine similarity model, the score from log-based database should be kept in the same scale. Therefore, normalization is taken to achieve the aim. Here is the formula for computing the score from log-based database.

$$score_{\log}(p, q) = \frac{\sum_{i=1}^m w_{i,p}}{\sum_{j=1}^t w_{j,p}} \quad (4-25)$$

Where $w_{i,p}$ is the weight of term i in page p in log-based database, m is the number of the terms in query q , and t is the total number of terms in page p .

(B). TFIDF model

The following formula can be used to compute the score from log-based database:

$$score_{\log}(p, q) = \sum_{i=1}^m tf(q_i) \times idf_i \times w_{i,p} \quad (4-26)$$

Where $tf(q_i)$ is the term frequency in the query q , and idf_i is the *inverse document frequency* in the database, $w_{i,p}$ is the weight of term i in the page p in the log-based database and m is the total number of terms in the query q .

(C). Okapi model

Since the scores from the web logs are in the same scale as the other two, the score from web logs does not need additional processing. This can easily be shown by experimentation.

(D). Inference Networks model

For Indri [69], the method of its combination is different from this linearly combination method, so it will be put in the next section.

4.5.2 Merging of Document Representations

The second combination approach is to combine document representations into one document representation, and then apply different retrieval models. Therefore, there is no parameter to modify the weights for the terms. Actually, this approach is similar to document expansion to some extent. The whole process is illustrated in Figure 4-8.

Indri [69], which combines the language modeling and inference network retrieval frameworks into a unified model, is used to implement the inference networks. Combination of belief in Indri model is different from the above three models which combine ranking scores linearly. The first step is to combine the three document representations into a single document representation. When combining the document representations, some tags are added as the field tags to differentiate the terms which come from different document representations. For example, if the terms come from anchor text database, tags $\langle \text{anchortext} \rangle$ and $\langle / \text{anchortext} \rangle$ are added to the combined document representation to hold the terms. The same way, tags $\langle \text{logtext} \rangle$ and $\langle / \text{logtext} \rangle$ are added to hold the terms from the web logs. And then the parameters α, β and γ in the structure queries are adjusted to weight the terms differently.

Figure 4-8. The process of combination of document representations.

Take one of queries in this study as an example to draw the retrieval network by using Indri model. The query is as follows (similar to the one explained in section 4.4):

```
#combine( #wsum( 0.5 cps109.(html) 0.2 cps109.(anchortext) 0.3 cps109.(logtext) )
```

```
#wsum( 0.5 exam.(html) 0.2 exam.(anchortext) 0.3 exam.(logtext) )
```

```
#wsum( 0.5 bank.(html) 0.2 bank.(anchortext) 0.3 bank.(logtext) ) )
```

Figure 4-9. An example of the Indri model with structured query.

CHAPTER 5 EXPERIMENT AND ANALYSIS

Two combination methods are applied and tested on different retrieval models. Also different parameter sets are tested in each retrieval model. The results are evaluated by a group of 20 students. These evaluations show how much the performance is improved by using the new algorithm, WLBRG. The following sections will introduce more details in experiment design, data source preparation, retrieval process and analysis of results.

5.1 Data Set

5.1.1 Databases

All of the experiments in this thesis were done using web data from the department of Computer Science web site (<http://www.scs.ryerson.ca/scs/>) at Ryerson University. There are a total of 9,739 web pages (after audio, image, and video pages were filtered out). Table 5-1 shows the allowed formats. The algorithms and all experiments are developed and implemented based on the Lemur Toolkit [63].

Table 5- 1. Format list of web pages.

ID	Allowed Extension
1	.html
2	.htm
3	.asp
4	.txt
5	.xml
6	.php
7	.jsp
8	.shtml

After all web pages were downloaded, they were written into one file with SGML format as the web page content database. As shown in Figure 5-1, each web page was inside of tags <DOC> <DOCNO> *document name* </DOCNO> and </DOC>, here the document name is represented by unique number.

Figure 5-2 shows the anchor text database. There are a total of 5780 web pages with anchor text in the experiment.

The web logs from Jan. 1st to Dec 31st, 2005 were downloaded. There are 582,799 records after the inappropriate logs were filtered out as mentioned in chapter 3. Two databases from web logs were obtained by two different ways in term propagation phase. The first way was that there was no propagation, only the first page within each session was considered; and the second one was that the propagation depth was set to 3, dealing with maximum of 4 pages within one session. For example, in Figure 5-3, when no propagation, only web pages P_0 , P'_0 , P''_0 ... were included in the log-based database. In the propagation case (depth = 3), pages P_0 , P_1 , P_2 , P_3 , P'_0 , P'_1 , P'_2 , P'_3 , P''_0 , P''_1 , P''_2 , and P''_3 were included in the log database.

```
Generated by <a href="http://www.cs.rice.edu/~dwallach/classgrid/">classgrid 2.3</a>, Mon
Feb 6 13:09:24 EST 2006
</body>
</html>
</DOC>
<DOC>
<DOCNO>28</DOCNO>
<html><head>
<title>ENG205 Lab Schedule, Winter 2006</title>
</head>
<!-- Generated by classgrid 2.3, Mon Feb 6 13:09:25 EST 2006 -->
<body bgcolor="FFFFFF">
<h1 style="font-size:400%">ENG205 Lab Schedule, Winter 2006</h1>
<table bgcolor="FFFFFF" border=1 width="100%" cellspacing=1 cellpadding=1>
<tr bgcolor="FFFFFF0">
<th>&nbsp;</th>
<th width="15%">Monday</th>
<th width="15%">Tuesday</th>
<th width="15%">Wednesday</th>
<th width="15%">Thursday</th>
<th width="15%">Friday</th>
<th width="15%">Saturday</th>
</tr>
```

Figure 5- 1. Web page content database with SGML format.

```

eng203 36 dell pcs
</DOC>
<DOC>
<DOCNO>28</DOCNO>
eng205 36 dell optiplex gx270 pcs
eng205 36 dell pcs
</DOC>
<DOC>
<DOCNO>29</DOCNO>
eng206 open lab
eng206 open lab
</DOC>
<DOC>
<DOCNO>30</DOCNO>
eng207 16 dell optiplex gx270 8 piiv 800mhz pcs
eng207 16 dell pcs and 8 clones
</DOC>
<DOC>
<DOCNO>31</DOCNO>
eng209 36 amd pcs
eng209 36 amd pcs
</DOC>

```

Figure 5- 2. Anchor text database with SGML format.

Figure 5- 3. Web pages propagation in the session.

Figure 5-4 shows the log-based database. There are a total of 976 web pages within the log-based database where the propagation depth is 3 in the experiment.

```

<DOC>
<DOCNO>28</DOCNO>
labs td facilities eng205 36 dell optiplex gx270 pcs
</DOC>
<DOC>
<DOCNO>29</DOCNO>
labs td facilities eng206 open lab eng201 36 dell optiplex gx270 pcs
</DOC>
<DOC>
<DOCNO>30</DOCNO>
labs td facilities eng207 16 dell optiplex gx270 8 piii 800mhz pcs
</DOC>
<DOC>
<DOCNO>31</DOCNO>
labs eng201 36 dell optiplex gx270 pcs eng209 amd td facilities eng205
</DOC>
<DOC>
<DOCNO>32</DOCNO>

```

Figure 5- 4. Log-based database with SGML format with propagation depth = 3.

After obtaining the original web page database and the anchor text database, the next step was to combine these two databases into one database. For each web page, the anchor text terms were added into it to create a new document representation. As shown in Figure 5-5, document 28 was updated by adding terms from the anchor text. Note that Figure 5-1 shows the beginning part of document 28, and Figure 5-5 shows the ending part of document 28.

```

<p>
GSL: Grad Study Lab
<p>
CPS 590: Intro. to Operating Systems, Nagendra
<p>
CPS 610: Database System II, Mastoras
<p>
CPS 621: Intro. to Multimedia Systems, Hamelin
<p>
MTH 207: Calculus I, Lawrence
<p>
<hr>
Generated by <a href="http://www.cs.rice.edu/~dwallach/classgrid/">classgrid 2.3</a>, Mon
Feb 6 13:09:25 EST 2006
</body>
</html>

```

```

eng205 36 dell optiplex gx270 pcs
eng205 36 dell pcs

```

```

</DOC>
<DOC>

```

Figure 5- 5. Combined web page content and anchor text database with SGML format.

In the same way, the combined database with the original web page, anchor text, and web logs was obtained. Since there are two types of log-based databases used to test, one is no propagation and another is propagation with depth 3, there are also two combined databases based on the different log-based database. Figure 5-6 shows the combined database. Document 28 involved two extra parts from anchor text and web logs.

```

MTH 207: Calculus I, Lawrence
<p>
<hr>
Generated by <a href="http://www.cs.rice.edu/~dwallach/classgrid/">classgrid 2.3
</a>, Mon Feb  6 13:09:25 EST 2006
</body>
</html>

```

eng205 36 dell optiplex gx270 pcs
 eng205 36 dell pcs

From Anchor Text

labs td facilities eng205 36 dell optiplex gx270 pcs

```

</DOC>
<DOC>
<DOCNO>280</DOCNO>

```

Figure 5- 6. Combined web page content, anchor text and web logs database with SGML format.

Combination of databases for the Indri model was similar to the combination of original web page, anchor text and log-based database. Since the Indri model can recognize the fields in a document, some tags were added into the document to differentiate the fields. As shown in Figure 5-7, the terms from anchor text were placed inside tags `<anchortext>` and `</anchortext>` and the terms from web logs were placed inside tags `<logtext>` and `</logtext>`. Furthermore, the tags `<DOCHDR>` and `</DOCHDR>` were added to the document.

MTH 207: Calculus I, Lawrence

<p>

<hr>

Generated by classgrid 2.3, Mon
Feb 6 13:09:25 EST 2006

</body>

</html>

<anchortext>

eng205 36 dell optiplex gx270 pcs

eng205 36 dell pcs

</anchortext>

From Anchor Text

<logtext>

labs td facilities eng205 36 dell optiplex gx270 pcs

</logtext>

</DOC>

<DOC>

<DOCNO>280</DOCNO>

<DOCHDR>

</DOCHDR>

Figure 5- 7. Combined web page content and anchor text database with SGML format for the Indri Model.

5.1.2 Database Summary

All the databases used in the experiment are listed in Table 5-2.

Table 5- 2. Database list used in the experiment.

ID	Database	Description
1	database_ori.sgml	Original web page
2	database_anw.sgml	Anchor text
3	database_com.sgml	Combined original web page and anchor text
4	database_log_3.sgml	web logs with propagation depth 3
5	database_log_0.sgml	web logs with no propagation
6	database_all_3.sgml	Combined three representations, web logs with propagation depth 3
7	database_all_0.sgml	Combined three representations, web logs with no propagation
8	database_com_indri.sgml	Combined three representations for indri model retrieval

5.1.3 Query

Twenty-four queries were chosen for the experiment. These queries are shown in Table 5-3. Queries were also written in SGML format as shown in Figure 5-8.

```
<DOC querySample01>
cps109
exam
bank
</DOC>
<DOC querySample02>
lab
facilities
policies
</DOC>
<DOC querySample03>
mth108
solution
quiz
lab
</DOC>
<DOC querySample04>
coop
prospective
description
</DOC>
```

Figure 5- 8. Query with SGML format.

Table 5- 3. Query list submitted to retrieval.

ID	Query	ID	Query
1	lab facilities policies	13	web related research
2	coop prospective description	14	unix tutorial
3	artificial intelligence course introduction	15	cps125 extra practice question
4	human computer interaction course outline	16	image animation design
5	cps109 assignment submission instruction	17	textbook reference
6	cps125 review problem final exam	18	pliant installation
7	cps607 lecture notes	19	winter course
8	java programming	20	eng203 lab schedule
9	admission requirement	21	computer graphics assignment
10	computer science course introduction	22	research project
11	data communications topic	23	algorithm analysis
12	unix account management	24	operating system course grade

5.2 Implementation

5.2.1 Retrieval Models

There are 8 types of databases in Table 5-2, and these databases can be divided into two categories: one is the single data source such as database_ori.sgml, database_anw.sgml, database_log_0.sgml, database_log_3.sgml; another is the combined data source such as database_com.sgml, database_all_3.sgml, database_all_0.sgml and database_com_indri.sgml. The combination method of combining ranking scores was applied to the single data source while the other combination method of combining document representations was applied to the combined data source.

In the linear combination method, the parameter settings are given in Table 5-4.

The formula of the combination method is:

$$S = \alpha \times S_1 + \beta \times S_2 + \gamma \times S_3 \quad (5-1)$$

$$\alpha + \beta + \gamma = 1 \quad (5-2)$$

where, S_1 is the score from original web page based database, S_2 is the score from anchor text based database, and S_3 is the score from web log based database.

Table 5- 4. Parameter Settings for experiment.

ID	α	β	γ	ID	α	β	γ
1	0.8	0.0	0.2	14	0.5	0.1	0.4
2	0.8	0.1	0.1	15	0.5	0.2	0.3
3	0.8	0.2	0.0	16	0.5	0.3	0.2
4	0.7	0.0	0.3	17	0.5	0.4	0.1
5	0.7	0.1	0.2	18	0.5	0.5	0.0
6	0.7	0.2	0.1	19	0.4	0.0	0.6
7	0.7	0.3	0.0	20	0.4	0.1	0.5
8	0.6	0.0	0.4	21	0.4	0.2	0.4
9	0.6	0.1	0.3	22	0.4	0.3	0.3
10	0.6	0.2	0.2	23	0.4	0.4	0.2
11	0.6	0.3	0.1	24	0.4	0.5	0.1
12	0.6	0.4	0.0	25	0.4	0.6	0.0
13	0.5	0.0	0.5	26	0.3	0.3	0.4

All our algorithms are developed based on the Lemur Toolkit [63]. Cosine Similarity model, TFIDF model, Okapi model and Indri model were applied to the two methods of combinations.

For Indri model, one combination method was to assign the weight to terms from different fields, such anchortext, logtext. The parameter settings were same with the other

retrieval models as shown in Table 5-4. Another combination method was to combine the three document representations into one document representation without considering different fields. So the weights of terms were assigned as 1. Figure 5-9 and Figure 5-10 shows the two combination methods. In Figure 5-9, the query is cps109 exam bank, and in Figure 5-10, the query is operating system course grade.

```
<parameters>
  <query>#combine( #wsum( 0.8 cps109.(html) 0.2 cps109. 0 c
cps109.
#wsum( 0.8 exam.(html) 0.2 exam. 0 exam. )
#wsum( 0.8 bank.(html) 0.2 bank. 0 bank. )
)</query>
  <query>#combine( #wsum( 0.8 cps109.(html) 0.1 cps109. 0.1
cps109.
#wsum( 0.8 exam.(html) 0.1 exam. 0.1 exam. )
#wsum( 0.8 bank.(html) 0.1 bank. 0.1 bank. )
)</query>
  <query>#combine( #wsum( 0.8 cps109.(html) 0 cps109. 0.2 c
cps109.
#wsum( 0.8 exam.(html) 0 exam. 0.2 exam. )
#wsum( 0.8 bank.(html) 0 bank. 0.2 bank. )
)</query>
  <query>#combine( #wsum( 0.7 cps109.(html) 0.3 cps109. 0 c
cps109.
#wsum( 0.7 exam.(html) 0.3 exam. 0 exam. )
#wsum( 0.7 bank.(html) 0.3 bank. 0 bank. )
)</query>
```

Figure 5- 9. Query with fields for indri retrieval.

```
<parameters>
  <query>#combine( #wsum( 1.0 operating )
#wsum( 1.0 system )
#wsum( 1.0 course )
#wsum( 1.0 grade )
)</query>
</parameters>
~
~
```

Figure 5- 10. Query without field for indri retrieval.

5.2.2 Summary of Models and Databases

Eventually, there are a bunch of retrieval models and databases used in the experiment. Table 5-5 shows the relationship of retrieval models and databases. In the table, × means that the current retrieval model does not apply to the database, √ is that the retrieval model does apply to the database.

Table 5- 5. The relationship of databases and retrieval models.

ID	Database	Cosine	TFIDF	Okapi	Indri
1	database_ori.sgml	√	√	√	×
2	database_anw.sgml	√	√	√	×
3	database_com.sgml	√	√	√	×
4	database_log_3.sgml	√	√	√	×
5	database_log_0.sgml	√	√	√	×
6	database_all_3.sgml	√	√	√	×
7	database_all_0.sgml	√	√	√	×
8	database_com_indri.sgml	×	×	×	√

5.3 Evaluation Method

Usually there are two basic metrics to measure the performance of IR systems: recall and precision.

Recall is the fraction of the relevant documents which has been retrieved [3] i.e.

$$\text{Recall} = \frac{Ra}{R} \quad (5-3)$$

where, Ra is the number of relevant documents retrieved; R is the total number of relevant documents in the collection.

Precision is the fraction of the retrieved documents which are relevant [3], i.e. ,

$$\text{Precision} = \frac{Ra}{Rr} \quad (5-4)$$

where Rr is the total number of documents retrieved out, Ra has the same meaning as in formula (5-3).

Ra , R and Rr are shown in Figure 5-11.

Figure 5- 11. Precision and Recall for a given example information request.

5.3.1 Top 10 Precision

Since it is difficult to know how many relevant documents are in the collection, a precision metric is often used to evaluate the performance of web search engines. Because the experiment is executed in one particular website, the number of relevant documents to a query is not large, in most cases less than 10. Thus the top 10 results for each query are observed as Rr .

The top 10 results from all retrieval models and each model with all parameter settings are merged into one single list for each query. In this way, every query has its combined single result list, and then these lists are put on a website for evaluation by 20 students. The URL for evaluation is: <http://ccr.scs.ryerson.ca/>.

Finally for each query, there are relevant documents Ra after evaluation, and then check how many relevant documents are in the top 10 results of each method. If there are

3 relevant pages in the top 10 list retrieved by one method, the precision of this retrieval method is $3 / 10 = 0.3$.

5.3.2 R-Precision

R-precision is to compute the precision at the R-th position in the ranking, where R is the total number of relevant documents for the query. For example, if there are 3 relevant documents for a query, for one retrieval model, there is only one relevant document in the top 3 positions, so the R-precision of this retrieval model is $1/3 = 0.33$. In the experiment, R-precision averaged on all queries is calculated to measure the retrieval performance.

5.3.3 Average Precision

The idea here is to generate a single value summary of the ranking by averaging the precision values at every relevant document observed. For instance, the precision values after each new relevant document is observed are 1, 0.66, 0.45, 0.2. Thus, the average precision is $(1+0.66+0.33+0.25) / 4$ or 0.56. Again, average precision will be averaged on all queries for each retrieval method.

5.3.4 Notes

Since only the top 10 results for each retrieval method are evaluated, the total number of relevant documents is just an approximation. For web site search, the number of relevant documents is not large. Thus the approximation is very close to the real value.

5.4 Results and Analysis

In the experiment, three measurements: top 10 precision, R-precision and average precision are used to evaluate the performance of the new model with combination methods.

Table 5-6 explains retrieval methods appeared in result figures. In the following result figures, I chose some parameter settings differently with different retrieval models

just to show how different the improvement is by using different parameter settings and in which parameter settings the performance reaches best for each retrieval models.

Table 5- 6. Term explanation in the result figures.

Term	Description
<i>anc</i>	use the single anchor window text database
<i>anc+ori</i>	use the combined database of anchor text and original web page databases
<i>anc+ori+log_0</i>	All retrieval models are applied to the combined database from anchor text, original web page and web logs without propagation within the session
<i>Anc+ori+log_3</i>	All retrieval models are applied to the combined database from anchor text, original web page and web logs which do the propagation within the session (depth = 3)
<i>ori</i>	All retrieval models are applied to the single original web page database, which is taken as the baseline
<i>log_3</i>	All retrieval models are applied to the single log-based database which has the propagation within the session (depth = 3)
<i>all_xyz</i>	All retrieval models are applied to the combination of ranking scores, x is the weight for original web pages, y is for anchor text, and z is for web logs, for example, 334 means $\alpha = 0.3, \beta = 0.3, \gamma = 0.4$
<i>indri_xyz</i>	In Indri model, x is the weight of terms from original web pages, y is for anchor text, and z is for web logs
<i>indri_all</i>	Indri model applied to the combined database without the weight schemes

Figure 5-12 (a) shows the performance of several selected methods using Cosine Similarity model. From this figure, it can be seen that both performances of combination of document representations and ranking scores are better than that of original method. The performance of the combination of three document representations: original web pages, web logs and anchor window text is better than that of the combination of two document representations: original web pages and anchor window text only. The former can improve the original model by 10.3%, while the latter only by 8.5%. It shows that even without considering the weight scheme, logs can be the useful evidence to improve

retrieval accuracy. Also the performance of the combination of three ranking scores is better than that of the combination of two ranking scores from original web pages and web logs only. By increasing the weight of original web pages and decreasing of the weight of web logs, the performance is slightly reduced. When $\alpha = 0.4, \beta = 0.2, \gamma = 0.4$, the improvement can reach the highest by 22.9%.

(a)

(b)

(c)

(d)

Figure 5- 12. Precisions of different retrieval models and methods.

In the Okapi retrieval model, both combination methods can achieve better performance than the original method. The performance of the combination of three document representations: original web pages, web logs and anchor text is better than that

of the combination of two document representations: original web pages and anchor text only. The former can improve by 10.6%, while the latter improves by 9.1%. When combining three document representations, the performance of combining web logs with propagation of depth 3 (10.6%) is better than that without the propagation (10.1%). It is interesting to see that if we just combine two ranking scores: original web pages and web logs, there is no improvement while if we combine three document representations, the performance is increased by 10.6% -- the highest among other methods.

From Figure 5-12 (c), the combination of document representations is a better method for the TFIDF retrieval model. The performance of the combination of three document representations is improved over that of the combination of two document representations, i.e., original web pages and anchor text only. The former can improve by 12.3%, while the latter by 6.6%. When combining three document representations, the performance of combining web logs with propagation of depth 3 (12.3%) is better than that without propagation (9.8%). In the TFIDF model, combination of ranking scores is better than combination of document representations. Also we find that the performance is greatly improved by using single document representation such as anchor window text, or web logs. If parameters are set to $\alpha = 0.3, \beta = 0.3, \gamma = 0.4$, the improvement of the retrieval can reach up to 45.4%. This is reasonable because this parameter setting reflects the fact that anchor window text and logs are important and useful evidences.

For the Indri retrieval model, the top 10 precisions are shown in Figure 5-12 (d). If we consider the weight scheme, the combination of anchor window text and original web page can help to improve the performance, as well the combination of three document representations. But in this model, the highest improvement is 8.2% at $\alpha = 0.6, \beta = 0.4, \gamma = 0.0$ and when combining three document representations, the performance is improved by 7.9%.

Figure 5-13 shows top 10 precision of the four retrieval models and two methods in each model based on 24 queries. Specifically, when $\alpha = 0.4, \beta = 0.2, \gamma = 0.4$ for the Cosine Similarity model, the top 10 precision of most queries is increased. The improvement is more obvious in the TFIDF model when the parameters are set to $\alpha = 0.3, \beta = 0.3, \gamma = 0.4$. Overall, Figure 5-13 illustrates that more than 2/3 queries get

higher precisions using the combination method than those not using any combination method.

Figure 5- 13. Precisions of different retrieval models and methods based on queries.

Figure 5-14 shows the performance of different models with different parameter settings in terms of R-precision measurement. From the four charts, combination methods based on WLBRG are better than the original method without combination.

Cosine Similarity Retrieval Model

(a)

Okapi Retrieval Model

(b)

(c)

(d)

Figure 5- 14. R-precisions of different retrieval models and methods.

In Figure 5-14 (a), the two combination methods both have improvement and the combination of ranking scores are better than the combination of document representations. The performance of combination of three scores is better than that of the

combination of only two scores based on original web pages and web logs. With the increase of the parameter α , the performance of combination of three ranking scores decreases slightly, while the performance of the combination of two ranking scores is relatively stable. This demonstrates that anchor window text has an impact on the retrieval performance and also is an important and useful source for combination. When combining document representations, the highest performance could improve the baseline by 18.0%, when combining three ranking scores, the highest performance increased by 39.9% at $\alpha = 0.3, \beta = 0.3, \gamma = 0.4$, and when combining only two ranking scores based on original web pages and web logs, performance could be improved by 21.6% at $\alpha = 0.4, \beta = 0.0, \gamma = 0.6$.

For the Okapi model shown in Figure 5-14 (b), the overall improvement is obvious. For this model, the result shows that the performance of combination of multiple document representations is better than those of combination of ranking scores. In the combination of ranking scores, the performance increases with the increase of the parameter α , which means the original web pages have the most impact for retrieval performance. When $\alpha = 0.7, \beta = 0.2, \gamma = 0.1$, the performance is improved by 11.8%. The highest improvement is 12.3% if combining the three document representations.

In Figure 5-14 (c), two combination methods both have improvement and the combination of ranking scores are better than the combination of document representations, which is similar to the Cosine Similarity model. Also, with the increase of the parameter α , the performance of the combination of three ranking scores has decreases slightly. The improvement could be up to 51.4% at $\alpha = 0.3, \beta = 0.3, \gamma = 0.4$ while the improvement is up to 26.5% when combining three document representations.

For the Indri model, it seems that web logs do not improve the performance. But when combining three document representations, the performance improves by 17.4%.

Figure 5-15 shows the performance of different models with different parameter settings in terms of average precision measurement. From the four charts, combination methods based on WLBRG are better than the original method without combination in terms of average precision.

Cosine Similarity Retrieval Model

(a)

Okapi Retrieval Model

(b)

Figure 5- 15. Average precisions of different retrieval models and methods

Figure 5-15 (a) shows the performance of combination methods applied to Cosine Similarity model. Overall, two combination methods both have improvement but the combination of ranking scores are better than the combination of three document

representations. Furthermore, the performance of the combination of three scores is better than that of the combination of only two scores based on original web pages and web logs. With the increase of the parameter α , the performance of combination of two ranking scores is relatively stable. When combining document representations, the highest performance could be improved by 17.5%, when combining three ranking scores, the highest performance could be improved by 38.0% at $\alpha = 0.5, \beta = 0.2, \gamma = 0.3$, and when combining only two ranking scores based on original web pages and web logs could be improved by 24.0% at $\alpha = 0.4, \beta = 0.0, \gamma = 0.6$.

For the Okapi model shown in Figure 5-15 (b), it is obvious that the performance of the combination of multiple document representations is better than that of combination of ranking scores. While the performance of combination of only two ranking scores from original web pages and anchor window text is better than that of combination of three ranking scores. When $\alpha = 0.7, \beta = 0.3, \gamma = 0.0$, the performance is improved by 13.9%. The highest performance is reached to 16.2% if combining the three document representations.

In Figure 5-15 (c), two combination methods both have improvement and the combination of ranking scores are better than the combination of document representations, which is similar to the Cosine Similarity model. Also with the increase of the parameter α , the performance of combination of three ranking scores has a bit decrease. It also can be seen from the chart, the performance of combination of two ranking scores from original web pages and anchor window text is better than those of combination of ranking scores from original web pages and web logs. The improvement is reached to 50.7% at $\alpha = 0.3, \beta = 0.3, \gamma = 0.4$ while the improvement is reached to 28.9% when combining three document representations.

For the Indri model, it seems that it is better to combine only anchor window text and original web pages. But when combining three document representations, the performance reaches the highest level and is improved by 24.0%.

5.5 Discussion

Table 5-7 summarizes the performance of four different retrieval models in terms of precision, R-precision and average precision. As it shows, it is always possible to find an optimal parameter set by which the performance of web site search is better than that text-based only approach. Here are some points we can find from the experimentation.

The performance of TFIDF and Cosine Similarity models has more improvement than that of Okapi and Indri models. This is reasonable since precisions of those models are low and if there are more relevant pages retrieved out, the improvement on precision increases obviously.

It is better to use the combination of multiple document representations for the Okapi and Indri models, and it is better to use the combination of ranking scores for TFIDF and Cosine Similarity models. Take R-precision measurement as an example, the highest improvement of combination of document representations for TFIDF model is 26.5%, while the combination of ranking scores for the same model is 51.4%; the highest improvement of combination of document representations for Indri model is 17.4% while the combination of ranking scores for the same model is 16.7%. The reason why TFIDF and Cosine Similarity models have smaller improvement when using the combination of document representations is the weight function. In these two retrieval models, the two factors: tf and idf are considered. Thus when combining three document representations into one document representation, tf is increased but idf is decreased according to the formula (4-12) because n_i , the number of documents in which the term appears may increase. And then the weight $w_{i,j} = tf_i \times idf_i$ is balanced by these two factors: tf and idf . The final score is less affected by the balanced weight so that the improvement of combination of document representations is not as much as that of combination of ranking scores.

For the Okapi model, the weighting function considers the factor tf and does not include idf . When using the combination of document representations, tf is increased, but according to the formula (4-22) the similarity scores may be a little bit decreased because n , the number of documents in which the term appears may increase. It means that the more pages contain the query terms in the collection, their similarity scores will be less.

In this sense, if these pages are not relevant, the performance of this kind of combination for Okapi is better. For this reason, it might be better to combine the multiple document representations to improve the retrieval performance for Okapi model. The experiment results also proved it.

In the Indri model, since the average length of a document in the web logs is 7.69, the length in anchor window text is 17.34 and the length in the original web pages is 288.67, so it is quite possible that some query terms are not in the log-based database. When assigning weights for terms from different fields, the belief scores from web logs part may be not trusted enough, since the terms in the log-based database only are a small portion of those in text-based database, which means some query terms are not in the log-based text. In this case, this kind of combination for the Indri model may allow the irrelevant documents to appear in the top 10 list. So it is better to ignore the weights of terms from different fields and just look at the combined document as a single document. The results also show that combination of document representations for the Indri model is a better method to improve the retrieval accuracy.

Table 5- 7. Summary of performance of different models.

Measurement	Cosine Similarity Model	Okapi Model	TFIDF Model	Indri Model
Precision of C1	10.3%	10.6%	12.3%	7.9%
Precision of C2	22.9% $\alpha = 0.4$, $\beta = 0.2$, $\gamma = 0.4$	7.0% $\alpha = 0.8$, $\beta = 0.1$, $\gamma = 0.1$	45.4% $\alpha = 0.3$, $\beta = 0.3$, $\gamma = 0.4$	8.2% $\alpha = 0.6$, $\beta = 0.4$, $\gamma = 0.0$
R-precision of C1	18.0%	12.3%	26.5%	17.4%
R-precision of C2	39.9% $\alpha = 0.3$, $\beta = 0.3$, $\gamma = 0.4$	11.8% $\alpha = 0.7$, $\beta = 0.2$, $\gamma = 0.1$	51.4% $\alpha = 0.3$, $\beta = 0.3$, $\gamma = 0.4$	16.7% $\alpha = 0.4$, $\beta = 0.6$, $\gamma = 0.0$
Average precision of C1	17.5%	16.2%	28.9%	24.0%
Average precision of C2	38.8% $\alpha = 0.5$, $\beta = 0.2$, $\gamma = 0.3$	13.9% $\alpha = 0.7$, $\beta = 0.3$, $\gamma = 0.0$	50.7% $\alpha = 0.3$, $\beta = 0.3$, $\gamma = 0.4$	18.8% $\alpha = 0.4$, $\beta = 0.6$, $\gamma = 0.0$

* C1: Combination of three document representations
C2: Combination of ranking scores

CHAPTER 6 CONCLUSIONS

In this study, a novel model WLBRG is proposed by analyzing web logs to improve the performance of web site search. In order to cover the entire web site, full text is the main document representation. Since anchor text is proved useful in web search and web site search, anchor window text is used as another document representation. These two representations are combined with log-based representation generated by WLBRG algorithm. Two combination method: combination of multiple document representations and combination of ranking scores are investigated to find the best combination methods for different retrieval models. In the experiment, the new algorithm and combination methods are applied to four retrieval models: Cosine Similarity, Okapi, TFIDF and Inference network (Indri).

The key of the WLBRG is to extract entry terms and propagate them to other pages in each session of the web log. When calculating the term weight, the similarity between pages is taken into account because it can reduce the risk of introducing noise to each page and the degree of recency is also considered because it can make latest accessed pages more important than those which contain the similar content but are older.

In the combination methods, from the experiments, it is found that the two types of combinations based on the WLBRG could improve the retrieval performance on the web site search for Cosine Similarity, Okapi, TFIDF and Indri retrieval models. In particular, for Cosine Similarity and TFIDF models, it is better to use combination of ranking scores than to use combination of multiple document representations; for Okapi and Indri models, it is better to combine multiple document representations than to combine ranking scores based on the average data. In terms of top 10 precision, R-precision and average precision, for Cosine Similarity model, the highest improvement is around 38%, for Okapi model, the highest improvement is around 13%, for TFIDF model, the highest improvement is around 48% and for Indri model, the highest improvement reaches around 17%.

Since the WLBRG algorithm is computed offline, it has no significant impact on the speed of retrieval.

Contributions of Thesis

The main contributions of this thesis are:

- Demonstration of effectiveness of web site search by combining the web server logs.
- A Web Log Analysis (WLB RG) model that analyzes and extracts implicit information from daily web server logs.
- Investigation into the combination methods using three document representations.
- Comparison of performance of four retrieval models with new model.

Future Work

For the future work, when doing the propagation, the way of determining the propagation depth in each session will be studied by setting one particular threshold value of the similarity of two pages. Because in this work, only two approaches are tested in this work, one is no propagation and another is setting propagation depth as 3.

To get better performance for combination of ranking scores, the normalization for each score from different databases can be performed. That is, the scores from text-based, anchor-based and log-based databases are normalized to certain range because scores from log-based database are different from other two databases.

In the future, more evidence can be investigated and applied to web site search. To generate more evidences, texts appearing in different tags such as titles, heads, or image titles can be considered and tested. And also the experimentation will be conducted on different web sites, for instance, a larger web site, a commercial site, etc.

More combination approaches can be investigated. For example, to combine the ranking orders in the results instead of ranking scores can be studied. Or the different combination methods mentioned in [67] can also be further studied. Furthermore, since these combination methods are all based on this fact that one single retrieval model is applied to different data sources, we can also research other combination method that uses different retrieval models into a single data source first and then combines the scores to get final one.

REFERENCES

- [1] M. A. Hearst, "Next Generation Web Search: Setting Our Sites", IEEE Data Engineering, Volume 23, Issue 3, pages 38-48, 2000.
- [2] P. Hagen, H. Manning and Y. Paul, "Must search stink?" The Forrester report, Forrester, June 2000.
- [3] R. Baeza-Yates and B. Ribeiro-Neto, "Modern Information Retrieval", Addison-Wesley Publishing Company, page 29, 1999.
- [4] B. J. Jansen, A. Spink, J. Bateman, and T. Saracevic, "Real life information retrieval: a study of user queries on the web", ACM SIGIR Forum, Volume 32, Issue 1, pages 5-7, 1998.
- [5] H. Cui, J.R. Wen, J.Y. Nie, and W.Y. Ma, "Query Expansion by Mining User Logs", IEEE Transaction on Knowledge and Data Engineering, Volume 15, Number 4, pages 829-839, 2003.
- [6] G.W. Funas, T.K. Landauer, L.M. Gomez, and S.T. Dumais, "The vocabulary problem in human-system communication", Communications of the ACM, Volume 30, Issue 11, pages 964-971, 1987.
- [7] L. Page, S. Brin, R. Motwani and T. Winograd, "The PageRank citation ranking: bringing order to the web." Technical report, Stanford University Database Group, 1998.
- [8] J. M. Kleinberg, "Authoritative sources in a hyperlinked environment", Journal of the ACM, 46(5):604-632, 1999.
- [9] N. J. Belkin, C. Cool, D. Kelly, H. J. Lee, G. Muresan, M. C. Tang, and X. J. Yuan, "Query length in interactive information retrieval", In Proceedings of the 26th Annual ACM International Conference on Research and Development in Information Retrieval, pages 205-212, 2003.
- [10] J. J. Rocchio, "Relevance feedback in information retrieval", In The SMART Retrieval System: Experiments in Automatic Document Processing, 1971.

- [11] G. Salton and C. Buckley, "Improving retrieval performance by retrieval feedback", *Journal of the American Society for Information Science*, 41(4):288–297, 1990.
- [12] D. Kelly and J. Teevan, "Implicit feedback for inferring user preference: A bibliography", *ACM SIGIR forum*, Volume 37, Issue 2, pages 18-28, 2003.
- [13] T. Joachims, "Optimizing search engines using clickthrough data", In *Proceedings of the 8th ACM SIGKDD international conference on Knowledge discovery and data mining*, 2002.
- [14] R. W. White, J. M. Jose, C. J. Rijsbergen, and I. Ruthven, "A simulated study of implicit feedback models", In *Proceedings of the 26th European Conference on Information Retrieval*, 2004.
- [15] K. Sugiyama, K. Hatano, and M. Yoshikawa, "Adaptive web search based on user profile constructed without any effort from users", In *Proceedings of the 13th conference on World Wide Web*, 2004.
- [16] D. Kelly and N. J. Belkin, "Display time as implicit feedback: Understanding task effects", In *Proceedings of the 27th annual international ACM SIGIR conference on Research and development in information retrieval*, 2004.
- [17] S. Feldman and C. Sherman, "The high cost of not finding information", *Technical Report #29127*, IDC, April 2003.
- [18] <http://www.atomz.com/>
- [19] <http://www.fastsearch.com/>
- [20] <http://www.autonomy.com/content/home/>
- [21] <http://www.google.com/enterprise/>
- [22] R. Cooley, J. Srivastava, and B. Mobasher, "web mining: Information and pattern discovery on the world wide web", In *9th IEEE International Conference on Tools with Artificial Intelligence*, page 558, 1997.
- [23] C. Nick, H. David, and R. Stephen, "Effective Site Finding using Link Anchor Information", In *Proceedings of the 24th annual international ACM SIGIR conference on Research and development in information retrieval*, 2001.
- [24] D. Harman, "Ranking Algorithms," In *Information Retrieval Data Structures and Algorithms*, W. B Frakes and R. Baeza-Yates, eds., Prentice Hall, pp. 363-392, 1992.

- [25] S. Brin and L. Page, "The Anatomy of a Large-Scale Hypertextual web Search Engine", In Proceedings of the 7th international World Wide web Conference, pages 107-117, 1998.
- [26] S. Chakrabarti, B. Dom, D. Gibson, J. Kleinberg, P. Raghavan, and S. Rajagopalan, "Automatic resource compilation by analyzing hyperlink structure and associated text", In Proceedings of the 7th International World Wide Web Conference, page 65-74, 1998.
- [27] W. Thijs, K. Wessel, and H. Djoerd, "Retrieving web Pages using Content, Links, URLs and Anchors", TREC10, 2002.
- [28] D. D. Brian, G. D. David, and B. L. David, "Finding Relevant website Queries", In Proceedings of the 12th International World Wide web Conference, pages 502-503, 2003.
- [29] G. Xue, H. Zeng, Z. Chen, Y. Yu, W. Ma, W. Xi, W. Fan, "Optimizing Web Search Using web Click-through Data", In Proceedings of the 13th ACM international conference on Information and Knowledge management, 2004.
- [30] A. Singhal and F. Pereira, "Document expansion for speech retrieval", In Proceedings of the 22nd annual international ACM SIGIR Conference on Research and development in information retrieval, 1999.
- [31] Y.-C. Li and H. M. Meng, "Document expansion using a side collection for monolingual and cross-language spoken document retrieval", In ISCA Workshop on Multilingual Spoken Document Retrieval, pages 85-90, 2003.
- [32] N. Lester and H. E. Williams, "Topic tracking at RMIT University", In Topic Detection and Tracking Workshop (TDT), 2002. National Institute of Standards and Technology.
- [33] G.-A. Levow and D. W. Oard, "Signal boosting for translingual topic tracking: Document expansion and n-best translation", In Topic Detection and Tracking: Event-Based Information Organization, pages 175-195., 2002.
- [34] B. Billerbeck, and J. Zobel, "Document Expansion versus Query Expansion for Ad-hoc Retrieval", In Proceedings of the 10th Australasian Document Computing Symposium, pages 34-41, 2005.

- [35] S. E. Robertson and S. Walker, "Okapi/Keenbow at TREC-8", In Proceedings of Text Retrieval Conference (TREC), 1999.
- [36] C. D. Paice, "Constructing literature abstracts by computer: techniques and prospects", Information Processing and Management, Volume 26, Issue 1, pages 171-186, 1990.
- [37] A. Tombros and M. Sanderson, "Advantages of query biased summaries in information retrieval", In Proceedings of the 21st annual international ACM SIGIR conference on Research and development in information retrieval, 1998.
- [38] A. Veerasamy and R. Heikes, "Effectiveness of a graphical display of retrieval results", In Proceedings of the 20th annual international ACM SIGIR conference on Research and development in information retrieval, 1997.
- [39] D. J. Harper, S. Coulthard, and S. Yixing, "A language modeling approach to relevance profiling for document browsing", In Proceedings of the second ACM/IEEE-CS joint conference on Digital libraries, 2002.
- [40] N. Craswell, D. Hawking, and S. Robertson, "Effective site finding using link anchor information", In Proceedings of the 24th Annual International ACM SIGIR Conference on Research and Development in Information Retrieval, page 250-257, 2001.
- [41] F. Scholer, H. E. Williams, and A. Turpin, "Document Surrogates for Web Search", Journal American Society Information Science and Technology (JASIST), Volume 55, Issue 7, pages 637-650, 2004.
- [42] C. Kemp and K. Ramamohanarao, "Long-term learning for web search engines", In Proceedings of the 6th European Conference of Principles of Data Mining and Knowledge Discovery, 2002.
- [43] R. Kosala and H. Blockeel, "Web Mining Research: A Survey", ACM SIGKDD, Volume 2, Number 1, pages 1-15, 2000.
- [44] G. Xue, H. Zeng, Z. Chen, W. Ma, C. Lu, "Log Mining to Improve the Performance of Site Search", In Proceedings of the 3rd international conference on Web Information Systems Engineering Workshops, 2002.
- [45] R. Srikant and R. Agrawal, "Mining Generalized Association Rules", In Proceedings of the 21st Int'l Conference on Very Large Databases, 1995.

- [46] M. R. Henzinger, "Link analysis in web information retrieval", IEEE Data Engineering, Volume 23, Issue 3, pages 3-8, 2000.
- [47] G. Xue, H. Zeng, Z. Chen, W. Ma, H. Zhang, C. Lu, "Implicit Link Analysis for Small Web Search", In Proceedings of the 26th annual international ACM SIGIR conference on Research and development in information retrieval, 2003.
- [48] N. Eiron, and K. S. McCurley, "Analysis of Anchor Text for Web Search", In Proceedings of the 26th annual international ACM SIGIR conference on Research and development in information retrieval, pages 459-460, 2003.
- [49] B. T. Bartell, G. W. Cottrell and R. K. Belew, "Automatic combination of multiple ranked retrieval systems", In Proceedings of the 17th annual international ACM SIGIR conference on Research and development in information retrieval, 1994.
- [50] J. H. Lee, "Analysis of multiple evidence combination", In Proceedings of the 20th annual international ACM SIGIR conference on Research and development in information retrieval, 1997.
- [51] C. C. Vogt and G. W. Cottrell, "Predicting the performance of linearly combined IR systems", In Proceedings of the 21st annual international ACM SIGIR conference on Research and development in information retrieval, 1998.
- [52] P. Ogilvie and J. Callan, "Combining Document Representations for Known-Item Search", In Proceedings of the 26th annual international ACM SIGIR conference on Research and development in information retrieval, 2003.
- [53] K. Collins-Thompson, P. Ogilvie, Y. Zhang, and J. Callan, "Information filtering, novelty detection, and named page finding", In Proceedings of the 11th Text Retrieval Conference (TREC-11), 2002.
- [54] W. Kraaij, T. Westerveld, D. Hiemstra, "The importance of prior probabilities for entry page search", In Proceedings of the 25th Annual International ACM SIGIR Conference on Research and Development in Information Retrieval, 2002.
- [55] S.H. Myaeng, D.H. Jang, M.S. Kim, and Z.C. Zhoo, "A flexible model for retrieval of SGML documents", In Proceedings of the 21st Annual International ACM SIGIR Conference on Research and Development in Information Retrieval, 1998.

- [56] R. Fagin, R. Kumar, K. S. McCurley, J. No-vak, D. Sivakumar, J. A. Tomlin, and D. P. Williamson, "Searching the workplace web", In Proceedings of the 12th World Wide Web Conference, 2003.
- [57] A. Shakery, C. X. Zhai, "Relevance Propagation for Topic Distillation UIUC TREC 2003 Web Frack Experiments", In the 12th TREC, 2003.
- [58] R. Song, J. R. Wen, S. M. Shi, G. M. Xin, T. Y. Liu, T. Qin, X. Zheng, J. Y. Zhang, G. R. Xue, and W. Y. Ma, "Microsoft Research Asia at Web Track and Terabyte Track of TREC 2004", In the 13th TREC, 2004.
- [59] T. Qin, T. Liu, X. Zhang, Z. Chen, W. Ma, "A Study of Relevance Propagation for Web Search", In Proceedings of the 28th annual international ACM SIGIR conference on Research and development in information retrieval, 2005.
- [60] G. Salton, "The SMART Retrieval System – Experiments in Automatic Document Processing", Prentice-Hall Inc., 1971.
- [61] R. Ferber, "Information Retrieval", page 27-28, 2003.
- [62] R. Wilson and T. R. Martinez, "Improved Heterogeneous Distance Functions", Journal of Artificial Intelligence Research, 6:1–34, 1997.
- [63] The Lemur Toolkit for Language Modeling and Information Retrieval, <http://www.lemurproject.org/>
- [64] T. L. Brauen, "Document vector modification", chapter 24, pages 456–484. Prentice-Hall Inc., 1971.
- [65] J. M. Ponte, and W. B. Croft, "A language modeling approach to information retrieval", In Proceedings of the 21st Annual international ACM SIGIR Conference on Research and Development in information Retrieval, 1998.
- [66] H. Turtle, and W.B. Croft, "Evaluation of an Inference Network-Based Retrieval Model", ACM Transactions on Information System, Volume 9, Issue 3, pages 187-222, 1991.
- [67] D. Metzler, and W.B. Croft, "Combining the Language Model and Inference Network Approaches to Retrieval", Information Processing and Management Special Issue on Bayesian Networks and Information Retrieval, Volume 40, Issue 5, pages 735-750, 2004.

- [68] D. Metzler, T. Strohman, H. Turtle, and W.B. Croft, "Indri at TREC 2004: Terabyte Track", In Online Proceedings of 2004 Text Retrieval Conference, 2004.
- [69] Metzler, D. and Croft, W.B., "Combining the Language Model and Inference Network Approaches to Retrieval," Information Processing and Management Special Issue on Bayesian Networks and Information Retrieval, pages 735-750, 2004.
- [70] <http://ciir.cs.umass.edu/~metzler/indriquerylang.html>
- [71] N. Eiron, and K. S. McCurley, "Analysis of Anchor Text for Web Search", In Proceedings of the 26th annual international ACM SIGIR conference on Research and development in information retrieval, pages 459-460, 2003.
- [72] J.A. Aslam and M. Montague, "Models for Metasearch", In Proceedings of the 24th Annual International ACM SIGIR Conference on Research and Development in Information Retrieval, pages 276-284, 2001.

APPENDICES

A. Top 10 Precision

Method	Cosine Similarity Model	Okapi Model	TFIDF Model	Method	Indri Model
<i>ori</i>	0.28888	0.40708	0.19963	<i>indri_ori</i>	0.42238
<i>anc</i>	0.24846	0.31271	0.29158	<i>indri_log</i>	0.27471
<i>anc+ori</i>	0.31354	0.44375	0.21275	<i>indri_anc</i>	0.30329
<i>anc+ori+log_0</i>	0.31988	0.44838	0.21921	<i>indri_334</i>	0.37263
<i>anc+ori+log_3</i>	0.31775	0.45033	0.22408	<i>indri_406</i>	0.36800
<i>log</i>	0.30571	0.25183	0.24775	<i>indri_415</i>	0.35171
<i>log_0</i>	0.27696	0.27179	0.25421	<i>indri_424</i>	0.35096
<i>log_3</i>	0.31725	0.31379	0.27271	<i>indri_433</i>	0.34733
<i>all_334</i>	0.35338	0.34075	0.29029	<i>indri_442</i>	0.37413
<i>all_406</i>	0.32996	0.35763	0.24542	<i>indri_451</i>	0.37421
<i>all_415</i>	0.34538	0.38192	0.25158	<i>indri_460</i>	0.44713
<i>all_424</i>	0.35513	0.38946	0.25104	<i>indri_505</i>	0.36346
<i>all_433</i>	0.34788	0.39338	0.25733	<i>indri_514</i>	0.35929
<i>all_442</i>	0.33688	0.39500	0.27483	<i>indri_523</i>	0.35175
<i>all_451</i>	0.30029	0.39071	0.28054	<i>indri_532</i>	0.35475
<i>all_460</i>	0.28596	0.39500	0.26108	<i>indri_541</i>	0.37608
<i>all_505</i>	0.31283	0.37267	0.23392	<i>indri_550</i>	0.45658
<i>all_514</i>	0.34288	0.39771	0.23500	<i>indri_604</i>	0.36517
<i>all_523</i>	0.34008	0.39446	0.24254	<i>indri_613</i>	0.34971
<i>all_532</i>	0.34779	0.41213	0.24704	<i>indri_622</i>	0.36196
<i>all_541</i>	0.33225	0.42429	0.24029	<i>indri_631</i>	0.38113
<i>all_550</i>	0.30175	0.40625	0.25383	<i>indri_640</i>	0.45700
<i>all_604</i>	0.31554	0.37108	0.21750	<i>indri_703</i>	0.36946
<i>all_613</i>	0.32742	0.40225	0.22792	<i>indri_712</i>	0.35967
<i>all_622</i>	0.33479	0.42025	0.23088	<i>indri_721</i>	0.37871
<i>all_631</i>	0.34125	0.43392	0.23100	<i>indri_730</i>	0.44754
<i>all_640</i>	0.32858	0.43467	0.22354	<i>indri_802</i>	0.37104
<i>all_703</i>	0.30025	0.38033	0.20938	<i>indri_811</i>	0.36725
<i>all_712</i>	0.32246	0.42696	0.20717	<i>indri_820</i>	0.43396
<i>all_721</i>	0.32454	0.43329	0.22071	<i>indri_all</i>	0.45588
<i>all_730</i>	0.32713	0.44013	0.22388		
<i>all_802</i>	0.30946	0.40608	0.20525		
<i>all_811</i>	0.31221	0.43546	0.20721		
<i>all_820</i>	0.31817	0.43429	0.21338		

B. R-precision

Method	Cosine Similarity Model	Okapi Model	TFIDF Model	Method	Indri Model
<i>ori</i>	0.28033	0.40217	0.18650	<i>indri_ori</i>	0.39929
<i>anc</i>	0.26625	0.29117	0.22238	<i>indri_log</i>	0.26442
<i>anc+ori</i>	0.31550	0.44713	0.21525	<i>indri_anc</i>	0.30088
<i>anc+ori+log_0</i>	0.32546	0.45154	0.22946	<i>indri_334</i>	0.38029
<i>anc+ori+log_3</i>	0.33071	0.44842	0.23600	<i>indri_406</i>	0.33367
<i>log_3</i>	0.26638	0.23525	0.22638	<i>indri_424</i>	0.34488
<i>log_0</i>	0.14013	0.14158	0.12508	<i>indri_433</i>	0.35396
<i>all_334</i>	0.39221	0.34208	0.28242	<i>indri_442</i>	0.36546
<i>all_406</i>	0.34075	0.35600	0.24600	<i>indri_460</i>	0.46579
<i>all_424</i>	0.38238	0.39604	0.26475	<i>indri_505</i>	0.33358
<i>all_433</i>	0.38883	0.39596	0.27133	<i>indri_523</i>	0.34258
<i>all_442</i>	0.36992	0.38804	0.28058	<i>indri_532</i>	0.34971
<i>all_460</i>	0.32692	0.41213	0.26254	<i>indri_550</i>	0.45383
<i>all_505</i>	0.32404	0.36771	0.23129	<i>indri_604</i>	0.33454
<i>all_523</i>	0.36600	0.39717	0.24900	<i>indri_613</i>	0.33879
<i>all_532</i>	0.39183	0.41996	0.26046	<i>indri_622</i>	0.35388
<i>all_550</i>	0.33358	0.42933	0.25242	<i>indri_631</i>	0.37263
<i>all_604</i>	0.33992	0.38004	0.22242	<i>indri_640</i>	0.44504
<i>all_613</i>	0.35258	0.41842	0.22625	<i>indri_703</i>	0.34475
<i>all_622</i>	0.36679	0.42413	0.24042	<i>indri_712</i>	0.34829
<i>all_631</i>	0.37058	0.44625	0.24975	<i>indri_721</i>	0.36242
<i>all_640</i>	0.35038	0.44842	0.25029	<i>indri_730</i>	0.42475
<i>all_703</i>	0.31600	0.38846	0.21550	<i>indri_802</i>	0.35142
<i>all_712</i>	0.35258	0.43563	0.21267	<i>indri_811</i>	0.34946
<i>all_721</i>	0.34733	0.44971	0.22625	<i>indri_820</i>	0.41375
<i>all_730</i>	0.35338	0.44504	0.23525	<i>indri_all</i>	0.46863
<i>all_802</i>	0.31521	0.40671	0.20433		
<i>all_811</i>	0.33188	0.44800	0.20563		
<i>all_820</i>	0.33779	0.43717	0.21571		

C. Average Precision

Method	Cosine Similarity Model	Okapi Model	TFIDF Model	Method	Indri Model
<i>ori</i>	0.276333	0.389458	0.176208	<i>indri_ori</i>	0.378292
<i>anc</i>	0.202833	0.231125	0.182083	<i>indri_log</i>	0.234625
<i>anc+ori</i>	0.302667	0.435083	0.204875	<i>indri_anc</i>	0.259917
<i>anc+ori+log_0</i>	0.31225	0.443	0.211458	<i>indri_334</i>	0.363375
<i>anc+ori+log_3</i>	0.324708	0.4525	0.227167	<i>indri_406</i>	0.337917
<i>log_3</i>	0.228417	0.196875	0.177333	<i>indri_424</i>	0.341792
<i>log_0</i>	0.118125	0.123708	0.106958	<i>indri_433</i>	0.346292
<i>all_334</i>	0.375375	0.343958	0.265458	<i>indri_442</i>	0.355208
<i>all_406</i>	0.34275	0.338375	0.21375	<i>indri_460</i>	0.449417
<i>all_424</i>	0.380917	0.375083	0.233625	<i>indri_505</i>	0.332708
<i>all_433</i>	0.376375	0.372125	0.248083	<i>indri_523</i>	0.335667
<i>all_442</i>	0.366042	0.379667	0.263208	<i>indri_532</i>	0.344458
<i>all_460</i>	0.322333	0.412542	0.251375	<i>indri_550</i>	0.434
<i>all_505</i>	0.333792	0.348208	0.202458	<i>indri_604</i>	0.329167
<i>all_523</i>	0.381458	0.377	0.230542	<i>indri_613</i>	0.326417
<i>all_532</i>	0.378208	0.398208	0.242875	<i>indri_622</i>	0.338
<i>all_550</i>	0.332583	0.435208	0.245	<i>indri_631</i>	0.348042
<i>all_604</i>	0.331625	0.35325	0.205	<i>indri_640</i>	0.418458
<i>all_613</i>	0.368917	0.382375	0.213375	<i>indri_703</i>	0.333125
<i>all_622</i>	0.371167	0.400667	0.221	<i>indri_712</i>	0.331875
<i>all_631</i>	0.369958	0.433875	0.226042	<i>indri_721</i>	0.342292
<i>all_640</i>	0.346292	0.442917	0.227958	<i>indri_730</i>	0.408
<i>all_703</i>	0.3295	0.353417	0.198333	<i>indri_802</i>	0.343292
<i>all_712</i>	0.355292	0.40125	0.204083	<i>indri_811</i>	0.333708
<i>all_721</i>	0.3465	0.427083	0.209667	<i>indri_820</i>	0.390583
<i>all_730</i>	0.347708	0.443625	0.208958	<i>indri_all</i>	0.469
<i>all_802</i>	0.314	0.373375	0.191792		
<i>all_811</i>	0.33175	0.423125	0.19775		
<i>all_820</i>	0.333333	0.430292	0.197875		